

This document was generated on 10/04/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>0836149014</u>			
Status:	Active	Active		
Overview:		High-Density Connectors		angager.
Description:	1.27mm Pitch Commercial Micro-D, PCB Mount, Right-Angle Plug, without Jackposts,			
Decemption	25 Circuits			and a second second
Documents:				
<u>3D Model (PDF)</u>		Product Specification PS-83421-001-001 (PDF)		1200
Drawing (PDF)		RoHS Certificate of Compliance (PDF)		
3D Model		Koris Certificate of Compliance (FDF)		
			Series image	e - Reference only
Comoral			oonoo iinago	
General Product Family		I/O Connectors	EU ELV	
Series		83614	Not Relevant	
Application		Wire-to-Board	Not Relevant	
Comments		830410005 Jackposts can be purchased separately	EU RoHS	China RoHS
Component Type			Compliant	
Overview		Plug Commercial Micro-D High-Density Connectors	REACH SVHC	
Product Name		Commercial Micro-D High-Density Connectors Commercial Micro-D	Not Contained Per -	
		N/A	D(2021)4569-DC (8	
Type UPC		800756436272	July 2021)	
UPC		000750430272	Halogen-Free	
Physical			Status	
Boot Color		N/A	Low-Halogen	
Circuits (Loaded)		25	_	n, please visit <u>Contact US</u>
Circuits (maximum)		25		n, please visit <u>oontaet oo</u>
Durability (mating cy	(cles max)	500	China ROHS	Green Image
Gender		Plug	ELV	Not Relevant
Lock to Mating Part		None	RoHS Phthalates	Not Contained
Material - Plating Mating		Gold]	
Number of Rows		2		
Orientation		Right Angle	Search Parts in this Series	
PC Tail Length		2.79mm	83614 Series	
PCB Locator		Yes	<u>03014</u> Selles	
PCB Retention		Yes		
PCB Thickness - Recommended		1.52mm	Mates With	
Packaging Type		Tube	83424 Cable Asse	embly
Panel Mount		Yes		
Pitch - Mating Interfa	ace	1.27mm		
Pitch - Termination I		1.27mm		
Plating min - Mating		0.381µm		
Polarized to Mating		Yes		
Polarized to PCB		Yes		
Ports		1		
Surface Mount Com	patible (SMC)	No		
Temperature Range - Operating		-40° to +125°C		
Termination Interfac		Through Hole		
Waterproof / Dustpro	oof	No		
Wire Size AWG		N/A		
Electrical				
Current - Maximum	ner Contact	1.0A		
		Full Shield		
Shield Type Shielded		Yes		
Voltage - Maximum		350V AC		

Material Info

Reference - Drawing Numbers Product Specification Sales Drawing

PS-83421-001-001 SD-83611-002-001

This document was generated on 10/04/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Micro-D Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 89076GBEPR
 65-1920-15
 M83513/03-G12N
 M83513/04-G04C
 664020C06F060
 6R2004A30F015
 6R4006A28A120
 703006A13F060

 704002A03F200
 705001A13F120
 7-1532020-5
 748567-1-P
 MDB1-9SH001
 MDM-100PH003L
 MDM-15PBS-L58
 MDM-15PCBRM7T

 MDM-15PH001M7-A174
 MDM-15PH003B-A174
 MDM-15SH003A
 MDM-15SH004B
 MDM-15SH006A-A174
 MDM-15SH048B
 MDM

 25PH003B-A174
 MDM-25SH003F
 MDM-25SH003K
 MDM-31PH003L
 MDM-37PH006L-A174
 MDM-37SH003K
 MDM51PH016FA174

 MDM-51PSF
 MDM-9SH001P
 MDM-9SH006B
 790-027SH-10P4MEP
 790-041PJ-25P2MPA
 790-043PJ-7P7MPB
 791-004SH-66MSA

 7R3A00A19A1201
 7R5006A19A120
 803000C02M020
 803001B02M040
 803001D01M040
 8030N1A09M020
 804001B03M100

 804006B03M100
 804006C02M030
 MLDM2L-21SCBRP-.110
 85043GULSR
 883020E03M030
 883031D01M030
 883033B03M020