

Voltage - Maximum

This document was generated on 07/27/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>0836199010</u>		
Status:	Active		
Overview:		High-Density Connectors	
Description:	Commercial Micro-D High-Density Connectors 1.27mm Pitch Commercial Micro D, Dual Stack, PCB Mount, Right-Angle Plug, 30		7
Description.	Circuits	nerelai miero D, Duar Stack, r OD mount, right Angle r lug, so	Concerne
	Oncons		
Documents:			
3D Model		Product Specification PS-83421-001-001 (PDF)	Constant of the second s
3D Model (PDF)		Packaging Specification PK-83619-008-001 (PDF)	
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	
Diawing (FDF)		Kons Centilicate of Compliance (FDF)	Series image - Reference only
Osmanal			
General Product Family		I/O Connectors	EU ELV
Series		83619	Not Relevant
		Wire-to-Board	
Application Comments		Dual Stack	EU RoHS China RoHS
Component Type		Plug	Compliant
Overview		Commercial Micro-D High-Density Connectors	REACH SVHC
Product Name		Commercial Micro-D High-Density Connectors	Not Contained Per
Type		N/A	-ED/88/2018 (15
UPC		756054758564	January 2019)
0FC		750054750504	Halogen-Free
Physical			<u>Status</u>
Boot Color		N/A	Low-Halogen
Circuits (Loaded)		30	For more information, please visit Contact US
Circuits (maximum)		30	
Durability (mating cycle	es max)	500	China ROHS Green Image
Gender	,	Plug	ELV Not Relevant
Lock to Mating Part		Yes	RoHS Phthalates Not Contained
Material - Plating Matin	g	Gold	
Net Weight		42.506/g	
Number of Rows		2	Search Parts in this Series
Orientation		Right Angle	83619 Series
PC Tail Length		2.79mm	
PCB Locator		Yes	Mates With
PCB Retention		Yes	83422 Cable Assembly
PCB Thickness - Recommended		1.52mm	
Packaging Type		Tube	
Panel Mount		Yes	
Pitch - Mating Interface		1.27mm	
Pitch - Termination Inte	erface	1.27mm	
Plating min - Mating		0.381µm	
Polarized to Mating Par	rt	Yes	
Polarized to PCB		Yes	
Ports		2	
Surface Mount Compat	· ,	No	
Temperature Range - C		-40° to +125°C	
Termination Interface: S		Through Hole	
Waterproof / Dustproof		No	
Wire Size AWG		N/A	
Electrical			
Current - Maximum per	Contact	1.0A	
Shield Type		Full Shield	
Shielded		Yes	

350V AC

Material Info

Reference - Drawing Numbers Packaging Specification Product Specification Sales Drawing

PK-83619-008-001 PS-83421-001-001 SD-83619-006

This document was generated on 07/27/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Micro-D Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 89076GBEPR
 65-1920-15
 M83513/03-G12N
 M83513/04-E15N
 M83513/04-G04C
 664020C06F060
 6R2004A30F015
 6R4006A28A120

 703006A13F060
 704002A03F200
 705001A13F120
 7-1532020-5
 748567-1-P
 MDB1-9SH001
 MDM-100PH003L
 MDM-15PBS-L58
 MDM

 15PCBRM7T
 MDM-15PH001M7-A174
 MDM-15PH003B-A174
 MDM-15SH003A
 MDM-15SH004B
 MDM-15SH006A-A174
 MDM

 15SH048B
 MDM-25PH003B-A174
 MDM-25SH003F
 MDM-25SH003K
 MDM-31PH003L
 MDM-37PH006L-A174
 MDM-37SH003K

 MDM51PH016FA174
 MDM-51PSF
 MDM-9SH001P
 MDM-9SH006B
 790-027SH-10P4MEP
 790-041PJ-25P2MPA
 790-043PJ-7P7MPB

 791-004SH-66MSA
 7R3A00A19A1201
 7R5006A19A120
 803000C02M020
 803001B02M040
 803001D01M040
 8030N1A09M020

 804001B03M100
 804006C02M030
 MLDM2L-21SCBRP-.110
 85043GULSR
 883021E03M030
 883031D01M030