

## This document was generated on 11/07/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

	Part Number:	0845250009			
Status:		Active			-
Overview: ML-XT Sealed Connection System					2
	Description: ML-XT / XRC Female (Socket) Te Diameter 1.40 to 2.16mm, Tin		tet) Terminal, 16 to 18 AWG, Terminal Size 16, Insulation	-	8
	Documents:			and the second second	
Drawing (PDF)		Packaging Specification 845250001-K (PDF)		1 miles	
	Product Specification PS-84501-001-001 (PDF) Application Specification 845241000-A (PDF)		<u>RoHS Certificate of Compliance (PDF)</u> Product Literature (PDF)		
				- Series image - Reference only	
	General				
	Product Family		Crimp Terminals	EU ELV	
	Series Application		<u>84525</u> Power, Wire-to-Wire	Not Relevant	
Crimp Quality Equip		ent	Yes	EU RoHS	China RoHS
	Overview		ML-XT Sealed Connection System	Compliant	
	Product Literature Order No Product Name		987651-0201	REACH SVHC	
			ML-XT, XRC	Not Contained Per -	
	UPC		78172511502	ED/71/2019 (16 July 2019)	
	Physical			Halogen-Free	
	Gender		Female	Status	
	Material - Metal		Copper Alloy	Low-Halogen	
	Material - Plating Mating		Tin over Nickel	For more information	, please visit <u>Contact US</u>
	Net Weight		0.362/g		0
	Packaging Type	01.14	Reel	China ROHS ELV	Green Image Not Relevant
	Termination Interface: Style Wire Insulation Diameter		Crimp or Compression 1.40-2.16mm	RoHS Phthalates	Not Contained
	Wire Size AWG		1.40-2.16000		
	Wire Size mm <sup>2</sup>		0.82-1.31		
	Material Info			Search Parts in this Series 84525 Series	
	Reference - Drawing		0.450.44000 A		
	Application Specification		845241000-A	Application Toolir	
	Packaging Specification Product Specification	UII	845250001-K PS-84501-001-001		ons and manuals are
	Sales Drawing		845250010-000	Crimp Height Spec	the products below.
'	Calco Draming			contained in the Ap	
				Specification docu	
				Global	
				Description	Product #
				Hand Crimp Tool	<u>638115500</u>
				for 3.56mm Crimp	
				Terminal, Pin FineAdjust	629691000
				Applicator, Insulation	<u>638681000</u> on
				Range 1.40–1.79m	
				FineAdjust	638681100
				Applicator Inculation	

Applicator, Insulation Range 1.79-2.16mm

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Standard Circular Contacts category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 RC16M23J
 133780-1
 RM20M13D28
 RM24M9D28
 RMMX110-1D28
 MS3474W10-6P L/C
 ELVP16100E
 164-901-CD
 EN3545007SCE

 BV002BSQ20049CZ
 BV002SSQ160404CZ
 BV002SSQ200404CZ
 1900ND05S1B00B
 192900-0061
 192900-0427
 192900-0430
 192900 

 0575
 166566-1
 1900ND04S1X00D
 192900-0058
 ST-JL05-16S-C3-100
 ST-JL05-20S-C1-100
 ST-JL05-20S-C2-100
 T01-CRIMP-S03
 APK 

 SA16A07-002
 27963-15T12
 CONT-JL05-08S-C2-10
 CONT-JL05-12S-C1-10
 RC16M-23T
 RFD26L-1D28
 BV002ASJ16049CW
 JN1-22 

 20S-R-PKG100
 031-50565
 SJS861301M
 ST-JL05-16S-C1-100
 ST-JL05-20P-C1-100
 82911466K
 192991-0087
 192900-0570
 44-104 

 10003-02
 T3P16FC3LZ
 ST-JL05-16S-C2-3500
 ZP-4016-10NF
 CONT-JL05-12P-C1-10
 RM20M12G8D28
 031-50676
 12115010110

 RJFTVC2MG
 CAP-DACMDPC2
 031-50675-002

 12115010110