

## This document was generated on 12/14/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 084729 Status: Active	2 <u>90009</u> e		
Overview: Sealed In	Industrial USB Solutions		
Description: Sealed In	Industrial USB 2.0 Type A Panel Mount PCB Receptacle		
Documents:			
<u>3D Model (PDF)</u>	Product Specification PS-84727-002-001 (PDF)		
Drawing (PDF) 3D Model	RoHS Certificate of Compliance (PDF)		
General		— Series image	e - Reference only
Product Family	I/O Connectors		
Series	<u>84729</u>	EU ELV	
Application	Wire-to-Board	Not Relevant	
Component Type	I/O Housing		
Overview	Sealed Industrial USB Solutions	EU RoHS	<u>China RoHS</u>
Product Name	Industrial USB	Compliant	
Туре	A	REACH SVHC	
UPC	822350592383	Not Contained Per -	
	···	D(2021)4569-DC (8	,
Physical		July 2021)	
Circuits (Loaded)	4	Halogen-Free	
Circuits (maximum)	4	Status	
Color - Resin	Black	Not Low-Halogen	
Durability (mating cycles max)	200	· · · · · · · · · · · · · · · · · · ·	n, please visit <u>Contact US</u>
Gender	Receptacle		
Keying to Mating Part	N/A	China ROHS	Not Relevant
Lock to Mating Part	Yes	ELV	Not Relevant
Material - Plating Mating	N/A	RoHS Phthalates	Not Contained
Material - Resin	Nylon, Polyester	ZZCERT_CE -	CER_4000380999_00_00
Net Weight	9.660/g	Declaration of	
Number of Rows	1.000/g	Conformity	
Orientation	Vertical	,	
PC Tail Length	2.90mm		
PCB Locator	Yes		·
PCB Retention	Yes	Search Parts in t	his Series
PCB Retention PCB Thickness - Recommended		<u>84729</u> Series	
Packaging Type Panel Mount	Bag Yes	Mates With	
			lustrial USB 2.0 Type A
Pitch - Mating Interface	2.00mm	Plugs	
Pitch - Termination Interface	2.00mm		1
Polarized to Mating Part	Yes		
Polarized to PCB	Yes		
Ports	1 • • • • • • • • • • • • • • • • • • •		
Surface Mount Compatible (SMC			
Temperature Range - Operating			
Termination Interface: Style	N/A		
Waterproof / Dustproof	Yes		
Waterproof / Dustproof Type	IP67		
Electrical	1.04		
Current - Maximum per Contact	1.0A		

Grounding to Panel Shield Type Shielded Voltage - Maximum

N/A Full Shield Yes 30V AC (RMS) Material Info

**Reference - Drawing Numbers** Product Specification Sales Drawing

PS-84727-002-001 SD-84729-004-000

## This document was generated on 12/14/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for USB Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

65-647-8-BK-BU 950 952 E8144-B01021-L A-USB A-LP-SMT-C MUSBA511N5 MUSBD11135 217450-1 CA 6 W LD KMBVX-TH-5S-B30 896-30-004-00-00000 KUSBVX-BS1N-W30 KUSBX-AP-KIT-SCBLK KUSBX-AS2N-W KUSBX-SMT2AP1S-W KUSBX-SMT2AP1S-W30 935 957 30-498-6 17-210051 1734082-1 30-1574 30-470 30-489 30-541 30-572-3 MAB 8 SN V A-USB A-2P-C MIKROE-1451 USBFTV2PEM2G USBFTVC6ZN KUSBX-AS2N-W30 KUSBX-SLAS1N-W KUSBX-SMT-AS1N-W30 4689-1 1-1734084-2 E8110-001-01 MUSBA81130 33UBARS1-04SW11 33UBAR-04SW11 USBF21ZNSCC USBBFTV6ZC 10135326-001LF M9177/3-1 USB-A-S-F-B-VT 925 4198 690-024-633-031 KUSBEX-BSFS1N-W USBFTVC6MRG