

This document was generated on 08/31/2021

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0855065002

Status: Active

Overview: Magnetic and Modular Jacks/Plugs

**Description:** Modular Jack, Cat5e, Vertical, Top Entry, Through Hole, 8/8, High Profile, no Ribs, Tray

**Documents:** 

3D Model Packaging Specification PK-95022-001 (PDF)

<u>Drawing (PDF)</u> <u>RoHS Certificate of Compliance (PDF)</u>

Product Specification PS-85506-001-001 (PDF) Product Literature (PDF)

**Agency Certification** 

CSA LR19980 UL E107635

General

Product Family Modular Jacks/Plugs

Series 85506

Comments Reflow capable
Component Type PCB Jack
Magnetic No

Overview <u>Magnetic and Modular Jacks/Plugs</u>

Performance Category 5e Power over Ethernet (PoE) N/A

Product Name Modular Jack 8/8, RJ45

UPC 800756825564

**Physical** 

Boot Color N/A
Color - Resin Black
Durability (mating cycles max) 2500
Flammability 94V-0
Inverted / Top Latch No

Jack Height 16.30mm Lightpipes/LEDs None

Material - Metal Phosphor Bronze

Material - Plating Mating Gold over Palladium Nickel

Material - Plating Termination Ti

Material - Resin High Temperature Thermoplastic

Net Weight 3.100/g

Orientation Vertical (Top Entry)

PCB Locator Yes
PCB Retention Yes
PCB Thickness - Recommended 1.57mm
Packaging Type Tray
Pitch - Mating Interface 1.02mm
Pitch - Termination Interface 1.27mm


Plating min - Mating 0.051µm, 1.016µm

Plating min - Termination 1.905µm
Port Configuration 1x1
Positions / Loaded Contacts 8/8
Surface Mount Compatible (SMC) No

Temperature Range - Operating -40° to +85°C
Termination Interface: Style Through Hole

Waterproof / Dustproof No Wire/Cable Type N/A

**Electrical** 



**EU ELV Not Relevant** 

EU RoHS China RoHS

Compliant REACH SVHC Not Contained Per -D(2021)4569-DC (8 July 2021)

<u>Halogen-Free</u>

**Status** 

**Not Low-Halogen** 

For more information, please visit Contact US

China ROHS Green Image
ELV Not Relevant
RoHS Phthalates Not Contained

Search Parts in this Series

85506 Series

**Mates With** 

95043 Modular Plug, Short Body

Current - Maximum per Contact 1.5A
Shielded No
Voltage - Maximum 125V DC

**Material Info** 

**Reference - Drawing Numbers** 

Packaging Specification PK-95022-001
Product Specification PS-85506-001-001
Sales Drawing SD-85506-501-001

This document was generated on 08/31/2021

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

8949-H88/06BLKA/SN 74441-0010/BKN MP1010RX-1000 MP44RX-1000 PHP-6P6C-5 GAX-3-66 GAX-8-62 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDCX-PN-66 GDLX-A-66 GDLX-N-66 GDLX-S-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-N-1010M-BLK GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT4-N-88 GPX-2-64 GSGX-N-2-88 GSGX-N-4-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05-50 GSX-NS-88-3.05-50 GSX-NS-88-3.68 PT-108A-8C-UL PT-J951-8C PTS-J531-8CS-50UL 1-1775629-2 A-2014-0-4 GWLX-S-88-GR GWLX-S9-88-YG DC-1021-8-WH-6 1300530003 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1413235 MP88X-1000 MPS88RX-5000 MRJR-5481-0F2 E5288-S000K3-L E5908-15A242-L