

## This document was generated on 08/26/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0855105027			
Status: Active		EU ELV	
Overview:		Not Relevant	
	, Top Entry, Surface Mount, 6/6, Solder Tabs, 22" Reel	EU RoHS	China RoHS
Agency Certification		Compliant REACH SVHC	
UL	E107635	Not Contained Per	_
OL	E107033	D(2020)9139-DC (1	
General			9
Product Family	Modular Jacks/Plugs	Jan 2021)	
Series	85510	Halogen-Free	
Comments	Reflow Capable, Small Panel Cutout	Status	
Component Type	PCB Jack	Low-Halogen	
Magnetic	No	For more informatio	n, please visit <u>Contact l</u>
Overview	modular_plugs_jacks	China ROHS	Green Image
Performance Category	3	ELV	Not Relevant
<b>3</b> ,	5 N/A	RoHS Phthalates	Not Contained
Power over Ethernet (PoE)		RONS Phinalales	Not Contained
Product Name	Modular Jack 6/6		
UPC	800756822402		
Physical		Search Parts in this Series	
Boot Color	N/A	85510 Series	
Color - Resin	Black		
Durability (mating cycles max)	2500	Mates With	
Flammability	94V-0	<u>90075</u> Modular P	lug
Inverted / Top Latch	No		
Jack Height	15.70mm		
Lightpipes/LEDs	None		
Material - Metal	Copper Alloy		
Material - Plating Mating	Gold over Palladium Nickel		
Material - Plating Termination	Tin		
Material - Resin	High Temperature Thermoplastic		
Net Weight	2.416/g		
Orientation	Vertical (Top Entry)		
PCB Locator	No		
PCB Retention	Yes		
Packaging Type	Embossed Tape on Reel		
Pitch - Mating Interface	1.02mm		
Pitch - Termination Interface	1.27mm		
Plating min - Mating	0.051µm, 1.016µm		
Plating min - Termination	1.905µm		
Port Configuration	1x1		
Positions / Loaded Contacts	6/6		
Surface Mount Compatible (SMC)	Yes		
Temperature Range - Operating	-40° to +85°C		
Termination Interface: Style	Surface Mount		
Waterproof / Dustproof	No		
Wire/Cable Type	N/A		
Electrical	<i>.</i> <b>- .</b>		
Current - Maximum per Contact	1.5A		
Shielded	No		
Voltage - Maximum	125V DC		
Solder Process Data			
Duration at Max. Process Temperature (secon			
Lead-freeProcess Capability Max. Cycles at Max. Process Temperature	REFLOW		
Blow Chalco of Mary Linescon Temperature	003		

## **Material Info**

**Reference - Drawing Numbers** Application Specification Packaging Specification Product Specification Sales Drawing

AS-85513-001-001 PK-85510-003 PS-95503-001-001 SD-85510-002-001

## This document was generated on 08/26/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

8949-H88/06BLKA/SN 74441-0010/BKN MP1010RX-1000 MP44RX-1000 PHP-6P6C-5 GAX-3-66 GAX-8-62 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDCX-PN-66 GDLX-A-66 GDLX-N-66 GDLX-S-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-N-1010M-BLK GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT4-N-88 GPX-2-64 GSGX-N-2-88 GSGX-N-4-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05 GSX-NS2-88-3.05 O GSX-NS-88-3.05-50 PT-108A-8C-UL PT-J951-8C PTS-J531-8CS-50UL 1-1775629-2 A-2014-0-4 GWLX-S-88-GR GWLX-S9-88-YG DC-1021-8-WH-6 1300530003 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1413235 MP88X-1000 MPS88RX-5000 MRJR-5481-0F2 E5288-S000K3-L E5908-15A242-L 155302-001