

Shielded

Voltage - Maximum

## This document was generated on 01/03/2022 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0855105118			
				•
Status: Active				
Overview:	Overview: Magnetic and Modular Jacks/Plugs			
Description: Modular Jack, Vertical, Top Entr		Entry, Surface Mount, 6/4, Solder Tabs, Pick-and-Place	the the	
	Polyimide Tape, 13" Reel			9842
			-	
Documents:				
<u> 3D Model (PDF)</u>		Application Specification AS-85513-001-001 (PDF)		
<u>3D Model</u>		Packaging Specification PK-85510-002 (PDF)		
Drawing (PDF)		Datasheet (PDF)		
Product Specification	on PS-95503-001-001 (PDF)	RoHS Certificate of Compliance (PDF)	Series imag	ge - Reference only
Osmanal				
General Broduct Family		Madular Jaaka/Dluga	EU ELV	
Product Family		Modular Jacks/Plugs	Not Relevant	
Series		85510 Rofley Canable, Small Banal Cutout	EU RoHS	China RoHS
Comments		Reflow Capable, Small Panel Cutout	Compliant	
Component Type		PCB Jack	REACH SVHC	
Magnetic Overview		No Magnetia and Madular, Jacks/Dluga	Not Contained Per	_
		Magnetic and Modular Jacks/Plugs	D(2021)4569-DC (	
Performance Category		3 N/A	July 2021)	•
Power over Ethernet (PoE) Product Name			Halogen-Free	
		Modular Jack 6/4	Status	
UPC		887191485218	Low-Halogen	
Physical				on, please visit <u>Contact US</u>
Boot Color		N/A		on, picase visit <u>contact 05</u>
Color - Resin		Black	China ROHS	Green Image
Durability (mating c	cycles max)	2500	ELV	Not Relevant
Inverted / Top Latch		No	RoHS Phthalates	Not Contained
Jack Height		15.70mm		
Lightpipes/LEDs		None		
Material - Metal		Copper Alloy	Counch Danta in this Carios	
Material - Plating Mating		Gold over Palladium Nickel	Search Parts in this Series	
Material - Plating Termination		Tin	85510 Series	
Material - Resin		High Temperature Thermoplastic		
Net Weight		2.600/g	Mates With	
Orientation		Vertical (Top Entry)	90075 Modular Plug	
PCB Locator		No		
PCB Retention		Yes	Use With	
Packaging Type		Embossed Tape on Reel	90075 Modular Plugs	
Pitch - Mating Inter	face	1.02mm	, L	
Pitch - Termination		1.27mm		
Plating min - Mating		0.051µm, 1.016µm		
Plating min - Termination		1.905µm		
Port Configuration		1x1		
Positions / Loaded Contacts		6/4		
Surface Mount Compatible (SMC)		Yes		
Temperature Range - Operating		-40° to +85°C		
Termination Interfa		Surface Mount		
Waterproof / Dustproof		No		
Wire/Cable Type		N/A		
Electrical				
Current - Maximum	n per Contact	1.5A		
Shielded		No		

No 125V DC

## Material Info

**Reference - Drawing Numbers** Application Specification Packaging Specification Product Specification Sales Drawing

AS-85513-001-001 PK-85510-002 PS-95503-001-001 SD-85510-002-001

This document was generated on 01/03/2022 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

8949-H88/06BLKA/SN 74441-0010/BKN MP1010RX-1000 MP44RX-1000 PHP-6P6C-5 GAX-3-66 GAX-8-62 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDLX-A-66 GDLX-N-66 GDLX-S-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-N-1010M-BLK GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT4-N-88 GPX-2-64 GSGX-N-2-88 GSGX-N-4-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05 GSX-NS-88-3.05-50 GSX-NS-88-3.05 GSX-NS-88-3.05 GSX-NS2-88-3.05 GSX-NS-88-3.05-50 GSX-NS-88-3.05-50 GSX-NS-88-3.68 PT-108A-8C-UL PT-J951-8C PTS-J531-8CS-50UL 1-1775629-2 A-2014-0-4 GWLX-S-88-GR GWLX-S9-88-YG DC-1021-8-WH-6 1300530003 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1413235 MP88X-1000 MPS88RX-5000 MRJR-5481-0F2 E5288-S000K3-L E5908-15A242-L