

Shielded

Voltage - Maximum

This document was generated on 01/04/2022 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>0855105119</u>			
Status:				
Oversieve				
• • • • • • • • • • • • • • • • • • • •				
Description:				
	FolyInide Tape, 13 Reel			
Documents:				
3D Model		Application Specification AS-85513-001-001 (PDF)		
Drawing (PDF)		Packaging Specification PK-85510-002 (PDF)		
3D Model (PDF)		Datasheet (PDF)	4	
· · ·	tion PS-95503-001-001 (PDF)	RoHS Certificate of Compliance (PDF)	Series ima	ge - Reference only
General			EU ELV	
Product Family		Modular Jacks/Plugs	Not Relevant	
Series		85510		
Comments		Reflow Capable, Small Panel Cutout	EU RoHS	China RoHS
Component Type		PCB Jack	Compliant	
Magnetic		No	REACH SVHC	
Overview		Magnetic and Modular Jacks/Plugs	Not Contained Per	r -
Performance Category		3	D(2021)4569-DC	(8
Power over Ethernet (PoE)		N/A	July 2021)	
Product Name		Modular Jack 6/6	Halogen-Free	
UPC		887191485195	<u>Status</u>	
			Low-Halogen	
Physical			For more informat	ion, please visit <u>Contact Us</u>
Boot Color		N/A		
Color - Resin		Black	China ROHS	Green Image
Durability (mating	cycles max)	2500	ELV	Not Relevant
Inverted / Top Late	ch	No	RoHS Phthalates	Not Contained
Jack Height		15.70mm		
Lightpipes/LEDs		None		
Material - Metal		Copper Alloy	Search Parts in this Series	
Material - Plating Mating		Gold over Palladium Nickel	85510 Series	
Material - Plating	Termination	Tin		
Material - Resin		High Temperature Thermoplastic	Metee With	
Net Weight		2.416/g	Mates With	
Orientation		Vertical (Top Entry)	90075 Modular Plug	
PCB Locator		No		
PCB Retention		Yes	Use With	
Packaging Type		Embossed Tape on Reel	90075 Modular Plugs	
Pitch - Mating Inte		1.02mm		
Pitch - Termination		1.27mm		
Plating min - Matir		0.051µm, 1.016µm		
Plating min - Term		1.905µm		
Port Configuration		1x1		
Positions / Loadec		6/6		
Surface Mount Co		Yes		
Temperature Rang		-40° to +85°C		
Termination Interfa		Surface Mount		
Waterproof / Dustr	proof	No		
Wire/Cable Type		N/A		
Electrical				
Current - Maximur	n per Contact	1.5A		
Shielded		No		

No 125V DC

Material Info

Reference - Drawing Numbers Application Specification Packaging Specification Product Specification Sales Drawing

AS-85513-001-001 PK-85510-002 PS-95503-001-001 SD-85510-002-001

This document was generated on 01/04/2022 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

8949-H88/06BLKA/SN 74441-0010/BKN MP1010RX-1000 MP44RX-1000 PHP-6P6C-5 GAX-3-66 GAX-8-62 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDLX-A-66 GDLX-N-66 GDLX-S-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-N-1010M-BLK GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT4-N-88 GPX-2-64 GSGX-N-2-88 GSGX-N-4-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05 GSX-NS-88-3.05-50 GSX-NS-88-3.05 GSX-NS-88-3.05 GSX-NS2-88-3.05 GSX-NS-88-3.05-50 GSX-NS-88-3.05-50 GSX-NS-88-3.68 PT-108A-8C-UL PT-J951-8C PTS-J531-8CS-50UL 1-1775629-2 A-2014-0-4 GWLX-S-88-GR GWLX-S9-88-YG DC-1021-8-WH-6 1300530003 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1413235 MP88X-1000 MPS88RX-5000 MRJR-5481-0F2 E5288-S000K3-L E5908-15A242-L