

This document was generated on 12/20/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 085513511	<u>6</u>	
Status: Active		
Overview: Magnetic and M	Iodular Jacks/Plugs	
	/ertical, Top Entry, Surface Mount, 4/4, Low Profile, Pick-and-Place	
Polyimide Tape		=
r oryinnide Tape		
Documents:	Draduct Creatives DC 05542 002 004 (DDE)	
Drawing (PDF)	Product Specification PS-85513-002-001 (PDF)	
<u>3D Model</u>	Datasheet (PDF)	2,23
<u>3D Model (PDF)</u>	RoHS Certificate of Compliance (PDF)	
		- Series image - Reference only
General		
Product Family	Modular Jacks/Plugs	EU ELV
Series	<u>85513</u>	Not Relevant
Comments	Reflow Capable, Small Panel Cutout	
Component Type	PCB Jack	EU RoHS China RoHS
Magnetic	No	Compliant
Overview	Magnetic and Modular Jacks/Plugs	REACH SVHC
Performance Category	3	Not Contained Per -
Power over Ethernet (PoE)	N/A	D(2021)4569-DC (8
Product Name	Modular Jack 4/4	July 2021)
UPC	887191677675	Halogen-Free
		Status
Physical		Low-Halogen
Boot Color	N/A	For more information, please visit <u>Contact US</u>
Color - Resin	Black	To more mornation, piease visit <u>contact oc</u>
Durability (mating cycles max)	2500	China ROHS Green Image
Inverted / Top Latch	No	ELV Not Relevant
Jack Height	12.70mm	RoHS Phthalates Not Contained
Lightpipes/LEDs	None	
Material - Metal		
	Copper Alloy Gold over Palladium Nickel	
Material - Plating Mating		Search Parts in this Series
Material - Plating Termination	Tin	85513 Series
Material - Resin	High Temperature Thermoplastic	
Net Weight	2.050/g	Mates With
Orientation	Vertical (Top Entry)	<u>90075</u> Modular Plug
PCB Locator	No	
PCB Retention	Yes	
Packaging Type	Embossed Tape on Reel	Use With
Pitch - Mating Interface	1.02mm	90075 Modular Plugs
Pitch - Termination Interface	1.27mm	
Plating min - Mating	0.051µm, 1.016µm	
Plating min - Termination	1.905µm	
Port Configuration	1x1	
Positions / Loaded Contacts	4/4	
Surface Mount Compatible (SMC)	Yes	
Temperature Range - Operating	-40° to +85°C	
Termination Interface: Style	Surface Mount	
Waterproof / Dustproof	No	
Wire/Cable Type	N/A	
Electrical		
Current - Maximum per Contact	1.5A	
Shielded	No	
Valtaga Maximum		

125V DC

Voltage - Maximum

Reference - Drawing Numbers Product Specification Sales Drawing

PS-85513-002-001 SD-85513-010-001

This document was generated on 12/20/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

8949-H88/06BLKA/SN 74441-0010/BKN MP1010RX-1000 MP44RX-1000 PHP-6P6C-5 GAX-3-66 GAX-8-62 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDLX-A-66 GDLX-N-66 GDLX-S-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-N-1010M-BLK GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT4-N-88 GPX-2-64 GSGX-N-2-88 GSGX-N-4-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05 GSX-NS-88-3.05-50 GSX-NS-88-3.05 GSX-NS-88-3.05 GSX-NS2-88-3.05 GSX-NS-88-3.05-50 GSX-NS-88-3.05-50 GSX-NS-88-3.68 PT-108A-8C-UL PT-J951-8C PTS-J531-8CS-50UL 1-1775629-2 A-2014-0-4 GWLX-S-88-GR GWLX-S9-88-YG DC-1021-8-WH-6 1300530003 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1413235 MP88X-1000 MPS88RX-5000 MRJR-5481-0F2 E5288-S000K3-L E5908-15A242-L