

Shielded

Voltage - Maximum

This document was generated on 07/30/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>0857912020</u>		
Status:	Active		
Overview:	Magnetic Jacks		
Description:		ed Gigabit Ethernet 8 Core PoE+ 30W Class 2 Single-Port RJ45	- 210
Description.		n Depth, 3.15mm Phy Pin Length, Right-Angle, Inverted Profile,	
		on-LED, Standard Temperature, Tray	
Documents:			
3D Model		Packaging Specification PK-85759-001-001 (PDF)	
Drawing (PDF)		Datasheet (PDF)	
<u>3D Model (PDF)</u>		RoHS Certificate of Compliance (PDF)	Series image - Reference only
. ,	ion PS-85791-001-001 (P		
-		· · · · · · · · · · · · · · · · · · ·	EU ELV
General			Not Reviewed
Product Family		Modular Jacks/Plugs	
Series		85791	EU RoHS China RoHS
Component Type		PCB Jack	Not Reviewed
Depth		39.00mm	REACH SVHC
Magnetic		Yes	Not Reviewed
Overview		Magnetic Jacks	Halogen-Free
Performance Category		1000Mb	Status
Power over Ethernet (PoE)		PoE+	Not Reviewed
Product Name		Magnetic Jack, MXMag, RJ45	For more information, please visit Contact US
UPC		887191157344	
		007191107044	China ROHS Not Reviewed
Physical			ELV Not Reviewed
Color - Resin		Black	RoHS Phthalates Not Reviewed
Durability (mating cycles max)		750)
Inverted / Top Latch		Yes	
Jack Height		13.87mm	Connete Danta in this Conice
Keying to Mating Part		None	Search Parts in this Series
Lightpipes/LEDs		None	<u>85791</u> Series
Material - Metal		Copper Alloy	
Material - Plating Mating		Gold	Mates With
Material - Plating Termination		Tin	Plugs according to IEC 60603-7
Material - Resin		PBT	,
Net Weight		11.097/g	
Orientation		Right Angle (Side Entry)	
PCB Locator		Yes	
PCB Retention		Yes	
PCB Thickness - Recommended		1.60mm	
Packaging Type		Tray	
Panel Mount		Spring Tabs	
Plating min - Matin	a de la companya de la	0.762µm	
Port Configuration		1x1	
Positions / Loaded		8/8	
		o/o No	
Surface Mount Co		0° to $+70^{\circ}$ C	
Temperature Rang			
Termination Interfa	ace. Style	Through Hole N/A	
Wire/Cable Type		IN/A	
Electrical			
Current - Maximun	n per Contact	1.0A	
Grounding to PCB		Yes	
Grounding to Pane		Yes	
Shielded		Voc	

Yes

60V AC

Material Info

Reference - Drawing Numbers Packaging Specification Product Specification Sales Drawing

PK-85759-001-001 PS-85791-001-001 857910020-000

This document was generated on 07/30/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

8949-H88/06BLKA/SN 74441-0010/BKN MP1010RX-1000 MP44RX-1000 PHP-6P6C-5 GAX-3-66 GAX-8-62 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDCX-PN-66 GDLX-A-66 GDLX-N-66 GDLX-S-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-N-1010M-BLK GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT4-N-88 GPX-2-64 GSGX-N-2-88 GSGX-N-4-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05 GSX-NS2-88-3.05 O GSX-NS-88-3.05-50 PT-108A-8C-UL PT-J951-8C PTS-J531-8CS-50UL 1-1775629-2 A-2014-0-4 GWLX-S-88-GR GWLX-S9-88-YG DC-1021-8-WH-6 1300530003 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1413235 MP88X-1000 MPS88RX-5000 E5288-S000K3-L E5908-15A242-L 155302-001 AX100653