

This document was generated on 09/23/2021

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0876781001

Status: Active

Overview: Serial ATA Connectors

**Description:** 1.27mm Pitch Serial ATA Backplane Receptacle, Through Hole, Vertical, Extended

Height, 0.76µm Gold (Au) Selective, 22 Circuits, Lead-Free

**Documents:** 

<u>3D Model</u> <u>Packaging Specification PK-87678-100-001 (PDF)</u>

Yes

None

Drawing (PDF)

RoHS Certificate of Compliance (PDF)

Product Specification PS-87678-029-001 (PDF)

**Agency Certification** 

CSA LR19980 UL E29179

General

Product Family PCB Receptacles

Series <u>87678</u>

Application Board-to-Board, Signal Overview Serial ATA Connectors

Product Name Serial ATA UPC 822348693399

**Physical** 

(p)ower-(s)ignal Configuration 15p - 7s Circuits (Loaded) 22 Circuits (maximum) 22 Durability (mating cycles max) 500 Flammability 94V-0 Glow-Wire Capable No Guide to Mating Part Yes Lock to Mating Part Yes Material - Metal Copper Material - Plating Mating Gold Material - Plating Termination Tin Net Weight 1.897/g Number of Rows Orientation Vertical PC Tail Length 3.45mm

PCB Thickness - Recommended 0.80mm, 2.50mm

Packaging TypeTrayPitch - Mating Interface1.27mmPlating min - Mating0.762μmPlating min - Termination2.540μmPolarized to Mating PartYesPolarized to PCBYesSurface Mount Compatible (SMC)Yes

Temperature Range - Operating -40° to +105°C

Termination Interface: Style Through Hole - Compliant Pin

**Electrical** 


**PCB Locator** 

**PCB** Retention

Current - Maximum per Contact 1.5A Voltage - Maximum 30V

**Solder Process Data** 

Duration at Max. Process Temperature (seconds) 010



**EU ELV** 

**Not Relevant** 

EU RoHS China RoHS

Compliant REACH SVHC Not Contained Per -D(2021)4569-DC (8 July 2021)

Halogen-Free

**Status** 

Low-Halogen

For more information, please visit Contact US

China ROHS Green Image
ELV Not Relevant
RoHS Phthalates Not Contained

Search Parts in this Series

87678 Series

**Mates With** 

87679, 87799, 87703

SMC&WAVE

Lead-freeProcess Capability
Max. Cycles at Max. Process Temperature 001 Process Temperature max. C 260

### **Material Info**

Reference - Drawing Numbers Electrical Model Document EE-87678-001-001 Packaging Specification PK-87678-100-001 Product Specification PS-87678-029-001 Sales Drawing SD-87678-023-001

This document was generated on 09/23/2021

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

571763P 58098-0628 72.250.1628.2 72.250.2428.2 74720-0505 76.350.0729.0 76871-1403 FCN-244F080-G/1 FCN-260A9920 PCR-E36PM PCS-XE26MA+ G38A71314B 1571250010 157-22500-3 MS3471L14-19P L/C 192991-0703 172501-4002 172501-6002 FCN-260C008-A/L0 FCN-260C024-AL0 FCN-261Z008 2000314-1 200331-1 PCR-E36FC+ PCS-E28FS+ PCS-XE26SLFD+ PCS-XE26SLFD+ PCS-XE26SLFD+ G730VID08BDC24 U90B2054081210 UE86K842720321 38113800006 DP3AR020WQ1R200 Z4.102.0680.0 500-1040 500-1052 500-1054 ZP-4008-66L 0709821002 DX40-20P(55) 5554841-1 MS3474W18-8P-LC\* U90B3054061110 U65-E04-4020 ZPF0000000000097891 747360449 10099439-003C-TRLF 10137239-0021LF E9320-001-01 10137239-0011LF 70289-001LF