

This document was generated on 09/23/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0879450002

Status: Active

Overview: Serial Attached SCSI (SAS) Connectors

Description: 1.27mm Signal Pitch, 0.80mm SCSI Pitch, 1.27mm Power Pitch SAS-2 Receptacle,

Right-Angle, Surface Mount, "Z" Height of 7.07mm, with Straight Solder Tab, 29

Circuits, Lead-Free

Documents:

<u>3D Model</u> <u>Packaging Specification PK-87945-001-001 (PDF)</u>

Drawing (PDF)

RoHS Certificate of Compliance (PDF)

3D Model (PDF)

Agency Certification

CSA LR19980 UL E29179

General

Product Family I/O Connectors

Series <u>87945</u>

Application Board-to-Board

Comments Solder Tab (Blade) hold-down, no pick and place

cap|"Z" Height - 7.07mm

Component Type Receptacle

Overview Serial Attached SCSI (SAS) Connectors

Product Name SAS 6G, SAS-2

Type N/A

UPC 822348850716

Physical

Panel Mount

Boot Color N/A
Circuits (Loaded) 29
Circuits (maximum) 29

Circuits Detail Signal 14, Power 15

Color - ResinBlackDurability (mating cycles max)500Flammability94V-0GenderFemaleKeying to Mating PartYesLock to Mating PartNone

Material - Metal Phosphor Bronze

Material - Plating Mating Gold Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic


Yes

Net Weight 2.644/g Number of Rows 2

Orientation Right Angle
PCB Locator Yes
PCB Retention Yes
PCB Thickness - Recommended 1.60mm
Packaging Type Tray

Pitch - Mating Interface 0.80mm, 1.27mm Pitch - Termination Interface 0.80mm, 1.27mm

Plating min - Mating 0.762µm
Plating min - Termination 2.540µm
Polarized to Mating Part Yes
Polarized to PCB Yes



EU ELV

Not Relevant

EU RoHS China RoHS

Compliant REACH SVHC Not Contained Per -D(2021)4569-DC (8 July 2021)

Halogen-Free

Status

Not Low-Halogen

For more information, please visit Contact US

China ROHS Green Image
ELV Not Relevant
ROHS Phthalates Not Contained

Search Parts in this Series

87945 Series

Mates With

87679, 87799, 87703, SFF 8482 Hard

Disk Drive and Backplane Plug

Surface Mount Compatible (SMC)

Temperature Range - Operating

Termination Interface: Style

Yes

0° to +55°C

Surface Mount

Waterproof / Dustproof No Wire Size AWG N/A

Electrical

Current - Maximum per Contact 1.5A Shielded No Voltage - Maximum 30V

Solder Process Data

Duration at Max. Process Temperature (seconds)

Lead-freeProcess Capability

Max. Cycles at Max. Process Temperature

O01

Process Temperature max. C

260

Material Info

Reference - Drawing Numbers

Electrical Model Document EE-87945-001-001
Packaging Specification PK-87945-001-001
Sales Drawing SD-87945-001-001

This document was generated on 09/23/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

571763P 58098-0628 72.250.1628.2 72.250.2428.2 74720-0505 76.350.0729.0 76871-1403 FCN-244F080-G/1 FCN-260A9920 PCR-E36PM PCS-XE26MA+ G38A71314B 1571250010 157-22500-3 MS3471L14-19P L/C 192991-0703 172501-4002 172501-6002 FCN-260C008-A/L0 FCN-260C024-AL0 FCN-261Z008 2000314-1 200331-1 PCR-E36FC+ PCS-E28FS+ PCS-XE26SLFD+ PCS-XE26SLFD+ PCS-XE26SLFD+ G730VID08BDC24 U90B2054081210 UE86K842720321 38113800006 DP3AR020WQ1R200 Z4.102.0680.0 500-1040 500-1052 500-1054 ZP-4008-66L 0709821002 DX40-20P(55) 5554841-1 MS3474W18-8P-LC* U90B3054061110 U65-E04-4020 ZPF0000000000097891 747360449 10099439-003C-TRLF 10137239-0021LF E9320-001-01 10137239-0011LF 70289-001LF