

This document was generated on 11/04/2019

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0900750027

Status: Active

Overview: <u>Magnetic and Modular Jacks/Plugs</u>
Description: <u>Modular Plug, Short Body, 4/4</u>

Documents:

<u>Application Specification AS-90075-001 (PDF)</u>

3D Model (PDF) RoHS Certificate of Compliance (PDF)

Drawing (PDF) Product Literature (PDF)

Product Specification PS-90075-001 (PDF)

Agency Certification

UL E107635

General

Product Family Modular Jacks/Plugs

Series 90075
Component Type Wire Plug
Magnetic No

Overview <u>Magnetic and Modular Jacks/Plugs</u>

Performance Category 3
Power over Ethernet (PoE) N/A

Product Literature Order No 987650-8441
Product Name Modular Plug 4/4
UPC 800753868670

Physical

Boot Color N/A Color - Resin Clear Durability (mating cycles max) 500 Flammability 94V-0 Inverted / Top Latch N/A Jack Height N/A Lightpipes/LEDs None Copper Alloy Material - Metal Material - Plating Mating Gold

Material - Plating Termination Tin
Material - Resin Polycarbonate


Net Weight 0.720/g Orientation N/A **PCB** Retention None Packaging Type Bag Pitch - Mating Interface 1.02mm Pitch - Termination Interface 1.02mm Plating min - Mating 1.270µm Plating min - Termination 1.270µm Port Configuration 1x1 Positions / Loaded Contacts 4/4 Surface Mount Compatible (SMC) No

Temperature Range - Operating -40° to +60°C

Termination Interface: Style N/A
Waterproof / Dustproof No
Wire/Cable Type Flat Oval

Electrical

Current - Maximum per Contact 1.5A
Grounding to Panel N/A



EU ELV

Not Relevant

EU RoHS China RoHS

Compliant REACH SVHC Not Contained Per -ED/71/2019 (16 July

2019) Halogen-Free Status

Low-Halogen

For more information, please visit Contact US

China ROHS Green Image
ELV Not Relevant
RoHS Phthalates Not Contained

Search Parts in this Series

90075 Series

Mates With FCC 68 Jacks...

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

DescriptionProduct #Parallel Action690081120

Handtool for Modular Plug, FCC 68, 4/4 Circuit, Short Body Shielded No Voltage - Maximum 125V DC

Solder Process Data

Lead-freeProcess Capability N/A

Material Info

Reference - Drawing Numbers

Application Specification AS-90075-001
Product Specification PS-90075-001
Sales Drawing SDA-90075

This document was generated on 11/04/2019

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

8949-H88/06BLKA/SN 74441-0010/BKN MP1010RX-1000 MP44RX-1000 PHP-6P6C-5 GAX-3-66 GAX-8-62 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDCX-PN-66 GDLX-A-66 GDLX-N-66 GDLX-S-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-N-1010M-BLK GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT4-N-88 GPX-2-64 GSGX-N-2-88 GSGX-N-4-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05-50 GSX-NS-88-3.05-50 GSX-NS-88-3.68 PT-108A-8C-UL PT-J951-8C PTS-J531-8CS-50UL 1-1775629-2 A-2014-0-4 GWLX-S-88-GR GWLX-S9-88-YG DC-1021-8-WH-6 1300530003 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1413235 MP88X-1000 MPS88RX-5000 MRJR-5481-0F2 E5288-S000K3-L E5908-15A242-L