

This document was generated on 11/11/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: Status: Overview: Description:	0900750141 Active Magnetic and Modular Modular Plug, Short Bo			
Documents: <u>3D Model</u> <u>3D Model (PDF)</u> <u>Drawing (PDF)</u> Product Specification PS-90075-001 (PD		Application Specification AS-90075-001 (PDF) RoHS Certificate of Compliance (PDF) Product Literature (PDF)		
Agency Certification			Series image - Reference only	
	I	E107635	EU ELV Not Relevant	
General Product Family Series		Modular Jacks/Plugs 90075	EU RoHS China RoHS Compliant	
Component Type Magnetic		Wire Plug No	REACH SVHC Not Contained Per -	
Overview Performance Catego	ſV	Magnetic and Modular Jacks/Plugs 3	ED/71/2019 (16 July 2019)	
Power over Ethernet Product Literature Or	(PoE)	N/A 987650-8441	Halogen-Free Status	
Product Name UPC		Modular Plug 8/8, RJ45 800753539198	Low-Halogen For more information, please visit <u>Contac</u>	
Physical Boot Color		N/A	China ROHS Green Image ELV Not Relevant	
Color - Resin Durability (mating cycles max)		Clear 500	RoHS Phthalates Not Contained	
Flammability		94V-0		
Inverted / Top Latch Jack Height Lightpipes/LEDs		N/A N/A None	Search Parts in this Series	
Material - Metal Material - Plating Mating		Copper Alloy Gold	Mates With	
Material - Plating Ter Material - Resin	mination	Tin Polycarbonate	FCC 68 Jacks	
Net Weight Orientation		1.031/g N/A	Application Tooling FAQ Tooling specifications and manuals are	
PCB Retention Packaging Type Pitch - Mating Interfac	ce	None Bag 1.02mm	found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling	
Pitch - Termination In Plating min - Mating		1.02mm 1.270µm	Specification document.	
Plating min - Termina Port Configuration		1.270µm 1x1	DescriptionProduct #IDT - Manual Press11201274	
Positions / Loaded Co Surface Mount Comp Temperature Range	atible (SMC)	8/8 No -40° to +60°C	Parallel Action <u>690081124</u> Handtool for Modular	
Termination Interface Waterproof / Dustpro- Wire/Cable Type	: Style	N/A No Flat Oval	Plug, FCC 68, 8/8 Circuit, Short Body Arbor Press Fixture <u>690200140</u> for Modular Plug,	
Electrical Current - Maximum p	er Contact	1.5A	FCC 68, Short Body, 8/8 Circuit	
Grounding to Panel		N/A		

Shielded Voltage - Maximum	No 125V DC
Solder Process Data Lead-freeProcess Capability	N/A
Material Info	
Reference - Drawing Numbers Application Specification Product Specification Sales Drawing	AS-90075-001 PS-90075-001 SDA-90075

This document was generated on 11/11/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

8949-H88/06BLKA/SN 74441-0010/BKN MP1010RX-1000 MP44RX-1000 PHP-6P6C-5 GAX-3-66 GAX-8-62 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDLX-A-66 GDLX-N-66 GDLX-S-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-N-1010M-BLK GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT4-N-88 GPX-2-64 GSGX-N-2-88 GSGX-N-4-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05 GSX-NS-88-3.05-50 GSX-NS-88-3.05 GSX-NS-88-3.05 GSX-NS2-88-3.05 GSX-NS-88-3.05-50 GSX-NS-88-3.05-50 GSX-NS-88-3.68 PT-108A-8C-UL PT-J951-8C PTS-J531-8CS-50UL 1-1775629-2 A-2014-0-4 GWLX-S-88-GR GWLX-S9-88-YG DC-1021-8-WH-6 1300530003 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1413235 MP88X-1000 MPS88RX-5000 MRJR-5481-0F2 E5288-S000K3-L E5908-15A242-L