

This document was generated on 08/28/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0905711301

Status: Active
Overview: QF-50TM

Description: 2.54mm Pitch QF-50 Header, Vertical, Dual Row, Shrouded, DIN Keying, with Latch/

Eject Levers, 30 Circuits, 0.1 µm Gold (Au)

Replacement Part http://www.molex.com/molex/products/listview.jsp?

Number: channel=Products&sType=p&query=090663130190663-1301 (drop-in)

Documents:

3D Model RoHS Certificate of Compliance (PDF)

Drawing (PDF)

Agency Certification

CSA LR19980 UL E29179

General

Product Family Ribbon Cable / Wire Trap Connectors

Series 90571
Comments Eject Levers
Component Type PCB Header

 Replacement Part Number
 90663-1301 (drop-in)

 UPC
 800753668027

Physical

30 Circuits (Loaded) Circuits (maximum) 30 Color - Resin Black Durability (mating cycles max) 50 **Entry Angle** Vertical Flammability 94V-0 Lock to Mating Part None Material - Metal **Brass** Material - Plating Mating Gold Material - Plating Termination Tin Material - Resin Polyester Net Weight 10225.400/mg

Number of Rows 2 PCB Locator Nο **PCB** Retention None PCB Thickness - Recommended 1.60mm Packaging Type Trav Pitch - Mating Interface 2.54mm Pitch - Termination Interface 2.54mm Plating min - Mating 0.102µm Plating min - Termination 3.048µm Polarized to Mating Part Yes Polarized to PCB No Shrouded Yes Stackable Yes Surface Mount Compatible (SMC) No

Temperature Range - Operating -25° to +85°C
Termination Interface: Style Through Hole

Wire Insulation Diameter N/A



China RoHS

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per -ED/01/2018 (15

January 2018) Halogen-Free

Status

Not Low-Halogen

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
Please visit the <u>Contact Us</u> section for any non-product compliance questions.

China ROHS Green Image
ELV Not Relevant
RoHS Phthalates Not Contained

Search Parts in this Series

90571 Series

Mates With

90635 QF-50 Female Housing

Wire Size AWG N/A

Wire/Cable Type Ribbon Cable

Electrical

Current - Maximum per Contact 1.0A Voltage - Maximum 250V

Material Info

Reference - Drawing Numbers

Sales Drawing SDA-90571

This document was generated on 08/28/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

95000-104TRLF 10135584-644402LF DF62W-EP2022PCA 95000-106TRLF DF62W-2022SCA DF62W-EP2022PC 2203348 DF62W-2022SC 1084018 1029039 1084017 802-10-012-10-002000 1112640 1112639 891-007-9SS-BST1T 000-34000 0008550134 0009482033 0009507031 57102-F02-18ULF 57102-S06-03LF 57202-S52-04LF PCN6-15S-2.5E 0039019024 58102-G61-06LF 582553-1 0009485154 0009508121 0022285053 0050291907 018731A LY20-4P-DT1-P1E-BR 02.125.8002.8 60101931 60598-1 (Cut Strip) M1625-3R/100 61062-3 61082-181009 CSU011177004 636-1427 638009-1 641938-9 641991-4 644168-1 644827-2 647662-1 65039-019ELF 65692-001LF 65781-018 65781-047