

This document was generated on 05/22/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0917160023			
Status:	Active		-	NA VA
Overview: Description:	RAST 2.5 Connector System 2.50mm Pitch Appli-Mate RA Removed Position Keys B &	ST 2.5 IDT Housing, Direct/Indirect, Female, 3 Circuits, D	A	1919
Documents: <u>3D Model</u> <u>Drawing (PDF)</u> Product Specification	PS-99020-0040-001 (PDF)	Application Specification 990330008-000 (PDF) Packaging Specification PK-90871-001-001 (PDF) RoHS Certificate of Compliance (PDF)	Series image	- Reference only
Agency Certification CSA UL		LR19980 E29179	EU ELV Not Relevant	
GL General Product Family Series Comments		IDT and Solder Connectors 91716 """This Molex product is manufactured from material that has the following ratings, tested by independent agencies:. a) A Glow Wire Ignition Temperature (GWIT) of at least 775 deg C per IEC 60695-2-13 b) A Glow Wire Flammability Index (GWFI) above 850 deg C per IEC 60695-2-12.and hence complies with the requirements set out in the International Standard IEC 60335-1 5th edition - household and similar electrical appliances - safety, section 30 Resistance to heat and fire. <p><p> The customers using this product must determine its suitability for use in their particular application through testing or other acceptable means as described in end-product glow-wire flammability test standard IEC 60695-2-11 and any applicable product end-use standard(s). <p> If it is determined during the customer's evaluation of suitability, that higher performance is required, please contact Molex for possible product options.""", """This Molex product is manufactured from material that has the following ratings, tested by independent agencies:. a) A Glow Wire Ignition Temperature (GWIT) of at least 775 deg C per IEC 60695-2-13 b) A Glow Wire Flammability Index (GWFI) above 850 deg C per IEC 60695-2-12.and hence complies with the requirements set out in the International Standard IEC 60335-1 5th edition - household and similar electrical appliances - safety, section 30 Resistance to heat and fire. <p><p> The customers using this product must determine its suitability for use in their particular application through testing or other acceptable means as described in end-product glow-wire flammability test standard IEC 60695-2-11 and any applicable product end-use standard(s). <p> If it is determined during the customer's evaluation of suitability, that higher performance is required, please contact Molex for possible product options."""</p></p></p></p></p></p>	EU RoHS Compliant REACH SVHC Not Contained Per -ED/88/2018 (15 January 2019) Halogen-Free Status Low-Halogen For more information China ROHS ELV RoHS Phthalates Search Parts in th 91716 Series Mates With	China RoHS please visit Contact US Green Image Not Relevant Not Contained Series 2.5 Header 90861, 90860
Crimp Quality Equipm Overview Product Name	ent	Yes RAST 2.5 Connector System RAST 2.5		

UPC Use With

PhysicalCircuits (Loaded)2Circuits (maximum)2Color - ResinNatural (White)Durability (mating cycles max)10Flammability94V-0GenderFemaleGlow-Wire CapableNoLock to Mating PartNoneMaterial - MetalPhosphor BronzeMaterial - Plating MatingTinMaterial - Plating TerminationTinMaterial - ResinNylonNet Weight0.655/gNumber of Rows1Packaging TypeTrayPanel MountNoPitch - Termination Interface2.50mmPitch - Mating Interface2.50mmPlating min - Termination1.016µmPlating min - Termination9.016µmPitch - Termination Interface2.50mmPitch - Termination1.016µmPitch - Termination2.016µmPitch - Termination Interface2.20° to +120°CTermination Interface: StyleIDT or PierceWire Size AWG22, 24Electrical2.0A, 4.0ACurrent - Maximum per Contact2.0A, 4.0AVoltage - Maximum32V
Wire Size AWG 22, 24 Electrical Current - Maximum per Contact 2.0A, 4.0A
Electrical Current - Maximum per Contact 2.0A, 4.0A
- · ·
Solder Process Data Lead-freeProcess Capability N/A
Material Info
Reference - Drawing NumbersApplication Specification990330008-000Packaging SpecificationPK-90871-001-001Product SpecificationPS-99020-0040-001Sales Drawing917160001-000

822348802173

This document was generated on 05/22/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 892-18-020-10-001101
 58102-G61-06LF
 582553-1
 0009485154
 009176003701906
 0050291907
 LY20-4P-DT1-P1E-BR
 02.125.8002.8

 609-3404
 61062-3
 61082-181009
 622-3653LF
 63453-116
 636-1030
 636-1427
 636-3427
 636-4007
 641938-9
 641991-4
 644827-2
 65817

 010LF
 65817-015LF
 65863-015LF
 66207-023LF
 67095-007LF
 67601157
 68648-049
 70.362.1628.0
 70-4220B
 70-4853B
 707

 5020
 707-5028
 71.350.2428.0
 71918-208LF
 71961-016LF
 733-134
 733-162
 754199-000
 760-3052
 787-8014-00
 79531-3000
 FCN

 360C032-B
 FCN-367T-T012/H
 FCN-723D010/2
 80.063.4001.1
 800-90-001-10-001000
 800-90-010-10-002000
 801-43-002-10-013000

 801-43-006-10-002000
 610-43-002-000
 610-43-002-000
 610-43-002-000
 801-43-002-10-013000
 801-43-002-10-013000