

This document was generated on 12/24/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

	<mark>478</mark> e <u>ctor System</u> RAST 5 Header, Vertical, 2 Circuits, Silver (Ag) Plating, Glow-Wire C	Capable
Documents: Drawing (PDF) Product Specification PS-99020-003	Packaging Specification PK-90858-001-001 (P RoHS Certificate of Compliance (PDF)	PDF)
Agency Certification CSA UL	LR19980 E29179	Series image - Reference only
Application tooling part link Application Tooling Part Link	216658-0200	EU ELV Not Relevant EU RoHS China RoHS
General Product Family Series Application Comments Overview Product Name UPC	PCB Headers 91999 Power, Wire-to-Board """"""This Molex product is manufactured from m that has the following ratings, tested by independ agencies:. a) A Glow Wire Ignition Temperature of at least 775 deg C per IEC 60695-2-13 b) A G Wire Flammability Index (GWFI) above 850 deg per IEC 60695-2-12.and hence complies with the requirements set out in the International Standar 60335-1 5th edition - household and similar elect appliances - safety, section 30 Resistance to hea and fire. <p><p> The customers using this produ- must determine its suitability for use in their parti application through testing or other acceptable m as described in end-product glow-wire flammabil standard IEC 60695-2-11 and any applicable pro- end-use standard(s). <p> If it is determined durin the customer's evaluation of suitability, that high performance is required, please contact Molex for possible product options.""""""" RAST Connector System RAST 5 883906536145</p></p></p>	Compliant REACH SVHC Not Contained Per - D(2021)4569-DC (8 July 2021) Halogen-Free (GWIT) Display (1) Glow (GWIT) Halogen-Free Status Not Low-Halogen For more information, please visit Contact US e Glow C For more information, please visit Contact US e C For more information, please visit Contact US e C China ROHS Green Image ELV Not Relevant RoHS Phthalates Incular neans ity test oduct Search Parts in this Series 91999 Series Mates With Mates With
PhysicalBreakawayCircuits (Loaded)Circuits (maximum)Color - ResinDurability (mating cycles max)First Mate / Last BreakFlammabilityGlow-Wire CapableGuide to Mating PartKeying to Mating PartLock to Mating PartMaterial - MetalMaterial - Plating MatingMaterial - Plating Termination	No 2 2 Natural 10 No 94V-0 Yes No Yes Yes Brass Silver Nickel	Application ToolingFAQTooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.GlobalDescriptionDescriptionProduct #RAST 5 Power2166580200Semi-Automatic IDC Machine

Material - Resin Net Weight Number of Rows Orientation PC Tail Length PCB Locator PCB Retention PCB Thickness - Recommended Packaging Type Pitch - Mating Interface Pitch - Termination Interface Shrouded Stackable Surface Mount Compatible (SMC) Temperature Range - Operating	Nylon 2.613/g 1 Vertical 3.90mm Yes None 1.40mm Bag 5.00mm 5.00mm Fully No No -20° to +120°C	
Termination Interface: Style	Through Hole	
Electrical Current - Maximum per Contact Voltage - Maximum	16.0A 250V AC	
Material Info		
Reference - Drawing Numbers Packaging Specification Product Specification	PK-90858-001-001 PS-99020-0037-001	

This document was generated on 12/24/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Power to the Board category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 6450171-4
 6450552-7
 6600323-8
 6643429-1
 6646040-2
 6651939-1
 6766604-1
 120959-1
 1393557-2
 1393532-2
 1393532-3
 1393532-4

 1393557-1
 1600812-5
 1-6450861-2
 1744132-7
 1761122-1
 1766250-1
 1892109-1
 2-6450860-5
 2-6450870-0
 1-6450161-4
 1-6450850-6
 1

 6450869-6
 1645526-2
 1-6600130-0
 2005243-2
 377-0020-11130
 TE34-12-16P-F0
 5-6450830-6
 5646956-4
 377-0080-11131A
 4-6450830-9

 4-6600333-3
 10125416-4050LF
 6600320-3
 3-6450860-5
 1888123-2
 6450166-1
 6643978-1
 6766605-1
 701-15-02109
 N11444
 6651938-1

 6450810-7
 46437-1112
 1-1589677-8
 5646956-5
 6450813-2
 6450129-4