

This document was generated on 09/27/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 09307	700008	
Status: Activ	7 <u>00008</u>	
Activ	-	
	<u>Connector System</u> ate RAST 2.5 Header, Vertical, 3 Circuits, Tin (Sn) Plating, Glow-Wire Capab	
	ning Keys A & D	
		334
Documents:		
Drawing (PDF)	Packaging Specification PK-90871-001-001 (PDF)	
Product Specification PS-93070		
Product Specification PS-99020		
		Series image - Reference only
Agency Certification		
CSA	LR19980	EU ELV
UL	E29179	Not Relevant
Application tooling part link		EU RoHS China RoHS
Application Tooling Part Link	216658-0100	Compliant
General		REACH SVHC
Product Family	PCB Headers	Not Contained Per -
Series	<u>93070</u>	D(2021)4569-DC (8 July 2021)
Application	Power, Wire-to-Board	Halogen-Free
Comments	"""""""This Molex product is manufactured from materia	al Status
	that has the following ratings, tested by independent	Not Low-Halogen
	agencies:. a) A Glow Wire Ignition Temperature (GWI	T) For more information, please visit <u>Contact US</u>
	of at least 775 deg C per IEC 60695-2-13 b) A Glow	
	Wire Flammability Index (GWFI) above 850 deg C	China ROHS Green Image
	per IEC 60695-2-12.and hence complies with the requirements set out in the International Standard IEC	ELV Not Relevant
	60335-1 5th edition - household and similar electrical	RoHS Phthalates Not Contained
	appliances - safety, section 30 Resistance to heat	
	and fire. <p><p> The customers using this product</p></p>	
	must determine its suitability for use in their particular	Search Parts in this Series
	application through testing or other acceptable means	<u>93070</u> Series
	as described in end-product glow-wire flammability tes	
	standard IEC 60695-2-11 and any applicable product	Mates With
	end-use standard(s). <p> If it is determined during</p>	Appli-Mate RAST 2.5 Female Connector
	the customer's evaluation of suitability, that higher	93050, Appli-Mate RAST 2.5 IDT Housing
	performance is required, please contact Molex for possible product options."""""""	<u>91716</u>
Overview	RAST Connector System	
Product Name	RAST 2.5	Use With RAST Standard Interface
UPC	883906564223	
		Application Teoling / EAO
Physical		Application Tooling <u>FAQ</u> Tooling specifications and manuals are
Breakaway	No	found by selecting the products below.
Circuits (Loaded)	3	Crimp Height Specifications are then
Circuits (maximum) Color - Resin	3 Natural	contained in the Application Tooling
Durability (mating cycles max)	10	Specification document.
First Mate / Last Break	No	Global
Flammability	94V-0	Description Product #
Glow-Wire Capable	Yes	RAST 2.5 Power <u>2166580100</u>
Guide to Mating Part	No	Semi-Automatic IDC
Keying to Mating Part	Yes	Machine with R-
Lock to Mating Part	Yes	Power Option
Material - Metal	Brass	

Material - Plating Mating Material - Plating Termination Material - Resin Net Weight Number of Rows Orientation PC Tail Length PCB Locator PCB Retention PCB Thickness - Recommended Packaging Type Pitch - Mating Interface Pitch - Termination Interface Plating min - Mating Plating min - Termination Polarized to Mating Part Polarized to PCB	Tin Nickel Nylon 1.030/g 1 Vertical 3.30mm Yes None 1.50mm 2.50mm 2.50mm 3.048µm 3.048µm Yes Yes
Polarized to PCB	Yes
Shrouded Stackable	Fully No
Surface Mount Compatible (SMC) Temperature Range - Operating Termination Interface: Style	No -20° to +120°C Through Hole
Electrical Current - Maximum per Contact Voltage - Maximum	6.0A 32V
Material Info	

Reference - Drawing Numbers Packaging Specification Product Specification Sales Drawing

PK-90871-001-001, PK-93070-001-001 PS-93070-001-001, PS-99020-0040-001 930700001-000

This document was generated on 09/27/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 892-18-020-10-001101
 58102-G61-06LF
 582553-1
 0009485154
 009176003701906
 0050291907
 LY20-4P-DT1-P1E-BR
 02.125.8002.8

 609-3404
 61062-3
 622-0430
 622-3653LF
 63453-116
 636-1030
 636-1427
 636-3427
 636-4007
 641938-9
 641991-4
 644827-2
 65817-010LF

 65817-015LF
 65863-015LF
 66207-023LF
 67095-007LF
 67601157
 68648-049
 70.362.1628.0
 70-4210
 70-4226B
 70-4853B
 707-5020
 707

 5028
 71.350.2428.0
 71918-208LF
 71961-016LF
 733-134
 733-162
 754199-000
 760-3052
 787-8014-00
 79531-3000
 FCN-360C032-B
 FCN

 367T-T012/H
 FCN-723D010/2
 80.063.4001.1
 800-90-001-10-001000
 800-90-010-10-002000
 801-43-002-10-013000
 801-43-006-10-002000