

This document was generated on 12/20/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0930700601

Status: Active

RAST Connector System Overview:

Appli-Mate RAST 2.5 Header, Vertical, 4 Circuits, Tin (Sn) Plating, Glow-Wire Capable, **Description:**

Positioning Keys B & C, Circuit 1 in Opposite Position

Documents:

Drawing (PDF) Product Specification PS-99020-0040-001 (PDF) 3D Model (PDF) Packaging Specification PK-90871-001-001 (PDF) Packaging Specification PK-93070-001-001 (PDF) 3D Model

RoHS Certificate of Compliance (PDF) Product Specification PS-93070-001-001 (PDF)

Agency Certification

CSA LR19980 UL E29179

Application tooling part link

Application Tooling Part Link 216658-0100

General

PCB Headers Product Family Series 93070

Application Power, Wire-to-Board Comments

""""This Molex product is manufactured from material that has the following ratings, tested by independent agencies:. a) A Glow Wire Ignition Temperature (GWIT) of at least 775 deg C per IEC 60695-2-13.. b) A Glow Wire Flammability Index (GWFI) above 850 deg C per IEC 60695-2-12.and hence complies with the requirements set out in the International Standard IEC 60335-1 5th edition - household and similar electrical appliances - safety, section 30 Resistance to heat and fire. <P><P> The customers using this product must determine its suitability for use in their particular application through testing or other acceptable means as described in end-product glow-wire flammability test standard IEC 60695-2-11 and any applicable product end-use standard(s). <P> If it is determined during the customer's evaluation of suitability, that higher performance is required, please contact Molex for


possible product options """""" **RAST Connector System**

Overview **Product Name RAST 2.5**

UPC 883906536190

Physical

Breakaway No Circuits (Loaded) 4 Circuits (maximum) Color - Resin Natural Durability (mating cycles max) 10 First Mate / Last Break No Flammability 94V-0 Glow-Wire Capable Yes Guide to Mating Part No Keying to Mating Part Yes Lock to Mating Part Yes



EU ELV

Not Relevant

EU RoHS China RoHS

Compliant

REACH SVHC

Not Contained Per -D(2021)4569-DC (8

July 2021)

Halogen-Free

Status

Not Low-Halogen

For more information, please visit Contact US

China ROHS Green Image **ELV** Not Relevant **RoHS Phthalates** Not Contained

Search Parts in this Series

93070 Series

Mates With

Appli-Mate RAST 2.5 Female Connector 93050, Appli-Mate RAST 2.5 IDT Housing 91716

Use With

RAST Standard Interface

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Power Option

Description Product # RAST 2.5 Power 2166580100 Semi-Automatic IDC Machine with R-

Material - Metal **Brass** Material - Plating Mating Tin Material - Plating Termination Nickel Material - Resin Nylon Net Weight 1.350/g Number of Rows Orientation Vertical PC Tail Length 3.30mm **PCB** Locator Yes **PCB** Retention None PCB Thickness - Recommended 1.50mm Packaging Type Carton Pitch - Mating Interface 2.50mm Pitch - Termination Interface 2.50mm Plating min - Mating 3.048µm Plating min - Termination 3.048µm Polarized to Mating Part Yes Polarized to PCB Yes Shrouded Fully Stackable No Surface Mount Compatible (SMC) No

Temperature Range - Operating -20° to +120°C
Termination Interface: Style Through Hole

Electrical

Current - Maximum per Contact 6.0A Voltage - Maximum 32V

Material Info

Reference - Drawing Numbers

 Packaging Specification
 PK-90871-001-001, PK-93070-001-001

 Product Specification
 PS-93070-001-001, PS-99020-0040-001

Sales Drawing 930700001-000

This document was generated on 12/20/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

892-18-020-10-001101 58102-G61-06LF 582553-1 0009485154 009176003701906 0050291907 LY20-4P-DT1-P1E-BR 02.125.8002.8

609-3404 61062-3 622-0430 622-3653LF 63453-116 636-1030 636-1427 636-3427 636-4007 641938-9 641991-4 644827-2 65817-010LF

65817-015LF 65863-015LF 66207-023LF 67095-007LF 67601157 68648-049 70.362.1628.0 70-4210 70-4226B 70-4853B 707-5020 707
5028 71.350.2428.0 71918-208LF 71961-016LF 733-134 733-162 754199-000 760-3052 787-8014-00 79531-3000 FCN-360C032-B FCN-367T-T012/H FCN-723D010/2 80.063.4001.1 800-90-001-10-001000 800-90-010-10-002000 801-43-002-10-013000 801-43-006-10-002000