

This document was generated on 12/21/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0930701501

Status: Active

RAST Connector System Overview:

Appli-Mate RAST 2.5 Header, Vertical, 6 Circuits, Tin (Sn) Plating, Glow-Wire Capable, **Description:**

Positioning Keys None

Documents:

Product Specification PS-99020-0040-001 (PDF) Drawing (PDF) 3D Model (PDF) Packaging Specification PK-90871-001-001 (PDF) Packaging Specification PK-93070-001-001 (PDF) 3D Model

RoHS Certificate of Compliance (PDF) Product Specification PS-93070-001-001 (PDF)

Agency Certification

CSA LR19980 E29179

Application tooling part link

Application Tooling Part Link 216658-0100

General

PCB Headers Product Family Series 93070

Application Power, Wire-to-Board Comments

""""This Molex product is manufactured from material that has the following ratings, tested by independent agencies:. a) A Glow Wire Ignition Temperature (GWIT) of at least 775 deg C per IEC 60695-2-13.. b) A Glow Wire Flammability Index (GWFI) above 850 deg C per IEC 60695-2-12.and hence complies with the requirements set out in the International Standard IEC 60335-1 5th edition - household and similar electrical appliances - safety, section 30 Resistance to heat and fire. <P><P> The customers using this product must determine its suitability for use in their particular application through testing or other acceptable means as described in end-product glow-wire flammability test standard IEC 60695-2-11 and any applicable product end-use standard(s). <P> If it is determined during the customer's evaluation of suitability, that higher performance is required, please contact Molex for


possible product options """"""

RAST Connector System Overview **Product Name** RAST 2.5

UPC 883906321222

Physical

Breakaway No Circuits (Loaded) 6 Circuits (maximum) 6 Color - Resin Natural Durability (mating cycles max) 10 First Mate / Last Break No Flammability 94V-0 Glow-Wire Capable Yes Guide to Mating Part No Keying to Mating Part None Lock to Mating Part Yes



EU ELV

Not Relevant

EU RoHS China RoHS

Compliant

REACH SVHC

Not Contained Per -D(2021)4569-DC (8

July 2021)

Halogen-Free

Status

Not Low-Halogen

For more information, please visit Contact US

China ROHS Green Image **ELV** Not Relevant **RoHS Phthalates** Not Contained

Search Parts in this Series

93070 Series

Mates With

Appli-Mate RAST 2.5 Female Connector 93050, Appli-Mate RAST 2.5 IDT Housing 91716

Use With

RAST Standard Interface

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description Product # RAST 2.5 Power 2166580100

Semi-Automatic IDC Machine with R-**Power Option**

Material - Metal **Brass** Material - Plating Mating Tin Material - Plating Termination Nickel Material - Resin Nylon Net Weight 1.690/g Number of Rows Orientation Vertical PC Tail Length 3.30mm **PCB** Locator Yes **PCB** Retention None PCB Thickness - Recommended 1.50mm Packaging Type Carton Pitch - Mating Interface 2.50mm Pitch - Termination Interface 2.50mm Plating min - Mating 3.048µm Plating min - Termination 3.048µm Polarized to Mating Part Yes Polarized to PCB Yes Shrouded Fully Stackable No Surface Mount Compatible (SMC) No

Temperature Range - Operating -20° to +120°C
Termination Interface: Style Through Hole

Electrical

Current - Maximum per Contact 6.0A Voltage - Maximum 32V

Material Info

Reference - Drawing Numbers

Packaging Specification PK-90871-001-001, PK-93070-001-001
Product Specification PS-93070-001-001, PS-99020-0040-001

Sales Drawing 930700001-000

This document was generated on 12/21/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Power to the Board category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

```
6450171-4 6450552-7 6600323-8 6643429-1 6646040-2 6651939-1 6766604-1 120959-1 1393557-2 1393532-2 1393532-3 1393532-4 1393557-1 1600812-5 1-6450861-2 1744132-7 1761122-1 1766250-1 1892109-1 2-6450860-5 2-6450870-0 1-6450161-4 1-6450850-6 1-6450869-6 1645526-2 1-6600130-0 2005243-2 377-0020-11130 TE34-12-16P-F0 5-6450830-6 5646956-4 377-0080-11131A 4-6450830-9 4-6600333-3 10125416-4050LF 6600320-3 3-6450860-5 1888123-2 6450166-1 6643978-1 6766605-1 701-15-02109 N11444 6651938-1 6450810-7 46437-1112 1-1589677-8 5646956-5 6450813-2 6450129-4
```