

This document was generated on 11/05/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0004450004		
	<u>0934452204</u>		
Status:	Active		
Overview: ML-XT Sealed Connection		on System	
		Plug Housing, Pre-Assembled with Large Rear Seal and Cover,	
	Blue		
	2.00		
Documents			
Documents:		Application Specification 024420010 A (DDE)	
<u>3D Model</u> <u>Drawing (PDF)</u>		<u>Application Specification 934430010-A (PDF)</u> Packaging Specification 934430002-K (PDF)	
3D Model (PDF)		RoHS Certificate of Compliance (PDF)	
			Series image - Reference only
Product Specification 934430010-P (PDF) Product Literature (PDF)			Series image - Reference only
Agency Certification		500/70	<u>EU ELV</u>
UL		E29179	Not Relevant
Application tooling	nart link		EU RoHS China RoHS
Application Tooling Part Link		63824-5300	Compliant
			REACH SVHC
General			
Product Family		Crimp Housings	Not Contained Per -
Series		93445	ED/71/2019 (16 July
Application		Power, Signal, Wire-to-Wire	2019)
Overview		ML-XT Sealed Connection System	Halogen-Free
Product Literature Order No		987651-0201	Status
Product Name		ML-XT	Low-Halogen
UPC		889056314954	For more information, please visit <u>Contact US</u>
		00000011001	China ROHS Green Image
Physical			ELV Not Relevant
Circuits (maximum)		3	RoHS Phthalates Not Contained
Color - Resin		Blue	RUHS FILIAIALES NUL CUITAINEU
Gender		Plug	
Glow-Wire Capable		No	
Keying to Mating Part		None	Search Parts in this Series
Lock to Mating Part		Yes	<u>93445</u> Series
Material - Resin		Nylon	
Net Weight		6.050/g	Mates With
Number of Rows		2	ML-XT Sealed 3 Circuit Receptacle Housing
Packaging Type		Bag	934442204
Panel Mount		No	
Pitch - Mating Interface		N/A	
Polarized to Mating Part		Yes	Use With
Temperature Range - Operating		-55° to +125°C	ML-XT Female (Socket) Terminal
	· •		845250009 (Nickel), ML-XT Female (Socket) Terminal 845250032 (Selective Gold), ML-
Electrical			
Current - Maximum per Contact		13.0A	XT 3 Circuit Plug Wedgelock <u>93448</u> , ML-XT Blind Cavity Plug <u>934941000</u>
Material Info			Bind Cavity Plug <u>934941000</u>
	. N		Application Tooling FAQ
Reference - Drawing Numbers		004400040 4	Tooling specifications and manuals are
Application Specification		934430010-A	found by selecting the products below.
Packaging Specification		934430002-K	Crimp Height Specifications are then
Product Specification		934430010-P	contained in the Application Tooling
Sales Drawing		934430020-000	Specification document.
			Global
			Description Product #
			Extraction Tool 638245300
			for ML-XT Sealed
I			

This document was generated on 11/05/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Automotive Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

003-018-000 60403001 60993906-B M902-2131 M902-2161 72.330.1035.1 73.353.4028.0 F119300-B F166900 F258300-B F358300-B F407400 F444110 F487000 F509500B-B 827153-1 8N1515-32-24P 9-1326729-8 925474-1 928905-1 964562-4 968782-1 GT17SA-8DS-HU 98891-1012 98947-1016 12004147 12004475-L 12010290 12010309-B 12015454 12020219-B 12020308 12041318-B 12052225-L 12052466 12059125 12064869 12004327-B 12010503-B 12015308 12015384 12015909 1-21030-1 12041254 12041318 12047946-B 12047957 12047957-L 12059473 12066261