

This document was generated on 11/05/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| Part Number: | 0934454208 | | |
|---|--|---|---|
| Status: | Active | | |
| Overview: | ML-XT Sealed Conne | ction System | |
| Description: | ML-XT Sealed 6 Circuit Plug Housing, Pre-Assembled with Large Rear Seal and Cover, | | |
| | Orange | | |
| Documents: | | | |
| <u>3D Model</u> | | Application Specification 934430010-A (PDF) | |
| <u>3D Model (PDF)</u> | | Packaging Specification 934430002-K (PDF) | |
| Drawing (PDF) | | RoHS Certificate of Compliance (PDF) | |
| Product Specificatio | <u>n 934430010-P (PDF)</u> | Product Literature (PDF) | Series image - Reference only |
| Agency Certification | on | | EU ELV |
| UL | | E29179 | Not Reviewed |
| Application tooling | ı part link | | EU RoHS China RoHS |
| Application Tooling Part Link | | 63824-5300 | Not Reviewed |
| | | | REACH SVHC |
| General | | | Not Reviewed |
| Product Family | | Crimp Housings | Halogen-Free |
| Series | | 93445 | Status |
| Application | | Power, Signal, Wire-to-Wire | Not Reviewed |
| Overview | | ML-XT Sealed Connection System | For more information, please visit Contact I |
| Product Literature Order No | | 987651-0201 | |
| Product Name | | ML-XT | China ROHS Not Reviewed |
| UPC | | 889056280273 | ELV Not Reviewed |
| Physical | | | RoHS Phthalates Not Reviewed |
| Circuits (maximum) | | 6 | |
| Color - Resin | | Orange | |
| Gender | | Plug | Search Parts in this Series |
| Glow-Wire Capable | | No | <u>93445</u> Series |
| Keying to Mating Part | | None | |
| Lock to Mating Part | | Yes | Mates With |
| Material - Resin | | Nylon | ML-XT Sealed 6 Circuit Receptacle Hous |
| Net Weight | | 8.170/g | <u>934444208</u> |
| Number of Rows | | 3 | |
| Packaging Type | | Bag | Use With |
| Panel Mount Pitch - Mating Interface | | No N/A | ML-XT Female (Socket) Terminal |
| Polarized to Mating Part | | Yes | 845250009 (Nickel), ML-XT Female (Soc |
| Temperature Range - Operating | | -55° to +125°C | Terminal <u>845250032</u> (Selective Gold), MI |
| remperature range | operating | | XT 6 Circuit Plug Wedgelock <u>93448</u> , ML- |
| Electrical Current - Maximum per Contact | | 12.04 | Blind Cavity Plug <u>934941000</u> |
| | | 13.0A | Application Tooling <u>FAQ</u> |
| Material Info | | | Tooling specifications and manuals are |
| Reference - Drawing Numbers | | | found by selecting the products below. |
| Application Specification | | 934430010-A | Crimp Height Specifications are then contained in the Application Tooling |
| Packaging Specification | | 934430002-K | Specification document. |
| Product Specification | | 934430010-P | Global |
| Sales Drawing | | 934430040-000 | Description Product # |
| | | | Extraction Tool 638245300 |
| | | | for ML-XT Sealed |
| | | | Connection System |
| | | | and Crimp Terminals |

This document was generated on 11/05/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Automotive Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

003-018-000 60403001 60993906-B M902-2131 M902-2161 72.330.1035.1 73.353.4028.0 F119300-B F166900 F258300-B F358300-B F407400 F444110 F487000 F509500B-B 827153-1 8N1515-32-24P 9-1326729-8 925474-1 928905-1 964562-4 968782-1 GT17SA-8DS-HU 98891-1012 98947-1016 12004147 12004475-L 12010290 12010309-B 12015454 12020219-B 12020308 12041318-B 12052466 12059125 12064869 12004327-B 12010503-B 12015308 12015384 12015909 1-21030-1 12041254 12041318 12047946-B 12047957 12047957-L 12059473 12066261 12110546