

This document was generated on 10/01/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>0936283725</u>			
Status:	Active			
Overview:	Magnetic Jacks			
		net 8 Core Non-PoE Single-Port RJ45 Connector, 25.40mm	The The	
Description.		in Length, Right-Angle, Inverted Profile, with Shield Tabs, with		
		EDs, Standard Temperature, with 2kV Shield Connection, Tray		
	Green-Green/ reliow L	EDS, Standard Temperature, with 2kV Shield Connection, Tray		
			D ANNARA	
Documents:				
<u>3D Model</u>		Packaging Specification 934620001-K (PDF)		
Drawing (PDF)		Datasheet (PDF)		
<u>3D Model (PDF)</u>		RoHS Certificate of Compliance (PDF)	Series imag	e - Reference only
Product Specificati	<u>on 934620001-N (PDF)</u>			
			EU ELV	
General			Not Relevant	
Product Family		Modular Jacks/Plugs		
Series		<u>93628</u>	EU RoHS	<u>China RoHS</u>
Component Type		PCB Jack	Compliant with	
Depth		25.40mm	Exemption 7(c)-I	
Magnetic		Yes	REACH SVHC	
Overview		Magnetic Jacks	Not Contained Per	
Performance Category		1000Mb	D(2021)4569-DC (8	
Power over Ethernet (PoE)		Non-PoE	July 2021)	
Product Name		Magnetic Jack, MXMag, RJ45	Halogen-Free	
UPC		889056683531	<u>Status</u>	
D I · ·			Not Low-Halogen	
Physical			For more informatio	n, please visit <u>Contact U</u>
Color - Resin		Black	China DOUS	EQ Imaga
Durability (mating cycles max)		2500	China ROHS	50 Image Not Relevant
Inverted / Top Latch		Yes	RoHS Phthalates	
Jack Height		14.10mm		Not Contained
Keying to Mating P	art	None		
Lightpipes/LEDs		LEDs		
Material - Metal		Phosphor Bronze	Search Parts in this Series	
Material - Plating Mating		Gold over Palladium Nickel	93628 Series	
Material - Plating T		Tin		
Material - Resin		Liquid Crystal Polymer	Mates With	
Net Weight		7.695/g Diable (Cida Fretra)	IEC 60603 / TIA-1	096-A
Orientation		Right Angle (Side Entry)		
PCB Locator		Yes		
PCB Retention		None		
PCB Thickness - Recommended		1.57mm		
Packaging Type Panel Mount		Tray Spring Taba		
		Spring Tabs		
Plating min - Matin	9	0.051µm (Au), 1.016µm (PdNi)		
Port Configuration Positions / Loaded Contacts		1x1		
Surface Mount Compatible (SMC)		8/8 No		
		No 0° to 170° C		
Temperature Rang		0° to +70°C		
Termination Interface: Style		Through Hole		
Wire/Cable Type		N/A		
Electrical				
Current - Maximum	n per Contact	0.5A		
Grounding to PCB		Yes		

Grounding to PCB Grounding to Panel Shielded Voltage - Maximum

Yes Yes Yes

125V

Material Info

Reference - Drawing Numbers Packaging Specification Product Specification Sales Drawing

934620001-K 934620001-N 936280001-000

This document was generated on 10/01/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

8949-H88/06BLKA/SN 74441-0010/BKN MP1010RX-1000 MP44RX-1000 PHP-6P6C-5 GAX-3-66 GAX-8-62 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDCX-PN-66 GDLX-A-66 GDLX-N-66 GDLX-S-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-N-1010M-BLK GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT4-N-88 GPX-2-64 GSGX-N-2-88 GSGX-N-4-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05 GSX-NS2-88-3.05 O GSX-NS-88-3.05-50 PT-108A-8C-UL PT-J951-8C PTS-J531-8CS-50UL 1-1775629-2 A-2014-0-4 GWLX-S-88-GR GWLX-S9-88-YG DC-1021-8-WH-6 1300530003 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1413235 MP88X-1000 MPS88RX-5000 E5288-S000K3-L E5908-15A242-L 155302-001 AX100653