

This document was generated on 09/14/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0936358314			
Status:	Active			1
Overview:	Magnetic Jacks		1 mm	- 4
Description: MXMag Fast Ethernet 6		6 Core Non-PoE Single-Port RJ45 Connector, 21.40mm Depth,		All No 1
		th, Right-Angle, Inverted Profile, with Shield Tabs, with Yellow-		
	Green LEDs, Industria		33	1
	Green LEDS, moustria			
Documents:				
3D Model		Packaging Specification 934620001-K (PDF)		
Drawing (PDF)		Datasheet (PDF)		
3D Model (PDF)		RoHS Certificate of Compliance (PDF)	Series imag	e - Reference only
	<u>on 934620001-K (PDF)</u>		Concerning	
•			EU ELV	
General			Not Relevant	
Product Family		Modular Jacks/Plugs		
Series		<u>93635</u>	EU RoHS	<u>China RoHS</u>
Component Type		PCB Jack	Compliant with	
Depth		21.40mm	Exemption 7(c)-I	
Magnetic		Yes	REACH SVHC	
Overview		Magnetic Jacks	Not Contained Per	
Performance Category		100Mb	D(2021)4569-DC (8	3
Power over Ethernet (PoE)		Non-PoE	July 2021)	
Product Name		Magnetic Jack, MXMag, RJ45	Halogen-Free	
UPC		889056572460	<u>Status</u>	
			Not Low-Halogen	
Physical			For more informatio	n, please visit <u>Contact U</u>
Color - Resin		Black		
Durability (mating cycles max)		2500	China ROHS	50 Image
Inverted / Top Latch		Yes	ELV	Not Relevant
Jack Height		14.10mm	RoHS Phthalates	Not Contained
Keying to Mating P	art	None		
Lightpipes/LEDs		LEDs		
Material - Metal		Phosphor Bronze	Search Parts in t	his Series
Material - Plating Mating		Gold over Palladium Nickel	<u>93635</u> Series	
Material - Plating T		Tin		
Material - Resin		Liquid Crystal Polymer		
Net Weight		6.285/g	Mates With	
Orientation		Right Angle (Side Entry)	IEC 60603 / TIA-1	1096-A
PCB Locator		Yes		
PCB Retention		None		
PCB Thickness - R	ecommended	1.57mm		
Packaging Type		Tray		
Panel Mount		Spring Tabs		
Plating min - Matin	g	0.051µm (Au), 1.016µm (PdNi)		
Port Configuration		1x1		
Positions / Loaded Contacts		8/8		
Surface Mount Compatible (SMC)		No		
Temperature Rang	e - Operating	-40° to +85°C		
Termination Interface: Style		Through Hole		
Wire/Cable Type		N/A		
Electrical				
Current - Maximum	n per Contact	0.5A		
Grounding to PCB	•	Yes		

Grounding to PCB Grounding to Panel Shielded Voltage - Maximum

Yes Yes Yes

125V

Material Info

Reference - Drawing Numbers Packaging Specification Product Specification Sales Drawing

934620001-K 934620001-K 934620003-K, 936350001-000

This document was generated on 09/14/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

8949-H88/06BLKA/SN 74441-0010/BKN MP1010RX-1000 MP44RX-1000 PHP-6P6C-5 GAX-3-66 GAX-8-62 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDLX-A-66 GDLX-N-66 GDLX-S-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-N-1010M-BLK GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT4-N-88 GPX-2-64 GSGX-N-2-88 GSGX-N-4-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05 GSX-NS-88-3.05-50 GSX-NS-88-3.05 GSX-NS-88-3.05 GSX-NS2-88-3.05 GSX-NS-88-3.05-50 GSX-NS-88-3.05-50 GSX-NS-88-3.68 PT-108A-8C-UL PT-J951-8C PTS-J531-8CS-50UL 1-1775629-2 A-2014-0-4 GWLX-S-88-GR GWLX-S9-88-YG DC-1021-8-WH-6 1300530003 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1413235 MP88X-1000 MPS88RX-5000 MRJR-5481-0F2 E5288-S000K3-L E5908-15A242-L