

This document was generated on 02/14/2020

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0955517667

Status: Active

Overview: Magnetic and Modular Jacks/Plugs

Description: Modular Jack, Vertical, Top Entry, Through Hole, 6/6, High Profile, Keyed Jack with

Ribs, Tray

Documents:

3D Model RoHS Certificate of Compliance (PDF)

<u>Drawing (PDF)</u> <u>Product Literature (PDF)</u>

Packaging Specification PK-95051-001-001 (PDF)

General

Product Family Modular Jacks/Plugs

Series <u>9555</u>

Comments Reflow Capable, Reflow Capable

Component Type PCB Jack Magnetic No

Overview <u>Magnetic and Modular Jacks/Plugs</u>

Performance Category 3
Power over Ethernet (PoE) N/A

Product Name Modular Jack 6/6 UPC 884982730601

Physical

PCB Locator

Boot Color N/A
Color - Resin Black

Durability (mating cycles max)

Inverted / Top Latch

Jack Height

Keying to Mating Part

Lightpipes/LEDs

No

2500

No

16.25mm

Yes

None

Material - Metal Copper Alloy
Material - Plating Mating Gold over Palladium Nickel

Material - Plating Termination Tir

Material - Resin High Temperature Thermoplastic

Yes

Net Weight 2.668/g

Orientation Vertical (Top Entry)

PCB Retention Yes
PCB Thickness - Recommended 1.57mm
Packaging Type Tray
Panel Mount Yes
Pitch - Mating Interface 1.02mm
Pitch - Termination Interface 1.27mm

Plating min - Mating 0.051µm, 1.016µm


Plating min - Termination 1.905µm
Port Configuration 1x1
Positions / Loaded Contacts 6/6
Surface Mount Compatible (SMC) Yes

Temperature Range - Operating -40° to +85°C Termination Interface: Style Through Hole

Waterproof / Dustproof No Wire/Cable Type N/A

Electrical

Current - Maximum per Contact 1.5A Grounding to PCB No



EU ELV

Not Relevant

EU RoHS China RoHS

Compliant REACH SVHC Not Contained Per -ECHA_01_2020 (16 January 2020

Halogen-Free

Status

Low-Halogen

For more information, please visit Contact US

China ROHS Green Image
ELV Not Relevant
ROHS Phthalates Not Contained

Search Parts in this Series

95551 Series

Mates With

Offset plug latch

Grounding to Panel None
Shielded No
Voltage - Maximum 125V DC

Material Info

Reference - Drawing Numbers

Packaging Specification PK-95051-001-001 Sales Drawing SD-95551-001

This document was generated on 02/14/2020

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

RJE231881317T MP1010RX-1000 MP44RX-1000 GAX-3-66 GAX-8-62 93606-0253 GD-A-44 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDCX-PN-66-50 GDLX-A-66 GDLX-A-88 GDLX-N-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-A-44 GLX-N-1010M-BLK GLX-N-44M GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT2-N-1010 GMX-SMT2-N-64-50 GMX-SMT2-S6-88 GMX-SMT4-N-88 GPX-2-64 GRT1-BT1-5 GSGX-N-2-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05-50 GSX-NS-88-3.05-30 GSX-NS-88-3.05-50 GSX-NS-88-3.68 1-1775629-2 GWLX-S-88-GR GWLX-S9-88-YG 1300500326 1300500227 1300530003 1300570002 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1400000 1413176