

This document was generated on 03/01/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| Part Number: | <u>1731130078</u> | | | |
|-------------------------------|--|---|--|--|
| Status: | Active | | | 100 |
| Overview: | | | 20 30 | |
| | FCT D-Sub Connectors | Connector Male Streight DCD Through Hele Cold Disting | Cal. | 100 |
| Description: | FCT High-Density D-Sub Connector, Male, Straight, PCB Through Hole, Gold Plating, 15 Circuits | | and the second s | |
| | 15 Circuits | | T sold | |
| Description | | | | with |
| Documents: | | Dello Certificate ef Compliance (DDE) | Carlo | ALL |
| Brochure (PDF) | | RoHS Certificate of Compliance (PDF) | 100 | 1.114 11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 |
| | | | | Willin, . |
| General | | | Sorios imas | e - Reference only |
| Product Family | | D-Sub Products | Series inay | e - Relefence Uniy |
| Series | | <u>173113</u> | | |
| IP Rating | | IP20 | EU ELV | |
| Overview | | FCT D-Sub Connectors | Not Relevant | |
| Product Category | | D-Sub Connector | EU RoHS | China RoHS |
| Product Name | | FCT Products | Compliant with | |
| Туре | | High Density | Exemption 6(c) | |
| UPC | | 889056489911 | REACH SVHC | |
| Physical | | | Not Reviewed | |
| Circuits (Loaded) | | 15 | | |
| Circuits (maximum) | | 15 | Halogen-Free | |
| Color - Resin | | Black | Status Not Reviewed | |
| Durability (mating cycle | | 50 | | n alson visit Osats at L |
| Gender | es max) | Male | For more information | on, please visit <u>Contact Us</u> |
| Material - Contact | | Copper Alloy | China ROHS | Green Image |
| Material - Resin | | PBT | ELV | Not Relevant |
| Material - Shell | | Steel | RoHS Phthalates | Not Contained |
| Net Weight | | 5.000/g | | |
| Number of Rows | | 3.000/g | | |
| Orientation | | Straight | | |
| PC Tail Length | | 9.50mm | Search Parts in this Series | |
| PCB Locator | | Yes | 173113 Series | |
| PCB Retention | | Yes | | |
| PCB Thickness - Reco | mmended | 1.60mm | Mates With | |
| Packaging Type | | Tray | FCT High-Density D-Sub, Size 1, 15 | |
| Panel Mount | | Rear | Position, Socket | |
| Panel Mount Method | | Flange | | |
| Pitch - Mating Interface | Э | 1.98mm | | |
| Pitch - Termination Inte | | 1.98mm | | |
| Plating - Contact | | Gold over Nickel | | |
| Plating - Shell | | Nickel | | |
| Polarized to Mating Part | | Yes | | |
| Polarized to PCB | | Yes | | |
| Ports | | 1 | | |
| Shielded | | Yes | | |
| Temperature Range - Operating | | -55° to +105°C | | |
| Termination Style | - | Through Hole | | |
| Waterproof / Dustproof | | No | | |
| Waterproof / Dustproo | | IP20 | | |
| | | | | |
| Electrical | | 0.04 | | |
| Current - Maximum pe | r Contact | 3.0A | | |
| | | | | |
| Material Info | | | | |

This document was generated on 03/01/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub High Density Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

97-3250-11 163A16809X 163A17089X 164A17199X 242A25680X L717HDB44POL2R210 L717HDEH15POL2 L777HDE15P L77HDE15SC309 163A16759X 163A16839X 163A16989X 163A17079X 164A17329X 164A18219X 241A16440X 241A16550X 241A16680X 241A20810X 241A25740X CT25-44P MDBE15PE766 L177HDE15SOL2RM23 L177HRC62S L177HRC62SVFM L177HRCG62S L717HDEG15POL2RM5 L77HDA26SVF L77HDE15SD1CO L77HDEH15SOL2RM832 443895-3 106698-1 280-012K2C L177HRB44S 164A17039X 09562004701510 164A17969X L777HRC62P 241A17960X 164A18269X 280-019S1S9MEN L777HDEG15P 280-018P3S25MEGN 206504-2 40-9515HDSP 2057140-1 C115370-6002 DFMA104SNMBFR172FR022 HDC9F200E2S L717HDAG26POL2RM8