

This document was generated on 08/25/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 100057 Status: Active	0231		
	Flat Ribbon Cable Solutions		
	High-Performance Flat-Ribbon Cable, 14 Circuits, 1.27mm Pitch, 28 AWG, ed Copper Alloy, UL 20424, 19/40 Stranded Extruded FEP, Natural		
Documents:			
Drawing (PDF)	Brochure (PDF)		
Datasheet (PDF)	RoHS Certificate of Compliance (PDF)		
General		Series image - Reference only	
Product Family	Cable		
Series	100057	EU ELV	
Crimp Quality Equipment	Yes	Not Relevant	
Overview	Temp-Flex Flat Ribbon Cable Solutions		
Product Name	Temp-Flex	EU RoHS	<u>China RoHS</u>
UPC	889056602808	Compliant REACH SVHC	
Physical		Not Contained Per -	
Cable Length	150 ft/spool, 20 ft min length	D(2021)4569-DC (8	
Circuits (Loaded)	14	July 2021)	
Color - Cable Jacket	Natural	Halogen-Free	
Insulation	FEP	<u>Status</u>	
Material - Outer Jacket	FEP	Low-Halogen	
Material - Plating Mating	Silver	For more informatio	n, please visit Contact US
Net Weight	16.190/g		
Packaging Type	Spool	China ROHS	Green Image
Pitch - Mating Interface	1.27mm		Not Relevant
Temperature Range - Operating	-65° to +200°C	RoHS Phthalates	Not Contained
Wire Size AWG	28		
Wire/Cable Type	19/40 Stranded, High-Performance Flat-Ribbon, UL		
	20424	Search Parts in this Series 100057 Series	
Electrical			
Current - Maximum per Contact	1.5A		
Voltage - Maximum	300V AC	Use With Molex Picoflex	
Material Info) <u>(</u>	
Engineering Number	F28H19S-14-050-N		
Reference - Drawing Numbers			
Sales Drawing	1000572819ALLOYNAT-000		

This document was generated on 08/25/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Flat Cables category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 F28-A25G
 F28-A34G
 F28-A36G
 FST-23A-15
 AYT1510-US
 171-37G
 C336514-500
 902220736002000
 902220736006000
 28100-0614

 9L28010-008-H300
 9L28014-008-H300
 F28-A24G
 F28-A60G
 25WDY00002
 28100-0571
 28100-0602
 28100-0664
 336506

 100SF
 336512-300
 336537-CUT-LENGTH
 3447/10-100
 362514100MSF
 40WDY00005
 AYT51163
 336506-300
 C3302/16
 C374910

 3625/24100M
 3749/10-100
 375630
 3-971111-6
 1-1437356-3
 812504
 20WDY00001
 5-1437214-8
 3355/15
 40WBY0007
 3609/12

 5111196336
 607.5689.087
 607.5689.091
 3801/04
 8124/04
 3801/12
 3625/22100MSF
 902220736005000
 902220736004000
 C3811/10-100