

## This document was generated on 07/29/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:   1727040095     Status:   Active     Overview:   Ect D-sub Connectors     Description:   FCT Matal Backshell for D-Sub Connector, Shell Size 1, 45° Angle Cable Outlet, Large Inner Chamber, with Rubber Bushing and Locking Screws     Documents:   Datasheet(FDF)   RoHS Centificate of Compliance (PDF)     Brochure (PDF)   RoHS Centificate of Compliance (PDF)     Product Family   D-Sub Connectors     Product Raminy   D-Sub Connectors     Product Category   Backshell     Product Rame   FCT Products     Type   Rugged Metail     UPC   889056020060     Physical   China RoHS     Cable Diameter   3.00-9.50mm     Material - Bushing   TPE     Material - Backshell   Zine General     Product Staging Type   Contained Per-     Orientation   45° Angle   Contained Per-     Orientation   Astring   FOT     Material - Backshell   Not Relevant   For more information, please visit Contact US     Orientation   45° Angle   China ROHS   Contained Per-     Orientation   45° Angle   China ROHS <th< th=""><th colspan="5"></th></th<>					
Datasheet (PDF) Brochure (PDF)   RoHS Certificate of Compliance (PDF)   Series     General Product Family   D-Sub Products   Series image - Reference only     Series   172704   Not Relevant     Product Category   Backshell   Not Relevant     Product Category   Backshell   EU EUX     Not Relevant   FCT Products   Compliant     Type   Rugged Metal   EU ROHS     UPC   889056020060   Contained Per - D(2020)4578-DC (25     Physical   Zinc Die-cast   June 2020)     Material - Bushing   TPE   Halogen-Free     Material - Screw   Stelel   Status     Mounting Style   Locking Screw   Not Relevant     Plating - Backshell   Nickel   For more information, please visit Contact US     Orientation   45* Angle   China ROHS   Not Relevant     Plating - Backshell   Nickel   ELV   Not Relevant     Plating - Backshell   Nickel   ELV   Not Relevant     Plating - Backshell   Nickel   ELV   Not Relevant     Plating - Backshell   Noteken   ELV   Not Relevant	Status: Overview: Description:	Active <u>FCT D-Sub Connectors</u> FCT Metal Backshell for D-Sub Connector, Shell Size 1, 45° Angle Cable Outlet, Large			
Product FamilyD-Sub ProductsSeries172704OverviewFCT D-Sub ConnectorsProduct CategoryBackshellProduct NameFCT ProductsTypeRugged MetalUPC889056020060PhysicalContained Per - D(2020)4578-DC (25Cable Diameter3.00-9.50mmMaterial - BackshellZinc Die-castMaterial - BushingTPEMaterial - ScrewSteelMaterial - ScrewSteelMounting StyleLocking ScrewNot RelevantFor more information, please visit Contact USOrientation45° AnglePackaging TypeCatonPackaging TypeSolid MetalShield Mare-35° to +100°CThread Size4-40 UNCThread Size1/22704 StriesWaterproof / DustproofNoWaterial InfoUse With FCT D-Sub, Size 1	Datasheet (PDF)	RoHS Certificate of Compliance (PDF)		T	
Product FamilyD-Sub ProductsSeries172704OverviewFCT D-Sub ConnectorsProduct CategoryBackshellProduct NameFCT ProductsTypeRugged MetalUPC889056020060PhysicalContained Per - D(2020)4578-DC (25Cable Diameter3.00-9.50mmMaterial - BackshellZinc Die-castMaterial - BushingTPEMaterial - ScrewSteelMaterial - ScrewSteelMounting StyleLocking ScrewNot RelevantFor more information, please visit Contact USOrientation45° AnglePackaging TypeCatonPackaging TypeSolid MetalShield Mare-35° to +100°CThread Size4-40 UNCThread Size1/22704 StriesWaterproof / DustproofNoWaterial InfoUse With FCT D-Sub, Size 1	General		Series image - Ref	erence only	
Series172704EU ELVOverviewFCT D-Sub ConnectorsNot RelevantProduct CategoryBackshellEU RoHSProduct NameFCT ProductsCompliantTypeRugged MetalCompliantTypeRugged MetalContained Per -D(2020)4578-DC (25D(2020)4578-DC (25Cable Diameter3.00-9.50mmJune 2020)Material - BushingTPEHalogen-FreeMaterial - BushingTPEHalogen-FreeMaterial - ScrewSteelStatusMounting StyleLocking ScrewNot RelevantNet Weight40.000/gFor more information, please visit Contact USOrientation45° AngleChina ROHSPackaging TypeCartonChina ROHSPackaging TypeSolid MetalRoHS Not RelevantShield TypeStolid MetalRoHS Not RelevantShield Material - StorueYesStolid MetalShield Material - StorueAnd RoHSNot ContainedShield Material - StorueAngleChina ROHSPackaging TypeSolid MetalRoHS PhthalatesShield Material For Torque40 UNCSearch Parts in this SeriesThread Size4-40 UNC172704 SeriesThread Size4-00 UNC172704 SeriesThread Size4-00 UNC </td <td></td> <td>D-Sub Products</td> <td></td> <td></td>		D-Sub Products			
OverviewFCT D-Sub ConnectorsNot RelevantProduct CategoryBackshellEU RoHSChina RoHSProduct NameFCT ProductsCompliantCompliantTypeRugged MetalCompliantCompliantUPC889056020060REACH SVHCContained Per -PhysicalJune 2020)Locking CoreaD(2020)4578-DC (25Cable Diameter3.00-9.50mmJune 2020)Material - BackshellZinc Die-castleadMaterial - ScrewSteelStatusMounting StyleLocking ScrewNot RelevantMot Weight40.000/gFor more information, please visit Contact USOrientation45° AngleELVNot RelevantPlating - BackshellNickelStielChina ROHSShield TypeSolid MetalELVNot RelevantShield TypeSolid MetalELVNot RelevantShield for per ature Range - Operating-35° to +100°CStandardThread Size4-40 UNCStandard172704 SeriesThread Size4-40 UNCTrazo4 Series172704 SeriesTightening Test Torque40 NcmNomUse WithWaterporof / DustproofNoStandard172704 SeriesMaterial InfoKaterial InfoLise Visit Per AugustionLise Visit Per Augustion			EU ELV		
Product CategoryBackshellProduct NameFCT ProductsEU RoHSChina RoHSTypeRugged MetalCompliantUPC89056020060REACH SVHCPhysicalContained Per -D(2020)4578-DC (25Cable Diameter3.00-9.50mmJune 2020)Material - BackshellZinc Die-castleadMaterial - ScrewSteelStatusMounting StyleLocking ScrewNot RelevantNet Weight40.000/gFor more information, please visit Contact USOrientation45° AngleELVNot RelevantPlating - BackshellNickelELVNot RelevantShieldedYesSolid MetalStot +100°CThread TypeStandard-35° to +100°C1/22/24 SeriesThread Size4-40 UNCStandard1/22/24 SeriesThread Size4-00 NemWaterproof / DustproofNoWaterial InfoKaterial InfoStandard					
Product NameFCT ProductsEU RoHSChina RoHSTypeRugged MetalCompliantUPC889056020060REACH SVHCChabe Diameter3.00-9.50mmJune 2020)Material - BackshellZinc Die-castleadMaterial - BushingTPEHalogen-FreeMaterial - ScrewSteelStatusMouring StyleLocking ScrewNot RelevantNet Weight40.000/gFor more information, please visit Contact USOrientation45° AngleChina ROHSPlating - BackshellNickelELVShieldedYesStield MetalShieldedYesStandardThread Size4-40 UNC172204 SeriesThread Size4-40 NormVorWaterproof / DustproofNoMaterial InfoVoe					
UPCResponsibilityPhysicalContained Per -Cable Diameter3.00-9.50mmMaterial - BackshellZinc Die-castMaterial - BushingTPEMaterial - ScrewSteelMounting StyleLocking ScrewNet Weight40.000/gOrientation45° AnglePackaging TypeCartonPlating - BackshellNickelShieldedYesTemperature Range - Operating-35° to +100°CThread Size40 NcmWaterporf / DustproofNoMaterial InfoKet Material		FCT Products		<u>hina RoHS</u>	
Choice   Contained Per -     Physical   D(2020)4578-DC (25     Cable Diameter   3.00-9.50mm     Material - Backshell   Zinc Die-cast     Material - Bushing   TPE     Material - Screw   Steel     Mounting Style   Locking Screw     Net Weight   40.000/g     Orientation   45° Angle     Packaging Type   Carton     Plating - Backshell   Nickel     Shield Type   Solid Metal     Shielded   Yes     Temperature Range - Operating   -35° to +100°C     Thread Size   4-40 UNC     Thread Type   Standard     Tightening Test Torque   40 Ncm     Waterproof / Dustproof   No     Material Info   Use With	Туре	Rugged Metal			
PhysicalD(2020)4578-DC (25Cable Diameter3.00-9.50mmJune 2020)Material - BackshellZinc Die-castleadMaterial - BushingTPEHalogen-FreeMaterial - ScrewSteelStatusMounting StyleLocking ScrewNot RelevantNet Weight40.000/gFor more information, please visit Contact USOrientation45° AnglePackaging TypeCartonChina ROHSPlating - BackshellNickelELVShield TypeSolid MetalShieldadYesTemperature Range - Operating-35° to +100°CThread Size4-40 UNCThread TypeStandardTightening Test Torque40 NcmWaterproof / DustproofNoMaterial InfoNo	UPC	889056020060			
Cable Diameter3.00-9.50mmJune 2020)Material - BackshellZinc Die-castleadMaterial - BushingTPEHalogen-FreeMaterial - ScrewSteelStatusMounting StyleLocking ScrewNot RelevantNet Weight40.000/gFor more information, please visit Contact USOrientation45° AngleChina ROHSPackaging TypeCartonChina ROHSPlating - BackshellNickelELVShield TypeSolid MetalShieldedYesTemperature Range - Operating-35° to +100°CThread Size4-40 UNCThread TypeStandardTightening Test Torque40 NcmWaterproof / DustproofNoMaterial InfoNo					
Material - BackshellZinc Die-castleadMaterial - BushingTPEHalogen-FreeMaterial - ScrewSteelStatusMounting StyleLocking ScrewNot RelevantNet Weight40.000/gFor more information, please visit Contact USOrientation45° AngleChina ROHSPackaging TypeCartonChina ROHSPlating - BackshellNickelELVShield TypeSolid MetalShieldaYesTemperature Range - Operating-35° to +100°CThread Size4-40 UNCThread Size4-40 UNCThread TypeStandardTightening Test Torque40 NcmWaterproof / DustproofNoMaterial InfoNo					
Material - BushingTPEHalogen-FreeMaterial - ScrewSteelStatusMounting StyleLocking ScrewNot RelevantNet Weight40.000/gFor more information, please visit Contact USOrientation45° AngleCartonPackaging TypeCartonChina ROHSPlating - BackshellNickelELVShield TypeSolid MetalShieldedYesTemperature Range - Operating-35° to +100°CThread Size4-40 UNCThread TypeStandardTightening Test Torque40 NcmWaterproof / DustproofNoMaterial InfoUse With FCT D-Sub, Size 1					
Material - ScrewSteelStatusMounting StyleLocking ScrewNot RelevantNet Weight40.000/gFor more information, please visit Contact USOrientation45° AngleChina ROHSPackaging TypeCartonChina ROHSPlating - BackshellNickelELVShieldedYesTemperature Range - Operating-35° to +100°CThread Size4-40 UNCThread Size4-40 UNCThread TypeStandardTightening Test Torque40 NcmWaterproof / DustproofNoMaterial InfoUse With FCT D-Sub, Size 1					
Mounting StyleLocking ScrewNot RelevantNet Weight40.000/gFor more information, please visit Contact USOrientation45° AngleFor more information, please visit Contact USPackaging TypeCartonChina ROHSNot RelevantPlating - BackshellNickelELVNot RelevantShield TypeSolid MetalROHS PhthalatesNot ContainedShieldedYesYesNot ContainedTemperature Range - Operating-35° to +100°CStandard172704 SeriesThread TypeStandard172704 Series172704 SeriesWaterproof / DustproofNoUse With FCT D-Sub, Size 1Size 1					
Net Weight40.000/gFor more information, please visit Contact USOrientation45° AngleChina ROHSNot RelevantPackaging TypeCartonChina ROHSNot RelevantPlating - BackshellNickelELVNot RelevantShield TypeSolid MetalROHS PhthalatesNot ContainedShieldedYesYesYesYesTemperature Range - Operating-35° to +100°CStandardYesThread Size4-40 UNCYesYesThread TypeStandardY2704 SeriesTightening Test Torque40 NcmYesWaterproof / DustproofNoUse With FCT D-Sub, Size 1					
Orientation45° AnglePackaging TypeCartonPlating - BackshellNickelShield TypeSolid MetalShieldedYesTemperature Range - Operating-35° to +100°CThread Size4-40 UNCThread TypeStandardTightening Test Torque40 NcmWaterproof / DustproofNoMaterial InfoUse With FCT D-Sub, Size 1					
Packaging TypeCartonChina ROHSNot RelevantPlating - BackshellNickelELVNot RelevantShield TypeSolid MetalROHS PhthalatesNot ContainedShieldedYesYesYesYesTemperature Range - Operating-35° to +100°CSearch Parts in this SeriesThread Size4-40 UNCSearch Parts in this SeriesThread TypeStandard172704 SeriesTightening Test Torque40 NcmUse WithWaterproof / DustproofNoUse WithFCT D-Sub, Size 1FCT D-Sub, Size 1			For more information, plea	se visit <u>Contact US</u>	
Plating - Backshell Nickel   Plating - Backshell Nickel   Shield Type Solid Metal   Shielded Yes   Temperature Range - Operating -35° to +100°C   Thread Size 4-40 UNC   Thread Type Standard   Tightening Test Torque 40 Ncm   Waterproof / Dustproof No   Material Info Lse With			China ROHS Not	Relevant	
Shield Type   Solid Metal     Shield Type   Solid Metal     Shielded   Yes     Temperature Range - Operating   -35° to +100°C     Thread Size   4-40 UNC     Thread Type   Standard     Tightening Test Torque   40 Ncm     Waterproof / Dustproof   No     Material Info   Ket 100°C					
ShieldedYesTemperature Range - Operating-35° to +100°CThread Size4-40 UNCThread TypeStandardTightening Test Torque40 NcmWaterproof / DustproofNoUse With FCT D-Sub, Size 1					
Temperature Range - Operating-35° to +100°CThread Size4-40 UNCThread TypeStandardTightening Test Torque40 NcmWaterproof / DustproofNoUse WithFCT D-Sub, Size 1			, [		
Thread Size4-40 UNCSearch Parts in this SeriesThread TypeStandard172704 SeriesTightening Test Torque40 NcmUse WithWaterproof / DustproofNoUse WithMaterial InfoFCT D-Sub, Size 1					
Thread Type Standard   Tightening Test Torque 40 Ncm   Waterproof / Dustproof No   Material Info Use With   FCT D-Sub, Size 1			Soaroh Parts in this So	rice	
Tightening Test Torque 40 Ncm   Waterproof / Dustproof No   Material Info FCT D-Sub, Size 1				1103	
Waterproof / Dustproof No   Material Info Use With   FCT D-Sub, Size 1	Tightening Test Torque	e 40 Ncm			
Material Info FCT D-Sub, Size 1					
Engineering Number FMK1					
	Engineering Number	FMK1			

This document was generated on 07/29/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Backshells category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

600X51137X600X54009X66241-12AM85049/6-38NM85049/86-12N03M85049/90-13P0370.350.0636.470.350.2435.172.350.1035.272.352.2435.173.359.4035.3829472-1PCS-E20W970-015-040R011971-009-030R121971-009-040R011971-015-040R011DPH-B-0031437013-91484402-8156-3025-EX16-500800165X02659X165X03399A165X10259X165X11359X165X11759X165X11889X165X11899X165X13019X165X13029X165X13169X165X13199X165X13239X165X13389X165X13489X165X14219X165X14429X165X14449X165X17409X165X17439X165X17569X165X17509X165X17609X165X17979XL171373971-025-030R121300X10989X165X02609X165X02639X