



## FEP Flat Ribbon Cable

### Mil-Spec Approved

#### Product Description

FEP Insulated Approved cables: M49055/11 & M49055/12

#### Features & Benefits

- Extruded Cable - Will Not Delaminate
- Tight Pitch Tolerances
- High Temp (200° C) Insulation Material
- Resistant to Chemicals
- Environmentally Stable
- High Performance Dielectric Insulation
- Non-combustible Cable

#### Product Scope

Military Spec	Conductor Count	Pitch Spec	Conductor Type
M49055/11	9-60	.050"	26 AWG, 7/34 Stranded, Bare Copper
	9-64	.050"	28 AWG, 7/36 Stranded, Bare Copper
M49055/12	9-60	.050"	26 AWG, 7/34 Stranded, Silver Plated Copper
	9-64	.050"	28 AWG, 7/36 Stranded, Silver Plated Copper

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Flat Cables](#) category:*

*Click to view products by [Molex](#) manufacturer:*

Other Similar products are found below :

[F28-A25G](#) [F28-A34G](#) [F28-A36G](#) [FST-23A-15](#) [AYT1510-US](#) [171-37G](#) [C336514-500](#) [902220736002000](#) [902220736006000](#) [28100-0614](#)  
[9L28010-008-H300](#) [9L28014-008-H300](#) [F28-A24G](#) [F28-A60G](#) [25WDY00002](#) [28100-0571](#) [28100-0602](#) [28100-0650](#) [28100-0664](#) [336506-](#)  
[100SF](#) [336512-300](#) [336537-CUT-LENGTH](#) [3447/10-100](#) [362514100MSF](#) [40WDY00005](#) [AYT51163](#) [336506-300](#) [C3302/16](#) [C374910](#)  
[3625/24100M](#) [3749/10-100](#) [375630](#) [3-971111-6](#) [1-1437356-3](#) [812504](#) [20WDY00001](#) [5-1437214-8](#) [3355/15](#) [40WBY00007](#) [3609/12](#)  
[5111196336](#) [607.5689.087](#) [607.5689.091](#) [3801/04](#) [8124/04](#) [3801/12](#) [3625/22100MSF](#) [902220736005000](#) [902220736004000](#) [C3811/10-100](#)