



8x 100GbE Network Ports and VU13P FPGA


The XUP-VV8 offers a large Xilinx FPGA in a 3/4-length PCle board featuring QSFP-DD (double-density) cages for maximum port density. Using the Virtex UltraScale+ VU13P or VU9P FPGA, the board supports up to 8x 100GbE or 32x 10/25GbE.

The FPGA provides large logic and memory resources—up to 3.8M logic cells and 455Mb embedded memory. The board also provides a jitter cleaner to support synchronous ethernet. The board can be configured as single width for users who don't need external memory on the DIMMs.






Xilinx VU13P FPGA: lidless package is used by BittWare's Viper thermal management for enhanced cooling performance



Air or Liquid Cooled

Up to 3.8M Logic Cells and 455Mb Embedded RAM



OCuLink Expansion Ports

Optimize the XUP-VV8 for your application with expansion:

- · Board-to-board interconnect
- · Connect to accessory boards for customization options

Inquire about customized Molex connectors/cables as required for your application.

Additional Services

Take advantage of BittWare's range of design, integration, and support options



Customization

Additional specification options or accessory boards to meet your exact needs.



Server Integration

Available pre-integrated in our <u>TeraBox servers</u> in a range of configurations.



Application Optimization

Ask about our services to help you port, optimize, and benchmark your application.



Service and Support

BittWare Developer Site provides online documentation and issue tracking.

Board Specifications

FPGA	Virtex UltraScale+ VU9P or VU13P in D2104 package Core speed grade - 2 Contact BittWare for other FPGA options
On-board Flash	Flash memory for booting FPGA
External memory	 4 DIMM sites, each supporting: Up to 128 GBytes DDR4 x72 with ECC Up to 576 Mbits dual QDR-II+ x18 (2 independent 288 Mbit banks)
Host interface	x16 Gen3 interface direct to FPGA
USB port	Micro USB: access to BMC, FPGA JTAG, and FPGA UART
Timestamp	1 PPS input and 10MHz clock input
OCuLink	2 OCuLink on rear edge, each connected to FPGA via 4x GTY transceivers
QSFP cages	 4 QSFP-DD cages on front panel Each supports 2x 100GbE, 2x 40GbE, 8x 25GbE, or 8x 10GbE Jitter cleaner for network recovered clocking

Board Management Controller	 Voltage, current, temperature monitoring Power sequencing and reset Field upgrades FPGA configuration and control Clock configuration I²C bus access USB 2.0 Voltage overrides
Cooling	 Standard: dual-width passive heatsink Optional: single-width passive heatsink* Optional: dual-width active heatsink Optional: dual-width liquid cooling
Electrical	On-board power derived from 12V PCIe slot & two AUX connectors (8-pin) Power dissipation is application dependent
Environmental	Operating temperature 5°C to 35°C
Form factor	 ¾-length, standard-height PCle dual-width board Single-width option* 10 x 4.37 inches (254 x 111.15 mm)

Development Tools

System development	BittWorks II Toolkit - host, command, and debug tools for BittWare hardware
FPGA development	 FPGA Examples - example Vivado projects, available with the BittWorks II Toolkit Xilinx Tools - Vivado® Design Suite

^{*} Available on boards with no external memory

To learn more, visit www.BittWare.com

Rev 2020.02.11 | Febrary 2020

© BittWare, Inc. 2020

UltraScale, Virtex, and Vivado are registered trademarks of Xilinx Corp. All other products are the trademarks or registered trademarks of their respective holders.



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Accelerator Cards category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

<u>VEGA-320-01A1 VEGA-330-02A1 VEGA-4000-X0A0 VEGA-4000-X0A1 MUSTANG-F100-A10-R10 Mustang-M2AE-MX1-R10 Mustang-M2BM-MX2-R10 Mustang-MPCIE-MX2-R10 BD-ACD-10AX1152B MUSTANG-V100-MX8-R10 MYS-ZU3EG-8E4D-EDGE-K2 A-U280-A32G-DEV-G</u>