

### DESCRIPTION

The MPQ9361 is a high performance, regulated charge pump converter. Its input voltage ranges from 2.8V to  $V_{out}$ . The output voltage is regulated to a fixed 5V. No external inductor is required for simplicity and compactness. Internal soft-start circuit effectively reduces the in-rush current both while start-up and mode change.

The MPQ9361 is available in a compact TSOT23-6 package

### FEATURES


- Guaranteed Industrial Temp Range Limits
- Input Voltage Range: 2.8V to 5V
- Internal Soft-Start
- Output Maximum Current up to 110mA
- Fixed 5V Output Voltage with 30mV Ripple
- 2X Charge Pump
- Fixed 1.35MHz Switching Frequency
- Over Current Protection
- Short Circuit Protection
- In-rush Current limit
- TSOT23-6 package and Lead (pb)-Free

### APPLICATIONS

- Cell phone, Smart phone, LED backlight
- PDA or hand Held Computer
- Camera Flash White LED
- LCD Display Supply
- TV-Remote Control

"MPS" and "The Future of Analog IC Technology" are Registered Trademarks of Monolithic Power Systems, Inc.

### TYPICAL APPLICATION




## ORDERING INFORMATION

| Part Number* | Package  | Top Marking | Free Air Temperature (T <sub>A</sub> ) |
|--------------|----------|-------------|--|
| MPQ9361DJ    | TSOT23-6 | U2          | -40°C to +85°C                         |

\* For Tape & Reel, add suffix -Z (e.g. MP MPQ9361DJ-Z);  
 For RoHS compliant packaging, add suffix -LF (e.g. MPQ9361DJ-LF-Z)

## PACKAGE REFERENCE



### ABSOLUTE MAXIMUM RATINGS <sup>(1)</sup>

|  |                 |
|--|-----------------|
| Supply Input Voltage.....  | -0.3V to +6.0V  |
| All Other Pins.....  | -0.3V to +6.0V  |
| Storage Temperature.....   | -65°C to +150°C |
| Continuous Power Dissipation (T <sub>A</sub> = +25°C) <sup>(2)</sup> | 0.64W           |
| Junction Temperature.....  | +150°C          |
| Lead Temperature.....  | +260°C          |

### Recommended Operating Conditions <sup>(3)</sup>

|  |                 |
|--|-----------------|
| Supply Voltage V <sub>IN</sub> .....         | 2.8V to 5.0V    |
| Output Voltage V <sub>OUT</sub> .....        | 5.0V            |
| Operating Junct. Temp (T <sub>J</sub> )..... | -40°C to +125°C |

| <b>Thermal Resistance <sup>(4)</sup></b> | <b>θ<sub>JA</sub></b> | <b>θ<sub>JC</sub></b> |
|--|-----------------------|-----------------------|
| TSOT23-6.....                            | 195.....              | 25... °C/W            |

**Notes:**

- 1) Exceeding these ratings may damage the device.
- 2) The maximum allowable power dissipation is a function of the maximum junction temperature T<sub>J</sub>(MAX), the junction-to-ambient thermal resistance θ<sub>JA</sub>, and the ambient temperature T<sub>A</sub>. The maximum allowable continuous power dissipation at any ambient temperature is calculated by P<sub>D</sub>(MAX)=(T<sub>J</sub>(MAX)-T<sub>A</sub>)/θ<sub>JA</sub>. Exceeding the maximum allowable power dissipation will cause excessive die temperature, and the regulator will go into thermal shutdown. Internal thermal shutdown circuitry protects the device from permanent damage.
- 3) The device is not guaranteed to function outside of its operating conditions.
- 4) Measured on JESD51-7 4-layer board.

## ELECTRICAL CHARACTERISTICS

$V_{IN}=3.7V$ ,  $C_{IN}=C_{OUT}=2.2\mu F$ ,  $C_P=0.22\mu F$ ,  $T_A=-40^{\circ}C$  to  $+85^{\circ}C$ . Typical values are at  $T_A=25^{\circ}C$ , unless otherwise noted.










| Parameter                | Symbol             | Condition                                 | Min  | Typ  | Max | Units   |   |
|--------------------------|--------------------|---|--|------|-----|---------|---|
| Input Supply Voltage     | $V_{IN}$           |   | 2.8  |      | 5   | V       |   |
| Output Voltage           | $V_{OUT}$          | $V_{IN}>3.2V$ ,<br>$I_{OUT}<110mA$        |  | 4.8  | 5   | 5.2     | V |
|                          |                    |   | $T_A=25^{\circ}C$<br>$-40^{\circ}C \leq T_A \leq +85^{\circ}C$ | 4.6  | 5   | 5.2     |   |
| Quiescent Current        | $I_Q$              | $I_{OUT}=0$                               |  | 2    | 4   | mA      |   |
| Maximum Output Current   | $I_O$              | $V_{IN}>3.2V$                             | 110  |      |     | mA      |   |
| Over Current Protection  | $I_{OCP}$          | $V_{OUT}=5V$                              | 250  | 350  | 500 | mA      |   |
| Short Circuit Protection | $I_{SHORT}$        | $T_A=25^{\circ}C$                         |  | 60   | 90  | mA      |   |
|                          |                    | $-40^{\circ}C \leq T_A \leq +85^{\circ}C$ |  | 60   | 150 |         |   |
| Output Ripple            |                    | $I_{OUT}=60mA$                            |  | 30   |     | mV      |   |
| Shut Down Current        | $I_{SHDN}$         | $V_{IN}=4.5V$ , $V_{EN}<0.4V$             |  | 0.1  | 1   | $\mu A$ |   |
| Operation Frequency      | $F_{OSC}$          |   | 1.1  | 1.35 | 1.6 | MHz     |   |
| Enable Voltage, High     | $V_{EN}$<br>(HIGH) |   |  | 1.5  |     | V       |   |
| Enable Voltage, Low      | $V_{EN}$<br>(LOW)  |   |  | 0.4  |     | V       |   |
| Enable Pin Leakage       | $I_{EN}$           | $V_{EN}=5V$                               |  | 0.2  | 1   | $\mu A$ |   |

## PIN FUNCTIONS

| Pin # | Name | Description  |
|-------|------|--|
| 1     | OUT  | Output Voltage. Decoupled with a 2.2 $\mu$ F ceramic capacitor for a load current less than 60mA. For a load current greater than 60mA, use 10 $\mu$ F decoupling capacitor. |
| 2     | GND  | Ground.  |
| 3     | EN   | Device Enable: A logic high input ( $V_{EN}>1.5V$ ) turns on the regulator. A logic low input ( $V_{EN}>0.4V$ )  |
| 4     | CN   | Flying Capacitor Negative Terminal.  |
| 5     | IN   | Input.   |
| 6     | CP   | Flying Capacitor Positive Terminal.  |

## TYPICAL PERFORMANCE CHARACTERISTICS

$V_{IN}=3.7V$ ,  $V_{OUT}=5V$ ,  $C1=C2=2.2\mu F$ ,  $C3=0.47\mu F$ .  $T_A=25^\circ C$ , unless otherwise noted.




## TYPICAL PERFORMANCE CHARACTERISTICS

$V_{IN}=3.7V$ ,  $V_{OUT}=5V$ ,  $C1=C2=2.2\mu F$ ,  $C3=0.47\mu F$ .  $T_A=25^\circ C$ , unless otherwise noted. (continued)


### Inrush Current

$V_{IN}=2.8V$ ,  $I_{OUT}=64mA$   
with resistor load




### Inrush Current

$V_{GN}=V_{IN}=3.6V$ ,  $I_{OUT}=64mA$   
with resistor load




### Load PWM Dimming Operation

$V_{EN}=V_{IN}=2.8V$ ,  $F_{PWM}=100HZ$




### Load PWM Dimming Operation

$V_{EN}=V_{IN}=2.8V$ ,  $F_{PWM}=2KHZ$




### Normal Load Ripple

$V_{EN}=V_{IN}=2.8V$ ,  $V_{OUT}=5V$ ,  $I_{OUT}=60mA$



### Normal Load Ripple

$V_{IN}=V_{EN}=4V$ ,  $I_{OUT}=60mA$



## OPERATION





Figure 1— Functional Block Diagram

The MPQ9361 uses a switched capacitor charge pump to boost an input voltage to a regulated output voltage. Regulation is achieved by sensing the charge pump output voltage through an internal resistor divider network. A switched doubling circuit is enabled when the divided output drops below a preset trip point controlled by an internal comparator. The switching signal, which drives the charge pump, is created by an integrated oscillator within the control circuit block. The fixed charge pump switching frequency is approximately 1.35MHz.


The MPQ9361 has complete output short-circuit and thermal protection to safeguard the device under extreme operating conditions. An internal thermal protection circuit senses die temperature and will shut down the device if the internal junction temperature exceeds approximately 145°C. The charge pump will remain disabled until the fault condition is relieved.

## PACKAGE INFORMATION


### TSOT23-6




**TOP VIEW**



**RECOMMENDED LAND PATTERN**




**FRONT VIEW**



**SEE DETAIL "A"**

**SIDE VIEW**



**DETAIL A**

#### NOTE:

- 1) ALL DIMENSIONS ARE IN MILLIMETERS.
- 2) PACKAGE LENGTH DOES NOT INCLUDE MOLD FLASH, PROTRUSION OR GATE BURR.
- 3) PACKAGE WIDTH DOES NOT INCLUDE INTERLEAD FL OR PROTRUSION.
- 4) LEAD COPLANARITY (BOTTOM OF LEADS AFTER FORMING) SHALL BE 0.10 MILLIMETERS MAX.
- 5) DRAWING CONFORMS TO JEDEC MO-193, VARIATION 6).
- 6) DRAWING IS NOT TO SCALE.
- 7) PIN 1 IS LOWER LEFT PIN WHEN READING TOP MARK LEFT TO RIGHT, (SEE EXAMPLE TOP MARK)

**NOTICE:** The information in this document is subject to change without notice. Users should warrant and guarantee that third party Intellectual Property rights are not infringed upon when integrating MPS products into any application. MPS will not assume any legal responsibility for any said applications.



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [LED Lighting Drivers](#) category:*

*Click to view products by [Monolithic Power Systems](#) manufacturer:*

Other Similar products are found below :

[LV5235V-MPB-H](#) [MB39C602PNF-G-JNEFE1](#) [MIC2871YMK-T5](#) [AL1676-10BS7-13](#) [AL1676-20AS7-13](#) [AP5726WUG-7](#) [ICL8201](#)  
[IS31BL3228B-UTLS2-TR](#) [IS31BL3506B-TTLS2-TR](#) [AL3157F-7](#) [AP5725FDCG-7](#) [AP5726FDCG-7](#) [LV52204MTTBG](#) [AP5725WUG-7](#)  
[STP4CMPQTR](#) [NCL30086BDR2G](#) [CAT4004BHU2-GT3](#) [LV52207AXA-VH](#) [AP1694AS-13](#) [TLE4242EJ](#) [AS3688](#) [IS31LT3172-GRLS4-TR](#)  
[TLD2311EL](#) [KTD2694EDQ-TR](#) [KTZ8864EJAA-TR](#) [IS32LT3174-GRLA3-TR](#) [ZXLD1374QESTTC](#) [MP2488DN-LF-Z](#) [NLM0010XTSA1](#)  
[AL1676-20BS7-13](#) [ZXLD1370QESTTC](#) [MPQ7220GF-AEC1-P](#) [MPQ7220GR-AEC1-P](#) [MPQ4425BGJ-AEC1-P](#) [MPQ7220GF-AEC1-Z](#)  
[MPQ7220GR-AEC1-Z](#) [MPQ4425BGJ-AEC1-Z](#) [NCL30486A2DR2G](#) [IS31FL3737B-QFLS4-TR](#) [IS31FL3239-QFLS4-TR](#) [KTD2058EUAC-](#)  
[TR](#) [KTD2037EWE-TR](#) [DIO5662ST6](#) [IS31BL3508A-TTLS2-TR](#) [MAX20052CATC/V+](#) [MAX25606AUP/V+](#) [BD6586MUV-E2](#)  
[BD9206EFV-E2](#) [BD9416FS-E2](#) [LYT4227E](#)