


NOTES:

Plastic material - Polypropylene, PP-1040
Flammability Rating - UL94-HB, UL File NO. E216959
Temperature Range: -10°C to +100°C
Springs - Brass, Nickel Plated Spring Steel
Rivets - Brass, Nickel Plated
Lugs - Brass, Nickel Plated
ROHS COMPLIANT

Contact Resistance: Under 50mΩ for +/- contacts per EIA-540J000
Title: TWO "AA" CELL HOLDER WITH SOLDER LUGS
Date: 03/07/19
Drawing Number: BC22AAL
Angular: ± 3°

NOTES:
Tolerance - Decimal (Except as noted)
Scale Drawn By B.S.
Approved By T.B.
200 Broad Hollow Road, Farmingdale, New York 11735
Plastic material - Polypropylene, PP-1040
Flammability Rating - UL94-HB, UL File NO. E216959
Temperature Range: -10°C to +100°C
Springs - Brass, Nickel Plated Spring Steel
Rivets - Brass, Nickel Plated
Lugs - Brass, Nickel Plated
ROHS COMPLIANT



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for mpd manufacturer:

Other Similar products are found below :

[AS212-L](#) [BH24AAAL](#) [BC4AAAPC](#) [ZA5075](#) [BC4AAAL](#) [AP-130](#) [BK-5021](#) [ZA5070](#) [BC3AAPC](#) [BH9VL](#) [APP-004](#) [AP-133](#) [BH2/3AC](#)
[413717H](#) [BC22AAL](#) [SBH421AS](#) [BH48DW](#) [AP-124](#) [APP-001](#) [BC-2013](#) [BC3AAPC](#) [AP-129](#) [ZA5074-B](#) [BS4T-HD](#) [ZA5350](#) [ZA5076](#)
[ABG-43](#) [SBH441AS](#) [ZA1060](#) [AP-131](#) [BH-20H-1T](#) [BE-2AAAAA-PC](#) [AS212](#) [BH26AAL](#) [BC2AAAL](#) [BHX1-1225-PC](#) [BH2/3A-SM](#) [BS6T](#)
[BA2032](#) [BH26DL](#) [BH1/2AA-3](#) [ZA5036](#) [BH2DL](#) [BC12AAL](#) [BH24AAAW](#) [BK-5091](#) [BH24AASF](#) [BC3AAL](#) [BH9VW](#) [BK-5003](#)