





Date	SYM	REVISION RECORD	AUTH	DR.	CK.
2/24/07	A	(1)Redrawn (2)Added "ROHS COMPLIANT"	T.B.	B.S.	
10/17/14	B	UPDATED TO ROHS 2 COMPLIANT	T.B.	B.S.	
06/27/17	C	DIM. 29.10 WAS 29.50	T.B.	B.S.	



NOTES:
MATERIAL:
HOUSING: POLYPROPYLENE
FLAMMABILITY RATING -UL94 HB, UL FILE NO. E216959
TEMPERATURE RANGE: -10°C to +100°C
SPRINGS: SPRING STEEL, NICKEL PLATED
LUGS: BRASS, NICKEL PLATED
RIVETS: BRASS, NICKEL PLATED
CONTACT RESISTANCE: UNDER 50m Ohms FOR +/- CONTACTS PER EIA-540J000

ROHS 2 COMPLIANT

Tolerance (Inches)	 Memory Protection Devices, Inc 200 Broad Hollow Road, Farmingdale, New York 11735		
Decimal ±.5 (.020)	Scale	Drawn By B.S. Approved By T.B.	
Fractional ± .8 (.030)	Title EIGHT "AA" BATTERY HOLDER WITH SOLDER LUGS		
Angular ± 3°	Date 06/27/17	Drawing Number BH48AAL	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [mpd](#) manufacturer:

Other Similar products are found below :

[AS212-L](#) [BH24AAAL](#) [BC4AAAPC](#) [ZA5075](#) [BC4AAAL](#) [AP-130](#) [BK-5021](#) [ZA5070](#) [BC3AAPC](#) [BH9VL](#) [APP-004](#) [AP-133](#) [BH2/3AC](#)
[413717H](#) [BC22AAL](#) [SBH421AS](#) [BH48DW](#) [AP-124](#) [APP-001](#) [BC-2013](#) [BC3AAAPC](#) [AP-129](#) [ZA5074-B](#) [BS4T-HD](#) [ZA5350](#) [ZA5076](#)
[ABG-43](#) [SBH441AS](#) [ZA1060](#) [AP-131](#) [BH-20H-1T](#) [BE-2AAAA-PC](#) [AS212](#) [BH26AAL](#) [BC2AAAL](#) [BHX1-1225-PC](#) [BH2/3A-SM](#) [BS6T](#)
[BA2032](#) [BH26DL](#) [BH1/2AA-3](#) [ZA5036](#) [BH2DL](#) [BC12AAL](#) [BH24AAAW](#) [BK-5091](#) [BH24AASF](#) [BC3AAL](#) [BH9VW](#) [BK-5003](#)