

Date	SYM	REVISION RECORD	AUTH	DR.	CK.
9/05/14	D	REDRAWN IN AUTOCAD UPDATED TO ROHS 2 COMPLIANT	T.B.	B.S.	
4/07/17	E	ADDED MOUNTING HOLES	T.B.	B.S.	



## NOTES:

## 1 MATERIAL:

**HOUSING: BLACK POLYPROPYLENE** 

FLAMMABILITY RATING -UL94-HB, UL FILE NO. E216959

TEMPERATURE RANGE: -10°C to +100°C

RIVETS: BRASS, NICKLE PLATED.

SPRING: SPRING STEEL, NICKLE PLATED. 9 VOLTS SNAPS: BRASS, NICKLE PLATED.

CONTACT RESISTANCE: UNDER  $50 \text{m}\Omega$  FOR +/- CONTACTS PER

EIA-540J000

## MOUNTING INSTRUCTION:

USE 6-32 MACHINE SCREWS.

ALSO ADHESIVES AND DOUBLE SIDED TAPES WORK WELL.

ROHS 2 COMPLIANT.

Tolerance (Except as noted)	MPD Memo	ory Protection Devices, Inc					
(,	200 Broad Hollow Road, Farmingdale, New York 11735						
decimal			Scale	Drawn By B.S.			
±.5 (.020)				Approved By T.B.			
Fractional	Title	<b>"-</b> "					
± .8 (.030)	FOUR "D" CELL HOLDER WITH SOLDER LUGS						
Angular	Date	Drawing Number					
± 3°	04/07/17	BH4DL					

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for mpd manufacturer:

Other Similar products are found below:

AS212-L BH24AAAL BC4AAAPC ZA5075 BC4AAAL AP-130 BK-5021 ZA5070 BC3AAPC BH9VL APP-004 AP-133 BH2/3AC

413717H BC22AAL SBH421AS BH48DW AP-124 APP-001 BC-2013 BC3AAAPC AP-129 ZA5074-B BS4T-HD ZA5350 ZA5076

ABG-43 SBH441AS ZA1060 AP-131 BH-20H-1T BE-2AAAA-PC AS212 BH26AAL BC2AAAL BHX1-1225-PC BH2/3A-SM BS6T

BA2032 BH26DL BH1/2AA-3 ZA5036 BH2DL BC12AAL BH24AAAW BK-5091 BH24AASF BC3AAL BH9VW BK-5003