


**P- Channel 40-V (D-S) MOSFET**

**GENERAL DESCRIPTION**

The ME12P04 is the P-Channel logic enhancement mode power field effect transistors are produced using high cell density, DMOS trench technology. This high density process is especially tailored to minimize on-state resistance. These devices are particularly suited for low voltage application such as cellular phone and notebook computer power management and other battery powered circuits where high-side switching, and low in-line power loss are needed in a very small outline surface mount package.

**PIN CONFIGURATION**




**FEATURES**

- $R_{DS(ON)} \leq 45m\Omega @ V_{GS} = -10V$
- $R_{DS(ON)} \leq 80m\Omega @ V_{GS} = -4.5V$
- Super high density cell design for extremely low  $R_{DS(ON)}$
- Exceptional on-resistance and maximum DC current capability

**APPLICATIONS**

- Power Management in Note book
- Portable Equipment
- Battery Powered System
- DC/DC Converter
- Load Switch
- LCD Display inverter



P-Channel MOSFET

**Ordering Information:** ME12P04 (Pb-free)

ME12P04-G (Green product-Halogen free)

**Absolute Maximum Ratings (Tc=25°C Unless Otherwise Noted)**

Parameter	Symbol	Maximum Ratings	Unit
Drain-Source Voltage	$V_{DS}$	-40	V
Gate-Source Voltage	$V_{GS}$	$\pm 25$	V
Continuous Drain Current	$I_D$	Tc=25°C	-18.6
		Tc=70°C	-15
Pulsed Drain Current	$I_{DM}$	-75	A
Maximum Power Dissipation	$P_D$	Tc=25°C	25
		Tc=70°C	16
Operating Junction Temperature	$T_J$	-55 to 150	°C
Thermal Resistance-Junction to Case*	$R_{\theta JC}$	5	°C/W

\*The device mounted on 1in<sup>2</sup> FR4 board with 2 oz copper



## P- Channel 40-V (D-S) MOSFET

Electrical Characteristics (T<sub>c</sub> =25°C Unless Otherwise Specified)

Symbol	Parameter	Limit	Min	Typ	Max	Unit
<b>STATIC</b>						
V <sub>(BR)DSS</sub>	Drain-Source Breakdown Voltage	V <sub>GS</sub> =0V, I <sub>D</sub> =-250 μA	-40			V
V <sub>GS(th)</sub>	Gate Threshold Voltage	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =-250 μA	-1	-1.9	-3	V
I <sub>GSS</sub>	Gate Leakage Current	V <sub>DS</sub> =0V, V <sub>GS</sub> =±25V			±100	nA
I <sub>DSS</sub>	Zero Gate Voltage Drain Current	V <sub>DS</sub> =-40V, V <sub>GS</sub> =0V			-1	μA
R <sub>DS(ON)</sub>	Drain-Source On-State Resistance <sup>a</sup>	V <sub>GS</sub> =-10V, I <sub>D</sub> = -12A		35	45	mΩ
		V <sub>GS</sub> =-4.5V, I <sub>D</sub> = -6A		57	80	
V <sub>SD</sub>	Diode Forward Voltage	I <sub>S</sub> =-1.7A, V <sub>GS</sub> =0V		-0.78	-1.2	V
<b>DYNAMIC</b>						
Q <sub>g</sub>	Total Gate Charge	V <sub>DS</sub> =-20V, V <sub>GS</sub> =-10V, I <sub>D</sub> =-12A		20.3		nC
Q <sub>g</sub>	Total Gate Charge			9.8		
Q <sub>gs</sub>	Gate-Source Charge	V <sub>DS</sub> =-20V, V <sub>GS</sub> =-4.5V, I <sub>D</sub> =-12A		5		
Q <sub>gd</sub>	Gate-Drain Charge			4.3		
C <sub>iss</sub>	Input capacitance			921		pF
C <sub>oss</sub>	Output Capacitance	V <sub>DS</sub> =-20V, V <sub>GS</sub> =0V, F=1MHz		91		
C <sub>rss</sub>	Reverse Transfer Capacitance			78		
t <sub>d(on)</sub>	Turn-On Delay Time			35.3		ns
t <sub>r</sub>	Turn-On Rise Time	V <sub>DS</sub> =-15V, R <sub>L</sub> =15Ω V <sub>GS</sub> =-10V, R <sub>G</sub> =6Ω		56		
t <sub>d(off)</sub>	Turn-Off Delay Time	I <sub>D</sub> =-1A,		15.6		
t <sub>f</sub>	Turn-Off Fall Time			8.2		







Notes:a. Pulse test; pulse width ≤ 300us, duty cycle ≤ 2%

b. Matsuki Electric/ Force mos reserves the right to improve product design, functions and reliability without notice.







**P- Channel 40-V (D-S) MOSFET**

**Typical Characteristics (T<sub>J</sub> = 25°C Noted)**




**P- Channel 40-V (D-S) MOSFET**

**Typical Characteristics (T<sub>J</sub> = 25°C Noted)**



**TO-252-3L Package Outline**



SYMBOL	MIN	MAX
A	2.10	2.50
B	0.40	0.90
C	0.40	0.90
D	5.30	6.30
D1	2.20	2.90
E	6.30	6.75
E1	4.80	5.50
L1	0.90	1.80
L2	0.50	1.10
L3	0.00	0.20
H	8.90	10.40
P	2.30 BSC	





## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [MOSFET](#) category:*

*Click to view products by [MQTSUKI](#) manufacturer:*

Other Similar products are found below :

[614233C](#) [648584F](#) [FDPF9N50NZ](#) [IRFD120](#) [IRFF430](#) [JANTX2N5237](#) [2N7000](#) [FCA20N60\\_F109](#) [FDZ595PZ](#) [2SK2267\(Q\)](#) [2SK2545\(Q,T\)](#)  
[405094E](#) [423220D](#) [MIC4420CM-TR](#) [VN1206L](#) [614234A](#) [715780A](#) [SSM6J414TU,LF\(T](#) [751625C](#) [PSMN4R2-30MLD](#)  
[TK31J60W5,S1VQ\(O](#) [2SK2614\(TE16L1,Q\)](#) [DMN1017UCP3-7](#) [EFC2J004NUZTDG](#) [FCAB21350L1](#) [P85W28HP2F-7071](#) [DMN1053UCP4-7](#)  
[NTE2384](#) [NTE2969](#) [NTE6400A](#) [DMN61D9UWQ-13](#) [US6M2GTR](#) [DMN31D5UDJ-7](#) [SSM6P54TU,LF](#) [DMP22D4UFO-7B](#)  
[IPS60R3K4CEAKMA1](#) [DMN1006UCA6-7](#) [DMN16M9UCA6-7](#) [STF5N65M6](#) [STU5N65M6](#) [C3M0021120D](#) [DMN13M9UCA6-7](#)  
[BSS340NWH6327XTSA1](#) [MCM3400A-TP](#) [DMTH10H4M6SPS-13](#) [IPS60R1K0PFD7SAKMA1](#) [IPS60R360PFD7SAKMA1](#)  
[IPS60R600PFD7SAKMA1](#) [IPS60R210PFD7SAKMA1](#) [DMN2990UFB-7B](#)