

MSKSEMI 美森科

SEMICONDUCTOR



ESD



TVS



TSS



MOV



GDT



PLED

DMG2302UK-7-MS

Product specification

Description

The DMG2302UK-7-MS is the high cell density trenched N-ch MOSFETs, which provides excellent R_{DS(ON)} and efficiency for most of the small power switching and load switch applications.

The DMG2302UK-7-MS meet the RoHS and Green Product requirement with full function reliability approved.

General Features

V_{DS} = 20V, I_D = 3.2A




R_{DS(ON)} < 45mΩ @ V_{GS}=-4.5V

R_{DS(ON)} < 57mΩ @ V_{GS}=-2.5V

Application

- Green Device Available
- Super Low Gate Charge
- Excellent C_{dv/dt} effect decline
- Advanced high cell density Trench technology

Reference News

PACKAGE OUTLINE	Pin Configuration	Marking
 <p data-bbox="284 1597 379 1630">SOT-23</p>		 <p data-bbox="1153 1451 1273 1485">A2SHB</p>

Absolute Maximum Ratings

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	20	V
V_{GS}	Gate-Source Voltage	± 12	V
$I_{D@T_A=25C}$	Continuous Drain Current, $V_{GS} @ 10V^1$	3.2	A
$I_{D@T_A=70C}$	Continuous Drain Current, $V_{GS} @ 10V^1$	2.0	A
I_{DM}	Pulsed Drain Current ²	12	A
$P_{D@T_A=25C}$	Total Power Dissipation ³	1.05	W
T_{STG}	Storage Temperature Range	-55 to 150	C
T_J	Operating Junction Temperature Range	-55 to 150	C

Thermal Data

Symbol	Parameter	Typ.	Max.	Unit
$R_{\theta JA}$	Thermal Resistance Junction-ambient ¹	---	112	C/ W
$R_{\theta JC}$	Thermal Resistance Junction-Case ¹	---	---	C/ W

Electrical Characteristics
 $T_C = 25^\circ C$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units ⁿ
--------	-----------	-----------------	-----	-----	-----	--------------------

On Characteristics

BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS} = 0 V, I_D = 250 \mu A$	20	--	--	V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS} = 20 V, V_{GS} = 0 V$	--	--	1	μA
		$V_{DS} = 16 V, T_C = 125^\circ C$	--	--	10	μA
I_{GSSF}	Gate-Body Leakage Current, Forward	$V_{GS} = 10 V, V_{DS} = 0 V$	--	--	100	nA
I_{GSSR}	Gate-Body Leakage Current, Reverse	$V_{GS} = -10 V, V_{DS} = 0 V$	--	--	-100	nA

On Characteristics

VGS(th)	Gate Threshold Voltage	VDS = VGS , ID = 250 uA	0.45	0.7	1.1	V
RDS(on)	Static Drain- Source On- Resistance	VGS = 4.5 V, ID =3.0A	--	35	45	Ω
		VGS = 2.5 V, ID =2.0A	-	46	57	

Dynamic Characteristics

Ciss	Input Capacitance	VDS = 10V, VGS = 0 V, f = 1.0 MHz	--	180	-	F
Coss	Output Capacitance		--	37	-	F
Crss	Reverse Transfer Capacitance		--	34	-	F

Switching Characteristics

td(on)	Turn-On Delay Time	VGS=5 V, VDS=10V, ID =3A, RG = 6 Ω ,RL = 2.7 Ω	--	4.5	--	ns
tr	Turn-On Rise Time		--	31	--	ns
td(off)	Turn-Off Delay Time		--	12	--	ns
tf	Turn-Off Fall Time		--	4.0	--	ns
Qg	Total Gate Charge	VDS = 10 V, ID =3A, VGS = 5V	--	6.23	--	nC
Qgs	Gate- Source Charge		--	6	--	nC
Qgd	Gate-Drain Charge		--	0.5	--	nC

Drain-Source Diode Characteristics and Maximum Ratings

IS	Maximum Continuous Drain-Source Diode Forward Current	--	--	3.2	A
ISM	Maximum Pulsed Drain-Source Diode Forward Current	--	--	10.5	A
VSD	Drain to Source Diode Forward Voltage, VGS = 0V, ISD =3.2A, TJ = 25°C	--	--	1.2	V

Notes:

1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature
2. Device mounted on FR-4 PCB, 1inch x 0.85inch x 0.062 inch
3. Pulse Test: Pulse Width≤300μs, Duty Cycle≤0.5%

Typical Performance Characteristics

N- Channel Typical Characteristics




Figure1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure3. On-Resistance Variation vs Drain Current and Gate




Figure4. Body Diode Forward Voltage Variation with Source Current and Temperature




Figure 5. Capacitance Characteristics




Figure 6. Gate Charge Characteristics

N- Channel Typical Characteristics (Continued)




Figure 5. Capacitance Characteristics




Figure 6. Gate Charge Characteristics




Figure 9. Maximum Safe Operating Area




Figure 10. Maximum PContinuous Drain Current vs Case Temperature






Figure 11. Transient Thermal Response Curve

PACKAGE MECHANICAL DATA



Symbol	Dimensions in Millimeters		Dimensions in Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP		0.037 TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

Suggested Pad Layout



- Note:
1. Controlling dimension: In millimeters.
 2. General tolerance: $\pm 0.05\text{mm}$.
 3. The pad layout is for reference purposes only.

REEL SPECIFICATION

P/N	PKG	QTY
DMG2302UK-7-MS	SOT-23	3000

Attention

- Any and all MSKSEMI Semiconductor products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your MSKSEMI Semiconductor representative nearest you before using any MSKSEMI Semiconductor products described or contained herein in such applications.
- MSKSEMI Semiconductor assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all MSKSEMI Semiconductor products described or contained herein.
- Specifications of any and all MSKSEMI Semiconductor products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- MSKSEMI Semiconductor strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all MSKSEMI Semiconductor products (including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of MSKSEMI Semiconductor.
- Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. MSKSEMI Semiconductor believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the MSKSEMI Semiconductor product that you intend to use.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [MOSFET](#) category:

Click to view products by [MSKSEMI](#) manufacturer:

Other Similar products are found below :

[IRFD120](#) [JANTX2N5237](#) [2SK2267\(Q\)](#) [BUK455-60A/B](#) [TK100A10N1,S4X\(S](#) [MIC4420CM-TR](#) [VN1206L](#) [NDP4060](#) [SI4482DY](#)
[IRS2092STRPBF-EL](#) [IPS70R2K0CEAKMA1](#) [TK31J60W5,S1VQ\(O](#) [TK31J60W,S1VQ\(O](#) [TK16J60W,S1VQ\(O](#) [2SK2614\(TE16L1,Q\)](#)
[DMN1017UCP3-7](#) [EFC2J004NUZTDG](#) [P85W28HP2F-7071](#) [DMN1053UCP4-7](#) [NTE2384](#) [DMC2700UDMQ-7](#) [DMN2080UCB4-7](#)
[DMN61D9UWQ-13](#) [US6M2GTR](#) [DMN31D5UDJ-7](#) [DMP22D4UFO-7B](#) [IPS60R3K4CEAKMA1](#) [DMN1006UCA6-7](#) [DMN16M9UCA6-7](#)
[STF5N65M6](#) [IRF40H233XTMA1](#) [STU5N65M6](#) [DMN6022SSD-13](#) [DMN13M9UCA6-7](#) [DMTH10H4M6SPS-13](#) [IPS60R360PFD7SAKMA1](#)
[DMN2990UFB-7B](#) [SSM3K35CT,L3F](#) [IPLK60R1K0PFD7ATMA1](#) [2N7002W-G](#) [MCAC30N06Y-TP](#) [IPWS65R035CFD7AXKSA1](#)
[MCQ7328-TP](#) [SSM3J143TU,LXHF](#) [DMN12M3UCA6-7](#) [PJMF280N65E1_T0_00201](#) [PJMF380N65E1_T0_00201](#)
[PJMF280N60E1_T0_00201](#) [PJMF600N65E1_T0_00201](#) [PJMF900N65E1_T0_00201](#)