

BU-4061-N-XX-@ (UL® Listed Test Probe PCV Wire)



- 4mm, Straight, Shrouded, Banana Plug
- Uses 18 AWG (65/36) UL 1855, with a flexible PVC jacket.
- Length is designated in inches by the “XX” in the part number.
Standard lengths are: 12”, 18”, 24”, 39”, 48”, 60” and 72”
- Material: Probe – Stainless Steel, #8-32 threads for attachments
Banana Plug – Nickel plated Beryllium Copper and Brass
Cover -- Polypropylene
- Ratings:
 - Operating Voltage: 1,000V CAT III
 - Current: 20 Amps
 - Operating Temperature: -40°C to 80°C
- Color: The “@” in the model number represents color. Available colors:
-0 Black, -2 Red, -4 Yellow, -5 Green, -6 Blue, -8 Gray, -9 White
- RoHS 3 Compliant, CE Certified

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Test Plugs & Test Jacks](#) category:

Click to view products by [Mueller](#) manufacturer:

Other Similar products are found below :

[01-2601-4-0210](#) [01-2601-4-0212](#) [01-2604-4-0212](#) [01-2150-1-0312](#) [01-2350-1-02](#) [01-2368-1-02](#) [01-2604-5-0212](#) [01-2606-4-0210](#) [01-2606-4-0212](#) [01-2606-5-0212](#) [M39024/11-09G](#) [M39024/11-42](#) [M39024/11-43](#) [M39024/12-08](#) [707-5311](#) [707-5402-01-19](#) [707-5410](#) [R644543000](#)
[R948161000](#) [1408-4](#) [1533-1](#) [1659559](#) [1659567](#) [1663921](#) [1663939](#) [1696-102](#) [174-R825B-EX](#) [211-101](#) [RS100GBL](#) [RS250GBL](#) [251-102](#)
[25-2251-2-03](#) [25-2259-2-03](#) [923743-28-I](#) [2854-BLU](#) [2970-BLK](#) [30-443G](#) [1909861](#) [1916120](#) [1918007](#) [1919515](#) [1929125](#) [1944375](#) [204-103](#)
[2079](#) [2435108](#) [2803-102](#) [300](#) [30-442G](#) [R644543003](#)