

### BU-6161-M-XX-@

(UL® Listed, Shrouded Banana, Silicone Test Lead)



- The BU-6161-M-XX-@ is a UL® Listed, CE Certified Test Lead with Standard 4mm Shrouded Banana Plugs on both ends.
- Uses 18 AWG (413/44) UL 3577, 105°C with a highly flexible silicone jacket.
- Length is designated in inches by the “XX” in the part number.  
Standard lengths are: 12”, 18”, 24”, 39”, 48”, 60” and 72”
- Material: Banana Plug – Nickel plated Beryllium Copper and Brass Cover -- Polypropylene
- Ratings:
  - Operating Voltage: 1,000V CAT III
  - Current: 20 Amps
  - Operating Temperature: -40°C to 80°C
  - Hands free testing to 3,000V
- Color: The “@” in the model number represents color. Available colors:  
-0 Black, -2 Red, -4 Yellow, -5 Green, -6 Blue, -8 Gray, -9 White
- RoHS 3 Compliant, CE Certified

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Test Plugs & Test Jacks](#) category:*

*Click to view products by [Mueller](#) manufacturer:*

Other Similar products are found below :

[01-2601-4-0210](#) [01-2601-4-0212](#) [01-2604-4-0212](#) [01-2604-5-0210](#) [01-2150-1-0312](#) [01-2350-1-02](#) [01-2352-1-02](#) [01-2368-1-02](#) [01-2604-4-0210](#) [01-2604-5-0212](#) [01-2606-4-0210](#) [01-2606-4-0212](#) [01-2606-5-0212](#) [M39024/10-01G](#) [M39024/10-17G](#) [M39024/11-09G](#) [M39024/11-42](#) [M39024/11-43](#) [M39024/12-08](#) [707-5311](#) [707-5402-01-19](#) [707-5410](#) [923739-40-I](#) [R644543000](#) [R948161000](#) [R999351000](#) [1408-4](#) [1499-101](#) [1533-1](#) [1659559](#) [1659567](#) [1663921](#) [1663939](#) [1696-102](#) [174-R825B-EX](#) [NYS508-BU](#) [NYS508-O](#) [211-101](#) [RS100GBL](#) [RS250GBL](#) [251-102](#) [25-2251-2-03](#) [25-2259-2-03](#) [923743-16-I](#) [923743-24-I](#) [923743-28-I](#) [2854-BLU](#) [30-443G](#) [1680](#) [174-R819B-EX](#)