

BU-P2249-C-XX**(Test Lead, Male BNC with Strain Reliefs, RG-58C/U)**

- Mueller's BU-P2249-C is a test lead with male BNC connectors and strain reliefs on each end of an RG-58C/U cable.
- Wire center conductor is 20 AWG (19x33) tinned copper, and shield is tinned copper braid (95% coverage).
- Material:

Wire insulation	PVC
Male BNC body	Tarnish-resistant, nickel-plated brass
Center contact	Gold-plated brass
Insulator	PTFE
Strain relief	Molded PVC
- Rating:

Impedance	50 Ohms
Capacitance per foot	30.8 pf
Power loss	0.40 dB per 100' @ 1 MHz
Voltage	Hands-free testing to 500 VRMS
Temperature	-40°C (-40°F) to 85°C (185°F)
- Length: The "XX" in the part number represents the length in inches. Standard Lengths: 6", 12", 24", 36", 48", 60", 72", 120", 180", 240", 300", 600"
- RoHS 3 Compliant

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Test Plugs & Test Jacks](#) category:

Click to view products by [Mueller](#) manufacturer:

Other Similar products are found below :

[01-2601-4-0210](#) [01-2601-4-0212](#) [01-2604-4-0212](#) [01-2604-5-0210](#) [01-2150-1-0312](#) [01-2350-1-02](#) [01-2352-1-02](#) [01-2368-1-02](#) [01-2604-4-0210](#) [01-2604-5-0212](#) [01-2606-4-0210](#) [01-2606-4-0212](#) [01-2606-5-0212](#) [M39024/10-01G](#) [M39024/10-17G](#) [M39024/11-09G](#) [M39024/11-42](#) [M39024/11-43](#) [M39024/12-08](#) [707-5311](#) [707-5402-01-19](#) [707-5410](#) [923739-40-I](#) [R644543000](#) [R948161000](#) [R999351000](#) [1408-4](#) [1499-101](#) [1533-1](#) [1659559](#) [1659567](#) [1663921](#) [1663939](#) [1696-102](#) [174-R825B-EX](#) [NYS508-BU](#) [NYS508-O](#) [211-101](#) [RS100GBL](#) [RS250GBL](#) [251-102](#) [25-2251-2-03](#) [25-2259-2-03](#) [923743-16-I](#) [923743-24-I](#) [923743-28-I](#) [2854-BLU](#) [30-443G](#) [1680](#) [174-R819B-EX](#)