

BU-P5697-XX

(Test Lead: Male BNC on Each End)



- The BU-P5697 is a coaxial cable test lead with male BNC connectors at each end.
- Material, cable:

Cable	RG-58C/U, complies to Mil-M17/155-00001
Jacket	Non-contaminating PVC
Conductor	20 AWG (19x33) tinned copper
Shield	Tinned copper braid (95% coverage)
- Material, BNC:

Body	Tarnish-resistant nickel-plated brass
Contact	Gold-plated brass
Insulator	PTFE
- Ratings:

Impedance	50 Ohms
Capacitance per foot	30.8 pf
Power loss/100 ft. @ 1 MHz	0.40 dB
Voltage	Hands-free to 500 VRMS
Temperature	-40°C to 85°C
- Length: The "XX" in the model number indicates the length in inches. Standard lengths: 6", 12", 24", 36", 48", 60", 120", 180", 240", 300", and 600"
- RoHS 3 compliant, CE compliant

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Test Plugs & Test Jacks](#) category:

Click to view products by [Mueller](#) manufacturer:

Other Similar products are found below :

[01-2601-4-0210](#) [01-2601-4-0212](#) [01-2604-4-0212](#) [01-2604-5-0210](#) [01-2150-1-0312](#) [01-2350-1-02](#) [01-2352-1-02](#) [01-2368-1-02](#) [01-2604-4-0210](#) [01-2604-5-0212](#) [01-2606-4-0210](#) [01-2606-4-0212](#) [01-2606-5-0212](#) [M39024/10-01G](#) [M39024/10-17G](#) [M39024/11-09G](#) [M39024/11-42](#) [M39024/11-43](#) [M39024/12-08](#) [707-5311](#) [707-5402-01-19](#) [707-5410](#) [923739-40-I](#) [R644543000](#) [R948161000](#) [R999351000](#) [1408-4](#) [1499-101](#) [1533-1](#) [1659559](#) [1659567](#) [1663921](#) [1663939](#) [1696-102](#) [174-R825B-EX](#) [NYS508-BU](#) [NYS508-O](#) [211-101](#) [RS100GBL](#) [RS250GBL](#) [251-102](#) [25-2251-2-03](#) [25-2259-2-03](#) [923743-16-I](#) [923743-24-I](#) [923743-28-I](#) [2854-BLU](#) [30-443G](#) [1680](#) [174-R819B-EX](#)