

BU-P5697-XX

(Test Lead: Male BNC on Each End)



- The BU-P5697 is a coaxial cable test lead with male BNC connectors at each end.
- Material, cable:

Cable	RG-58C/U, complies to Mil-M17/155-00001
Jacket	Non-contaminating PVC
Conductor	20 AWG (19x33) tinned copper
Shield	Tinned copper braid (95% coverage)
- Material, BNC:

Body	Tarnish-resistant nickel-plated brass
Contact	Gold-plated brass
Insulator	PTFE
- Ratings:

Impedance	50 Ohms
Capacitance per foot	30.8 pf
Power loss/100 ft. @ 1 MHz	0.40 dB
Voltage	Hands-free to 500 VRMS
Temperature	-40°C to 85°C
- Length: The "XX" in the model number indicates the length in inches. Standard lengths: 6", 12", 24", 36", 48", 60", 120", 180", 240", 300", and 600"
- RoHS 3 compliant, CE compliant

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Test Leads](#) category:

Click to view products by [Mueller](#) manufacturer:

Other Similar products are found below :

[795-2384-10-25](#) [1301430020](#) [1510-24-105](#) [15308](#) [15408](#) [15302](#) [15409](#) [BU-1149-A-36-0](#) [BU-1481-E-12-0](#) [BU-1481-E-24-0](#) [1927617](#) [2450](#)
[2524-A-60](#) [924961-C](#) [LB1F-2R-RED](#) [LB1F-2R-YLW](#) [2500](#) [2524-A-48](#) [2977-J-48](#) [R948131000](#) [380200](#) [BU-1449-E-12-2](#) [BU-1480-E-24-0](#)
[BU-1481-E-12-2](#) [BU-1481-E-24-2](#) [LB1F-2R-BLK](#) [LB1F-2R-BLUE](#) [LB1F-2R-WHT](#) [6345](#) [6432](#) [6416](#) [EM3782-24-3#](#) [R948161002](#)
[R948160002](#) [R948170002](#) [R948171002](#) [R948163002](#) [973604100](#) [934160101](#) [934160100](#) [R948174000](#) [CT3269](#) [CT3258](#) [CT3158-100](#)
[HSPL 8568/AWG16/200/RT](#) [HSPL 8568/AWG16/200/SW](#) [28.0119-10020](#) [28.0127-05025](#) [28.0127-20025](#) [49.0079-20021](#)