



BU-P6384-02

(Red and Black Pair of Shrouded 4mm Banana Jack with Insulators)



- Used on stranded wire from 18 to 22 AWG with an insulator diameter from 0.06" to 0.15".
- Attach to wire with available crimp tools or by soldering.
- Provides safe and secure connections to 4mm shrouded banana plugs.
- Material:
 - Banana Jack – Nickel plated Brass
 - Insulation – Santoprene (Thermoplastic Elastomer)
- Ratings:
 - Hands free testing up to 1,500 V Max.
 - Operating Voltage: 300V Cat II (Handheld)
 - Current: 15 Amps
 - Operating Temperature: -20°F (-29°C) to 275°F (135°C)
- RoHS 3 Compliant **CE** Certified

Assembly Instructions: (Wire Not Included)



1. Slide Insulator over wire
2. Crimp/Solder wire to Banana Jack
3. Pull wire and slide insulator over banana jack
4. Insulator will lock into place once you have pulled it far enough over the Jack.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Test Plugs & Test Jacks](#) category:

Click to view products by [Mueller](#) manufacturer:

Other Similar products are found below :

[01-2601-4-0210](#) [01-2601-4-0212](#) [01-2604-4-0212](#) [01-2604-5-0210](#) [01-2150-1-0312](#) [01-2350-1-02](#) [01-2352-1-02](#) [01-2368-1-02](#) [01-2604-4-0210](#) [01-2604-5-0212](#) [01-2606-4-0210](#) [01-2606-4-0212](#) [01-2606-5-0212](#) [M39024/10-01G](#) [M39024/10-17G](#) [M39024/11-09G](#) [M39024/11-42](#) [M39024/11-43](#) [M39024/12-08](#) [707-5311](#) [707-5402-01-19](#) [707-5410](#) [923739-40-I](#) [R644543000](#) [R948161000](#) [R999351000](#) [1408-4](#) [1499-101](#) [1533-1](#) [1659559](#) [1659567](#) [1663921](#) [1663939](#) [1696-102](#) [174-R825B-EX](#) [NYS508-BU](#) [NYS508-O](#) [211-101](#) [RS100GBL](#) [RS250GBL](#) [251-102](#) [25-2251-2-03](#) [25-2259-2-03](#) [923743-16-I](#) [923743-24-I](#) [923743-28-I](#) [2854-BLU](#) [30-443G](#) [1680](#) [174-R819B-EX](#)