

BU-P72922-@
(Safety 2mm Banana Jack)



- Accepts shrouded or non-shrouded 2mm banana plugs
- Overall length is: 1.2" (30mm), Bezel Diameter is .39" (9.9mm), Bezel height above panel is: .08" (2mm)
- Wire connection: .187" (4.7mm) Quick Connect or solder
- Panel Thickness up to and .50" (12.7mm), Recommended Mounting hole diameter is: .319" (8.1mm)
- Material: Contacts— Nickel Plated Brass
 Insulator— Polyamide
- Color: The "@" in the model number represents color. Available colors are:
 - 0 Black, -2 Red
- Ratings: 600 V. CAT II, 10 Amps.
- Temperature: -40°C to 90°C
- RoHS 2 Compliant

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Test Plugs & Test Jacks](#) category:

Click to view products by [Mueller](#) manufacturer:

Other Similar products are found below :

[01-2601-4-0210](#) [01-2601-4-0212](#) [01-2604-4-0212](#) [01-2604-5-0210](#) [01-2150-1-0312](#) [01-2350-1-02](#) [01-2352-1-02](#) [01-2368-1-02](#) [01-2604-4-0210](#) [01-2604-5-0212](#) [01-2606-4-0210](#) [01-2606-4-0212](#) [01-2606-5-0212](#) [M39024/10-01G](#) [M39024/10-17G](#) [M39024/11-09G](#) [M39024/11-42](#) [M39024/11-43](#) [M39024/12-08](#) [707-5311](#) [707-5402-01-19](#) [707-5410](#) [923739-40-I](#) [R644543000](#) [R948161000](#) [R999351000](#) [1408-4](#) [1499-101](#) [1533-1](#) [1659559](#) [1659567](#) [1663921](#) [1663939](#) [1696-102](#) [174-R825B-EX](#) [NYS508-BU](#) [NYS508-O](#) [211-101](#) [RS100GBL](#) [RS250GBL](#) [251-102](#) [25-2251-2-03](#) [25-2259-2-03](#) [923743-16-I](#) [923743-24-I](#) [923743-28-I](#) [2854-BLU](#) [30-443G](#) [1680](#) [174-R819B-EX](#)