

### JP-25182-@

(Small Telecom Clip with Bed of Nails)



JP-25182/JP25182-S



JP-25182-N/JP25182-SN



JP-25182-J/JP-25182-TJ

- The JP-25182 is the smaller version of the JP-8783. Intended for applications that do not require the single spike. Jaws open to a maximum of 1.0" (25.4mm).
- Overall length 2.34" (59.4mm) (Except where noted)
- Material: Clip            Nickel Silver (Except where noted)  
                  Hardware    Brass
- RoHS 3 compliant
- The JP-25182 is sold as is or with the following suffixes:
  - Blank            Has wire mounting hardware installed
  - N                No wire mounting (used if you want to solder wire to clip)
  - L                Wire mounting hardware included but not installed
  - J                4mm banana jack installed (increases length to 2.9" (74mm))
  - TJ               8-32 threaded banana jack installed (Increases to 2.9" (74mm))
  - S                Same as {Blank} except material is nickel-plated steel
  - SN              Same as {-N} except material is nickel-plated steel
  - SL              Same as {-L} except material is nickel-plated steel

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Test Clips](#) category:*

*Click to view products by [Mueller](#) manufacturer:*

Other Similar products are found below :

[010000](#) [923742-28](#) [923743-16](#) [923850-C](#) [927739-40](#) [BU-656-0](#) [923738-28](#) [923743-20](#) [4140A](#) [4324A](#) [TL820](#) [TL822](#) [5116](#) [5450](#) [5216](#)  
[5252](#) [5454](#) [5694](#) [923700](#) [923698](#) [CR0060](#) [3038](#) [0040.1151.2](#) [927739-20](#) [923743-14](#) [923743-40](#) [R999701600](#) [923706](#) [5240](#) [603006001](#)  
[930317800](#) [930317801](#) [973889100](#) [923714](#) [R999710600](#) [949-1](#) [458-3](#) [SK 201200278 020](#) [AA0-A4830-A00](#) [00425](#) [R8-1A RED](#) [R8-1B](#)  
[BLACK](#) [R8-54 BLACK](#) [R8-54 RED](#) [MA1SW](#) [MA260SH SW](#) [AX-CR-02-SET](#) [5004-LM-IEC-RT](#) [5004-LM-IEC-SW](#) [5066-IEC-GE](#)