



Material Safety Data Sheet



Revision Date: 12/07/2006
Issue date: 05/10/2006
Version: 1

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: NC-AA; NC-AB; NC-BB; NC-MW; NC-OO

Item No. : MBWICK

Product type: No Clean Desoldering Wick

Region: Europe

Company Name & Address

Henkel Loctite Adhesives Ltd.

Multicore Solders

Technologies House, Wood Lane End

Hemel Hempstead, Herts HP2 4RQ, UK

Tel: +44 (0) 1442 278000

Fax: +44 (0) 1442 278071

Emergency Tel: +44 (0) 1442 278000

2. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components CAS No.	EINECS-No.	%	Classification
Copper 7440-50-8	231-159-6	80 - 100	

Additional Information:

For the explanation of the listed risk phrases refer to Section 16.

3. HAZARDS IDENTIFICATION

This product contains modified rosin. Flux fumes emitted during reflow will irritate the nose and throat and may cause an asthmatic type reaction.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Eye contact: Flush eyes with plenty of water for at least 15 minutes. If irritation persists seek medical attention.

Ingestion: Do not induce vomiting. Seek medical attention immediately.

Skin contact: Wash off with soap and plenty of water. Obtain medical attention if irritation persists.

5. FIRE-FIGHTING MEASURES

Extinguishing media: The product itself does not burn. Use extinguishing measures appropriate to local circumstances and the surrounding environment.

Special fire fighting procedures: Fire fighters should wear positive pressure breathing apparatus. Do not use water on fires where molten metal is present.

Unusual fire or explosion hazards: None.

Hazardous combustion products: High temperatures may produce heavy metal dust, fumes or vapours. The flux will give rise to irritating fumes.

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions: Do not allow material to contaminate ground water system.

Clean-up methods: Scrape up.

7. HANDLING AND STORAGE

Handling: Use only in area provided with appropriate exhaust ventilation. Do not eat, drink or smoke when handling. Wash hands before breaks and immediately after handling the product.

Storage: Store in a cool, dry place. Keep out of reach of children.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous components CAS No.	ACGIH TLV	Austria	Belgium	Czech
Copper 7440-50-8	0.2 mg/m ³ TWA 1 mg/m ³ TWA	0.1 mg/m ³ MAK 0.1 mg/m ³ MAK 0.4 mg/m ³ STEL 1 mg/m ³ MAK 4 mg/m ³ STEL	0.2 mg/m ³ VLE 1 mg/m ³ VLE	0.1 mg/m ³ TWA 1 mg/m ³ TWA

Hazardous components CAS No.	Estonia	Greece	Finland	France	Hungary
Copper 7440-50-8	0.2 mg/m ³ TWA 1 mg/m ³ TWA 0.2 mg/m ³ TWA	2 mg/m ³ STEL 1 mg/m ³ TWA 0.2 mg/m ³ TWA	0.1 mg/m ³ TWA 1 mg/m ³ TWA 1 mg/m ³ TWA	0.2 mg/m ³ VME 1 mg/m ³ VME 2 mg/m ³ VLE	4 mg/m ³ STEL 0.4 mg/m ³ STEL 1 mg/m ³ TWA 0.1 mg/m ³ TWA

Hazardous components CAS No.	Germany	Ireland	Netherlands	Norway	Portugal
Copper 7440-50-8	0.1 mg/m ³ MAK 0.2 mg/m ³ Peak	0.2 mg/m ³ TWA 1 mg/m ³ TWA 2 mg/m ³ STEL	0.2 mg/m ³ MAC 1 mg/m ³ MAC	0.1 mg/m ³ TWA 1 mg/m ³ TWA	0.2 mg/m ³ TWA 1 mg/m ³ TWA

Hazardous components CAS No.	Poland	Spain	Sweden	UK EH40
Copper 7440-50-8		0.2 mg/m ³ VLA-ED 1 mg/m ³ VLA-ED	0.2 mg/m ³ LLV 1 mg/m ³ LLV	0.2 mg/m ³ TWA 1 mg/m ³ TWA 0.6 mg/m ³ STEL 2 mg/m ³ STEL
Modified rosin				Rosin flux fume: 0.05 mg/m ³ MEL TWA (As total resin acids) 0.15 mg/m ³ MEL STEL (As total resin acids)

Engineering controls: Extraction is necessary to remove fumes evolved during reflow. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Respiratory protection: In case of insufficient ventilation, wear suitable respiratory equipment.

Skin protection: No special protective equipment required.

Eye/face protection: Safety glasses should be worn.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	solid
Colour:	copper
Odour:	none
pH:	not applicable
Vapour pressure:	negligible vapour pressure at ambient temperatures
Boiling point/range:	not determined
Melting point/range:	1083°C (1981°F) (copper)
Specific gravity:	8.9
Vapour density:	not applicable
Flash point:	not applicable
Autoignition temperature:	not applicable
Solubility in water:	insoluble
Partition coefficient (n-octanol/water):	not determined

10. STABILITY AND REACTIVITY

Stability:	Stable under recommended storage conditions.
Hazardous polymerisation:	Will not occur.
Hazardous decomposition products:	Thermal decomposition can lead to release of irritating gases and vapours.
Conditions to avoid:	Reacts with concentrated nitric acid to produce toxic fumes of nitrogen oxides.

11. TOXICOLOGICAL INFORMATION

Inhalation:	Fumes evolved at soldering temperatures will irritate the nose, throat and lungs. Prolonged or repeated exposure to flux fumes may result in sensitisation in sensitive workers.
Skin:	Fumes emitted during soldering may irritate the skin.
Eyes:	Fumes emitted during soldering may irritate the eyes.
Ingestion:	This material is considered to have low toxicity if swallowed.

12. ECOLOGICAL INFORMATION

Mobility:	No data available.
Bioaccumulation:	No data available.
Ecotoxicity:	No information available.
Persistence and degradability:	Not inherently biodegradable.
WGK Water Classification (VwVwS):	Class 1

13. DISPOSAL CONSIDERATIONS

Product

Disposal methods: Wherever possible unwanted product should be recycled for recovery of metal. Otherwise dispose of in accordance with local and national regulations.

European Waste Catalogue: 17 04 01 - copper, bronze, brass.

Packaging

Disposal Methods: Dispose of in accordance with local and national regulations.

14. TRANSPORT INFORMATION

ICAO/IATA (Air):

Identification number: None
Proper shipping name: Not regulated
Hazard class or division: None
Packing group: None

IMO/IMDG (Sea)

Identification number: None
Proper shipping name: Not regulated
Hazard class or division: None
Packing group: None

ADR/RID (Road/Rail)

UN Number None
Proper shipping name: Unrestricted
Hazard class or division None
Packing group None

15. REGULATORY INFORMATION

Indication of danger: None.

Risk Phrases: None.
Safety Phrases: None

Additional Labelling: Avoid breathing fumes given out during soldering. Flux fumes may irritate the nose, throat and lungs and may after prolonged/repeated exposure give an allergic reaction (asthma). Keep out of reach of children.

UK National regulations: The Health & Safety at Work etc. Act
The Control of Substances Hazardous to Health Regulations 2002
L5: General Approved Code of Practice to the COSHH Regulations
HS(G)97: A Step by Step Guide to the COSHH Regulations
HS(G)193: COSHH essentials: Easy steps to control chemicals
IND (G)248L: Solder fume and you(G)249L: Controlling health risks from rosin (colophony) based solder fluxes

16. OTHER INFORMATION

Prepared by: Barry Chase
Senior Specialist
Product Safety & Regulatory Affairs - Europe

MSDS data Revised: 12/07/2006

The information in this safety data sheet was obtained from reputable sources and to the best of our knowledge is accurate and current at the mentioned date. Neither Loctite nor its subsidiary companies accept any liability arising out of the use of the information provided here or the use, application or processing of the product(s) described herein. Attention of users is drawn to the possible hazards from improper use of the product(s). This safety data sheet was prepared in accordance with Commission Directive 2004/73/EC adapting to technical progress for the 29th time Council Directive 67/548/EEC, and Commission Directive 1999/45/EC.

Explanation of Section 2 R - Phrases

Not applicable.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [multicore manufacturer](#):

Other Similar products are found below :

[MM02104](#) [NO.5](#) [673832](#) [NC-OO 0.89MM 30M](#) [96SC 400 5C 0.50MM](#) [MF300S](#) [D620505](#) [609985](#) [MM01097](#) [MFR 301](#) [PC21A](#) [MM00991](#)
[NC-AB30M](#) [3099095-M](#) [MF300](#) [DS22 500G REEL](#) [96SC 502 5C 1.00MM](#) [631719](#) [63/37AP](#) [5029725-M](#) [DLMP22 250G REEL](#) [DS18](#)
[500G REEL](#) [D96SCF222-250G](#) [D4016 500G REEL](#) [96SCLF318ADP88.5V](#) [737196](#) [DLMP24 250G REEL](#) [609961](#) [D6192](#) [D9922](#)
[MM00975](#) [DLMP26 250G REEL](#) [5029075-M](#) [289515](#) [397102](#) [737197](#) [D622505](#) [D99182](#) [MM02179](#) [DLMP22 500G REEL](#) [3099075-M](#)
[395437](#) [MM01066](#) [D96SCF192. 2METRE](#) [63CRYSTAL-400-P2-.050](#) [D96SCF222-250G. 2METRE](#) [386851](#) [D414 500G REEL](#) [386832](#)
[3096122-M](#)