

Note: This datasheet may be out of date. Please download the latest datasheet of BLE32PN260SH1# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=BLE32PN260SH1%23

"#" indicates a package specification code.

BLE32PN260SH1#









< List of part numbers with package codes >

BLE32PN260SH1B


BLE32PN260SH1K


BLE32PN260SH1L



Appearance & Shape









Applications

Automotive Usage Powertrain/Safety



Packaging Information

Packaging	Specifications	Standard Packing Quantity
В	Bulk(Bag)	1000
K	330mm Embossed Tape	7000
L	180mm Embossed Tape	1500



Features

- 1.Bead inductor BLE series is designed to function nearly as a resistor at noise frequencies, which greatly reduces the possibility of resonance and leaves signal wave forms undistorted.
- 2. The nickel barrier structure of the external electrodes provides excellent solder heat resistance.
- 3.BLE32PN series can be used in high current circuits due to its low DC resistance. It can match power lines to a maximum of 10ADC.

1 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





BLE32PN260SH1#

Note: This datasheet may be out of date.

Please download the latest datasheet of BLE32PN260SH1# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=BLE32PN260SH1%23

"#" indicates a package specification code.



Specifications

Shape	SMD
Size Code (in inch)	1210
Length	3.2mm
Length Tolerance	±0.2mm
Width	2.5mm
Width Tolerance	±0.2mm
Thickness	1.5mm
Thickness Tolerance	+0.1mm/-0.2mm
Operating Temperature Range	-55°C to 125°C
Mass(typ.)	0.06g
Number of Circuit	1
Rated Current (at 85°C)	10A
Rated Current (at 125°C)	10A
DC Resistance(max.)	1.6mΩ
Impedance (at 100MHz)	26Ω
Impedance (at 100MHz) Tolerance	±10Ω
Size Code (in mm)	3225

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



1 Toddet Ocarcii Data Office

BLE32PN260SH1#


Note: This datasheet may be out of date.

Please download the latest datasheet of BLE32PN260SH1# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=BLE32PN260SH1%23

"#" indicates a package specification code.







Impedance-Frequency Characteristics

Equivalent Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Ferrite Beads category:

Click to view products by Murata manufacturer:

Other Similar products are found below:

CZB1EGTTP700P CZB1JGTTD101P CZB1JGTTD151P CZB1JGTTD601P CZB2AFTTD800P CZB2AGTTD601P CZB2BFTTE600P PE0402FB121ST EMI0805R-11 NCB0603R301TR050F NCB0805A320TR050F NCB-H1206B680TR300F SMB2.5-1TR SMB2.5R-2
2943778301 CZB1EGTTP121P CZB1JGTTD102P CZB1JGTTD121P CZB1JGTTD221P CZB2AGTTD301P CZB2BFTTE601P 4221R-1
4221R-2 4221R-3 EMI0805R-2000 EMI0805R-600 SBY100505T-100Y-N NCB-GH0402D121TR060F NCB-H1812D125TR150F
CZB2AGTTD102P NCB0402P301TR005F NCB0603R152TR030F NCB0805A121TR050F NCB3312K900TR500F NCBH0805A221TR300F NCB-H1806E181TR300F NCB0402P300TR030F NCB0402P700TR050F NCB0805A102TR040F
NCB1806E151TR020F NCB-H0603R121TR300F NCB-H0805A220TR600F NCB-H0805A390TR400F CIM21J252NE CZB2BFTTE121P
EMI0805R-220 74279250 7427924 CZB1JGTTD202P ABUPDE160808121Y00