

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of CSBFB1M00J58-R1 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=CSBFB1M00J58-R1

# CSBFB1M00J58-R1










## Appearance & Shape







### **Features**

MURATA's original package technologies have enabled the development of the kHz band CERALOCK(R). The series is perfect in miniature remote control units and AV modules. CERALOCK(R) can be reflow soldered and mounted by automatic placement

### Features

- 1. Withstands reflow soldering.
- 2. Compatible with automatic placement equipment.
- 3. No adjustment is necessary for oscillation circuits.



## **Applications**

Other Usage	Consumer/Industrial
-------------	---------------------



# **Packaging Information**

Packaging		Standard Packing Quantity
R1	330mm Embossed Tape	3000

1 of 2

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





### Product Search Data Sheet

Note: This datasheet may be out of date.  ${\it Please download the latest datasheet of CSBFB1M00J58-R1 from the official website of Murata}$ Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=CSBFB1M00J58-R1

# CSBFB1M00J58-R1



# **Specifications**

Product Type	Ceramic Resonator	
Troduct Type	(CERALOCK)	
Series	CSBFB_J	
Frequency	1000.0kHz	
Frequency Tolerance	+/-0.50% max.	
Operating Temperature	-20°C~80°C	
Range		
Frequency Shift by	+/-0.30% max.	
Temperature	17-0.50 70 max.	
Frequency Aging	+/-0.30% max.	
Resonant Impedance (R1)	100ohm max.	
Shape	SMD	
Wash	available	
L x W (size)	6.0x5.0mm	

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Resonators category:

Click to view products by Murata manufacturer:

Other Similar products are found below:

B39431R820H210 CSAC2.00MGCM-TC ECS-HFR-40.00-B-TR CSTLS4M00G53Z-A0 ECS-CR2-16.00-A-TR ECS-HFR-20.00-B-TR ECS-CR2-20.00-A-TR RO3164E-3 CSTNE14M7V510000R0 7D038400I01 7B009843R01 NX2012SA 32.768KHZ STD-MUB-1 NX3215SA 32.768KHZ STD-MUS-2 7B009843M01 OZ26030001 Q22FA12800519 CSTCR4M00G55E-R0 XC32M4-37.400-F16NLDT CSTLS24M0X53-B0 AWSCR-10.00CELB-C10-T3 AWSCR-12.00CELA-C33-T3 AWSCR-2.00CPLB-C15-T4 AWSCR-3.58CPLA-C30-T4 AWSCR-3.58CPLB-C30-T4 AWSCR-4.00CPLA-C33-T4 AWSCR-4.00CPLB-C10-T4 AWSCR-4.00CRLA-C39-T3 AWSCR-4.19CPLA-C30-T4 AWSCR-4.19CRLA-C15-T3 AWSCR-4.19CRLB-C15-T3 AWSCR-4.91CRLB-C15-T3 AWSCR-5.00CPLA-C30-T4 AWSCR-5.00CPLA-C30-T4 AWSCR-5.00CPLA-C30-T4 AWSCR-7.37CPLB-C30-T4 AWSCR-5.00CRLA-C15-T3 AWSCR-5.00CRLB-C15-T3 AWSCR-7.37CPLA-C30-T4 AWSCR-7.37CPLB-C30-T4 AWSCR-7.37CPLB-C30-T4 9AC04194152080D2JB CSTCR4M91G55B-R0 CSTLS3M68G56-B0 FC-12M32.768KHZ9PF20PPM ASR433.42E-T ZTTCS8.00MT X1A000091000500 X1A0000910001 ECS-SR1-4.19-B-TR 7C024000HW1 7C012000IW1 7C012000IMV1