

DMT3N4R2U224M3DTA0 / Supercapacitor(EDLC)

RoHS

REACH


Hand Soldering Only

DMT series: General-Purpose Type

~Featuring low ESR, small&slim package, and wide operation temperature range up to 85°C ~

[Features]

- High Power: Discharge up to 10A max. per piece
- Low ESR(equivalent series resistance)
- Small and Slim Package (21.0 x 14.0 x 2.2mm)
- Wide Operational Temperature : -40°C to 85°C
- Long life 5years @70 °C
- High Reliability: Characteristic degradation is reduced by airtight package and optimized electrochemical system
- Low leakage current : less than 5µA @96hrs




[Application Examples]


- **Backup** :SSD, PLC, UPS, ATM, etc.
- **Peak power assist** :IoT devices, sensor node, wearable devices, RKE, handy terminals, smart meters(wireless communication system, valve operation), motor-driven devices, e-paper, and so on.
- **Battery Peak Load Leveling** : Portable devices, GPS/GPRS tracking system, POS, Insulin pump, and so on.
- **Energy Harvest** : Supercapacitor can be used as maintenance-free storage device with flexible charge-discharge

Part Number	Rated voltage(V)	Capacitance (mF)	ESR@1kHz (mΩ)	LxW (mm)	Thickness (mm)	Operation temp.
DMT3N4R2U224M3DTA0	4.2	220	300	21 x 14	2.2(2.5Max)	-40°C~+85°C



1. Dimensions



2. Leakage Current






3. Temperature Characteristics(V.S. 25°C)






4. Discharge Characteristics



Constant Current Discharge



Constant Power Discharge



5. High Temperature Loading Test (Test Condition: 4.2V / 85°C/ 1,000hours)



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Supercapacitors](#) / [Ultracapacitors](#) category:

Click to view products by [Murata](#) manufacturer:

Other Similar products are found below :

[C-TEC1225 P](#) [SCCY73B407SLBLE](#) [CDCL3000C0-002R85STB](#) [MDCM0058C0-0016R0TBZ](#) [FE0H473ZF](#) [MAL223551012E3](#)

[MAL223551014E3](#) [MAL223551015E3](#) [MAL223551016E3](#) [MAL223551006E3](#) [MAL223551007E3](#) [MAL223551001E3](#) [MAL223551008E3](#)

[MAL219612474E3](#) [MAL219632473E3](#) [DRE10/2.5](#) [DRL106S0TI25RRDAP](#) [DRL226S0TK25RR](#) [106DCN2R7M](#) [SCCT30B156SRB](#)

[SCMR14C474MSBA0](#) [SCMR22C155MSBA0](#) [GW209F](#) [TV1020-3R0605-R](#) [SCCX50B207VSB](#) [PAS0815LS2R5105](#) [HVZ0E475NF](#)

[SCMR18F105PSBA0](#) [FT0H565ZF](#) [FE0H224ZF](#) [SCCT30E156SRB](#) [MAL222090006E3](#) [SCCY68B407SSBLE](#) [CPH3225A-2K](#)

[SCMT22C505PRBA0](#) [207DCN2R7M](#) [DB5U307W35050HA](#) [DB5U407W35060HA](#) [DGH505Q5R5](#) [DGH305Q2R7](#) [DGH505Q2R7](#)

[DGH705Q2R7](#) [DGH506Q2R7](#) [DGH335Q2R7](#) [DGH256Q2R7](#) [DGH255Q5R5](#) [DGH207Q2R7](#) [DGH155Q5R5](#) [DGH107Q2R7](#) [107DCN2R7Q](#)