Product Search Data Sheet




LDB215G2510C-001

In Production Recommended RoHS REACH

Appearance & Shape





* Terminal of "NC" should be connected the floating land. * All the technical data and information contained herein are subject to change without prior notice. (in mm)



Packaging	Specifications	Minimum Order Quantity
-	180mm Embossed Tape	4000

Features

Note: This datasheet may be out of date

Co., Ltd.

Chip type SMD baluns constructed with copper conductor and ceramic material.

Ideal for high-frequency applications.

Small-size and low-loss baluns can be customized for the balance impedance of 500hm to 2000hm.

Please download the latest datasheet of LDB215G2510C-001 from the official website of Murata Manufacturing

https://www.murata.com/en-global/products/productdetail?partno=LDB215G2510C-001

- 1. Available in the 5150MHz to 5350MHz frequency range.
- 2. Impedance at balanced terminals is 50ohm.
- 3. Small, Low-profiled SMD.
- 4. Low loss.
- 5. Available in tape and reel packing for automatic mounting.

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

1 of 3



Product Search Data Sheet

LDB215G2510C-001

Note: This datasheet may be out of date

Please download the latest datasheet of LDB215G2510C-001 from the official website of Murata Manufacturing

Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=LDB215G2510C-001

Specifications

Applications	WLAN	
Center Frequency	5250.00MHz	
Frequency Range	5150.00MHz to 5350.00MHz	
Insertion Loss I)	0.95dB max. (at 25℃)	
Insertion Loss II)	1.10dB max. (-40 to +85℃)	
Unbalance Impedance (Nom.)	50Ω	
Balance Impedance (Differential) (Nom.)	100Ω	
Unbalance Port VSWR	2.00 max. (Balance Port:at 100ohm)	
Power Capacity	0.5W	
Operating Temperature Range	-40℃ to 85℃	
L x W (size)	2.00x1.25mm	
Thickness(max.)	1.05mm	

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.


Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering


Product Search Data Sheet



LDB215G2510C-001

Product Data





Please download the latest datasheet of LDB215G2510C-001 from the official website of Murata Manufacturing

https://www.murata.com/en-global/products/productdetail?partno=LDB215G2510C-001


Note: This datasheet may be out of date.

Co., Ltd.

a : unbalance port b, c : balance port

Insertion Loss Characteristics

0 5 10 15 20 25 30 40 40 45,1 5,25 5,45 Frequency Range (GHz) Measurement Circuit of Insertion Loss



a : unbalance port b, c : balance port

Characteristics of Unbalance Port VSWR

Measurement Circuit of Unbalance Port VSWR

Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



3 of 3

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Signal Conditioning category:

Click to view products by Murata manufacturer:

Other Similar products are found below :

MAPDCC0001 MAPDCC0004 PD0409J5050S2HF 880157 HHS-109-PIN DC1417J5005AHF AFS14A30-2185.00-T3 AFS14A35-1591.50-T3 DS-323-PIN B39321R801H210 1A0220-3 JP510S LFB212G45SG8C341 LFB322G45SN1A504 LFL182G45TC3B746 SF2159E 30057 FM-104-PIN CER0813B MAPDCC0005 3A325 40287 41180 ATB3225-75032NCT BD0810N50100AHF BD2425J50200AHF C5060J5003AHF JHS-115-PIN JP503AS DC0710J5005AHF DC2327J5005AHF DC3338J5005AHF 43020 LFB2H2G60BB1C106 LFL15869MTC1B787 X3C19F1-20S XC3500P-20S 10013-20 SF2194E CDBLB455KCAX39-B0 TGL2208-SM, EVAL RF1353C PD0922J5050D2HF 1E1305-3 1F1304-3S 1G1304-30 B0922J7575AHF 2020-6622-20 TP-102-PIN TP-103-PIN