


Product Search Data Sheet

LFB212G45SG8C341

In Production Recommended RoHS REACH

Appearance & Shape





A : Directional Input Mark

All the technical data and information contained herein are subject to change without prior notice. (in mm)

Features

Ultra-small, low-profiled, lightweight chip filters based on ceramic multilayer technology.

Extremely ultra-small band-bass filters.

- 1. Ultra-small, low-profiled, lightweight band-pass filters.
- 2. Absolutely no adjustment required.
- 3. Reflow solderable.
- 4. Available in tape and reel packagings for automatic mounting.
- 5. Available in the 2400MHz to 2500MHz frequency range.

Packaging Information

Packaging	Specifications	Standard Packing Quantity
-	180mm Embossed Tape	4000

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Note: This datasheet may be out of date. Please download the latest datasheet of LFB212G45SG8C341 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=LFB212G45SG8C341



LFB212G45SG8C341

Note: This datasheet may be out of date. Please download the latest datasheet of LFB212G45SG8C341 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=LFB212G45SG8C341

Specifications

Applications	WLAN	
Nominal Center Frequency (fo)	2450.00MHz	
Bandwidth(BW)	fo±50.00MHz	
Insertion Loss in BW I)	1.80dB max. (at 25°C)	
Insertion Loss in BW II)	2.00dB max. (-40 to +85°C)	
Attenuation(Absolute Value) I)	26.0dB min. at 1200.00 to 1300.00MHz	
Attenuation(Absolute Value) II)	9.0dB min. at 2000.00MHz	
Attenuation(Absolute Value) III)	11.0dB min. at 3000.00MHz	
Attenuation(Absolute Value) IV)	22.0dB min. at 3600.00 to 3800.00MHz	
Attenuation(Absolute Value) V)	29.0dB min. at 4800.00 to 5000.00MHz	
Attenuation(Absolute Value) VI)	29.0dB min. at 7200.00 to 7500.00MHz	
Characteristic Impedance (Nom.)	50Ω	
Power Capacity	500mW	
Operating Temperature Range	-40°C to 85°C	
L x W (size)	2.00x1.25mm	
Thickness(max.)	1.05mm	

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.






Product Search Data Sheet


LFB212G45SG8C341

Note: This datasheet may be out of date. Please download the latest datasheet of LFB212G45SG8C341 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=LFB212G45SG8C341

Product Data





Frequency Characteristics

Spurious Response

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



3 of 3

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Signal Conditioning category:

Click to view products by Murata manufacturer:

Other Similar products are found below :

MAPDCC0001 MAPDCC0004 PD0409J5050S2HF 880157 HHS-109-PIN DC1417J5005AHF AFS14A30-2185.00-T3 AFS14A35-1591.50-T3 DS-323-PIN B39321R801H210 1A0220-3 JP510S LFB212G45SG8C341 LFB322G45SN1A504 LFL182G45TC3B746 SF2159E 30057 FM-104-PIN CER0813B MAPDCC0005 3A325 40287 41180 ATB3225-75032NCT BD0810N50100AHF BD2425J50200AHF C5060J5003AHF JHS-115-PIN JP503AS DC0710J5005AHF DC2327J5005AHF DC3338J5005AHF 43020 LFB2H2G60BB1C106 LFL15869MTC1B787 X3C19F1-20S XC3500P-20S 10013-20 SF2194E CDBLB455KCAX39-B0 TGL2208-SM, EVAL RF1353C PD0922J5050D2HF 1E1305-3 1F1304-3S 1G1304-30 B0922J7575AHF 2020-6622-20 TP-102-PIN TP-103-PIN